

Command Summary

.....	6-150
ACTivate ACC CALL= <i>name</i> [PHONenumber= <i>phone-number</i>]	28-16
ACTivate ATM= <i>instance</i> CHANnel= <i>channel</i> OAMfunction=LOOpback TYpe=[F4EtelF4Seg F5EtelF5Seg]	8-22
ACTivate Flash COMPACTION	1-60
ACTivate IPSec CONVERToldsa [SA= <i>sa-id</i>]	45-45
ACTivate ISDN CALL= <i>name</i>	11-58
ACTivate L2TP CALL= <i>name</i>	37-12
ACTIVATE MIOX=x25t-interface CIRCUIT= <i>circuit-name</i> [USER={APPLE IP IPX PPP}]	12-39
ACTivate PORTAuth Port={ALL <i>port-name</i> } REAUTHENTICate [SUPPLicantmac= <i>macadd</i>]	4-18
ACTIVATE PPP=ppp-interface RXPKT= <i>hexstring</i>	9-48
ACTivate Q931=interface ASpid	11-59
ACTivate Q931=interface MESSage= <i>message</i> [DLC= <i>dlc-index</i>]	11-59
ACTivate SScript= <i>filename</i> [OUtput= <i>device</i>] [<i>parameters</i>]	34-6
ACTivate TRIGger= <i>trigger-id</i>	30-5
ACTIVATE X25C=interface TEST LCGN=0..15 LCN=0..128 REMOTE= <i>Remote-DTE-address</i> LOCAL= <i>Local-DTE-address</i> [ACTION={DTE DCE DXE}]	12-38
ADD ACC CALL= <i>name</i> ASyn= <i>asyn-number</i> [AUthentication={AUto NONE PAssword}] [CScript= <i>script-name</i>] [DIAL= <i>phone-number</i>] [DIRECTION={ANSwer BOTH ORiginate}] [DScript= <i>script-name</i>] [ENCapsulation={ADaptive AUto CSlip ENquire NONE OKPpp PPp SLip DIStil}] [IPPool={ <i>pool-name</i> NONE}] [LIne={Direct MODem}] [PPPTemplate= <i>template</i>] [REMotecall= <i>remote-call</i>] [RScript= <i>script-name</i>]	28-16
ADD ACC DOmainname= <i>domain-name</i>	28-19
ADD ACC SScript= <i>script-name</i> [LIne= <i>line-number</i>] [TEXT= <i>script-text</i>] [TEMplate= <i>script-name</i>]	28-20
ADD ALLas= <i>name</i> STRing= <i>substitution</i>	1-61
ADD APPlE CIRCUit= <i>circuit</i> PORT= <i>port</i>	31-22
ADD APPlE DLCi= <i>dlci</i> PORT= <i>port</i>	31-23
ADD APPlE PACKETFilter= <i>filter-id</i> [ENTry= <i>entry</i>] [SNEtwork={ <i>network-range</i> ANY}] [DNEtwork={ <i>network-range</i> ANY}] [SNOde={ <i>node-range</i> ANY}] [DNOde={ <i>node-range</i> ANY}] [SSOcket={ <i>socket-range</i> ANY}] [DSOcket={ <i>socket-range</i> ANY}] [DIRECTION={IN OUT}] [LOG={YES NO ON OFF TRUE FALSE}] ACTION={DENY ALLOW}	31-24
ADD APPlE PORT INTERface= <i>interface</i> [DEMAnd={ON OFF YES NO}] [HInt= <i>network:node</i>] [SEED= <i>seed</i>] [PACKETFilter={ <i>filter-id</i> NONE}] [ROUTEFilter={ <i>filter-id</i> NONE}] [ZONEFilter={ <i>filter-id</i> NONE}]	31-26
ADD APPlE ROUTe= <i>network</i> PORT= <i>port</i> [{NEXThop= <i>network:node</i> CIRCUit= <i>circuit</i> DLCI= <i>dlci</i> }] [HOPs= <i>hopcount</i>]	31-29
ADD APPlE ROUTEfilter= <i>filter-id</i> [ENTry= <i>entry</i>] NETWork= <i>network-range</i> [DIRECTION={IN OUT}] [LOG={YES NO ON OFF}] ACTION={DENY ALLOW}	31-30
ADD APPlE ZONE= <i>zone-name</i> PORT= <i>port</i> [DEFAULT]	31-31



ADD APPlE ZONEFilter= <i>filter-id</i> [ENTrY= <i>entry</i>] ZOne= <i>zone-name</i> [LOG={YES NO ON OFF}] ACtion={DENY ALLOW}	31-32
ADD ATM=0..9 CHANnel=1..30 SERViceclass={VBRNrt VBRrt} PCR=1..155000 SCR=1..155000 MBS=2..10000 [DESCRiption= <i>description</i>] [ENCapsulation={AAL5Snap LLC VCMux}] [VPI=0..255 VCI=32..1023]	8-23
ADD ATM=0..9 CHANnel=1..30 SERViceclass=CBR PCR=1..155000 [DESCRiption= <i>description</i>] [ENCapsulation={AAL5Snap LLC VCMux}] [VPI=0..255 VCI=32..1023]	8-23
ADD ATM= <i>instance</i> CHANnel= <i>channel</i> [SERViceclass=UBR] [PCR=0 32..155000] [DESCRiption= <i>description</i>] [ENCapsulation={AAL5Snap LLC VCMux}] [VPI=0..255 VCI=32..1023]	8-23
ADD BGP AGGregate= <i>prefix</i> [/0..32] [MASK= <i>mask</i>] [SUMmary={NO YES}] [ROUTEMap= <i>routemap</i>]	49-46
ADD BGP CONFEDerationpeer=1..65534	49-48
ADD BGP IMPort={INTERface OSPF RIP STatic} [ROUTEMap= <i>routemap</i>]	49-49
ADD BGP NETwork= <i>prefix</i> [/0..32] [MASK= <i>mask</i>] [ROUTEMap= <i>routemap</i>]	49-50
ADD BGP PEer= <i>ipadd</i> POLICYTemplate=1..30 REMoteas=1..65534 [AUthentication={MD5 NONE}] [DESCRiption= <i>description</i>] [EHops={DEFAult 1..255}] [PASSword= <i>password</i>]	49-51
ADD BGP PEer= <i>ipadd</i> REMoteas=1..65534 [AUthentication={MD5 NONE}] [CONNectretry={DEFAult 0..4294967295}] [DESCRiption= <i>description</i>] [EHops={DEFAult 1..255}] [HOLDtime={DEFAult 0 3..65535}] [INFIter={NONE 300..399}] [INPathfilter={NONE 1..99}] [INRoutemap= <i>routemap</i>] [KEEpalive={DEFAult 1..21845}] [LOCAl={NONE 1..15}] [MAXPREFIX={OFF 1..4294967295}] [MAXPREFIXAction={Terminate Warning}] [MINAsooriginated={DEFAult 0..3600}] [MINRouteadvert={DEFAult 0..3600}] [NEXthopself={NO YES}] [OUTFilter={NONE 300..399}] [OUTPathfilter={NONE 1..99}] [OUTRoutemap= <i>routemap</i>] [PASSword= <i>password</i>] [SENdcommunity={NO YES}]	49-51
ADD BGP PEERTemplate=1..30 [CONNectretry={DEFAult 0..4294967295}] [DESCRiption= <i>description</i>] [HOLDtime={DEFAult 0 3..65535}] [INFIter={NONE 300..399}] [INPathfilter={NONE 1..99}] [INRoutemap= <i>routemap</i>] [KEEpalive={DEFAult 1..21845}] [LOCAl={NONE 1..15}] [MAXPREFIX={OFF 1..4294967295}] [MAXPREFIXAction={Terminate Warning}] [MINAsooriginated={DEFAult 0..3600}] [MINRouteadvert={DEFAult 0..3600}] [NEXthopself={NO YES}] [OUTFilter={NONE 300..399}] [OUTPathfilter={NONE 1..99}] [OUTRoutemap= <i>routemap</i>] [SENdcommunity={NO YES}]	49-57
ADD BOOTp RELAy= <i>ipadd</i>	14-62
ADD BRIDGe FILter=1..99 [ENTrY= <i>entry</i>] [SAddress<sep1> <i>macadd</i>] [SMask= <i>macadd</i>] [DAddress<sep1> <i>macadd</i>] [DMask= <i>macadd</i>] [ENCapsulation<sep1>{802 Ethii Snap NOVell}] [Discriminator<sep1> <i>protocoltype</i>] [SizeZE<sep2>1..65535] [Offset=1..1500 Data<sep1> <i>datastring</i>] [TYpe<sep1>{UNICast MULticast BROadcast ANY}] Port={ALL NONE 1..32[,1..32]...}	24-18
ADD BRIDGe GROUp={groupname 1..32} [REclustering=0..15]	24-20
ADD BRIDGe PORT=1..32 INTERface= <i>interface</i> [CIRCuit= <i>circuit</i>]	24-21
ADD BRIDGe PROTOcol[= <i>protocolname</i> index] TYpe= <i>protocoltype</i> [PRIOrity= <i>priority</i>]	24-22
ADD BRIDGe STation= <i>macadd</i> PORT=1..32	24-24
ADD CLNS[= <i>virtual-router-id</i>] ADJacency= <i>nsap-system-id</i> CIRCuit= <i>circ-id</i> [ETHernetaddress= <i>macadd</i>] ..	48-12
ADD CLNS[= <i>virtual-router-id</i>] AREa= <i>nsap-area-address</i>	48-13
ADD CLNS[= <i>virtual-router-id</i>] CIRCuit= <i>circ-id</i> INTERface= <i>interface</i> [IIHpint=1..65535] [L1DEFmetricval=1..63] [L1DELmetricval=0..63] [L1EXPmetricval=0..63] [L1ERRmetricval=0..63] [L2DEFmetricval=1..63] [L2DELmetricval=0..63] [L2EXPmetricval=0..63] [L2ERRmetricval=0..63] [ISIS={ON OFF YES NO TRUE FALSE}] [L2Only={ON OFF YES NO TRUE FALSE}] [L1Priority=1..127] [L2Priority=1..127] [ESIS={ON OFF YES NO TRUE FALSE}] [ISConfint=1..65535] [PORT= <i>port</i>] [VLantag=1..4094]	48-13
ADD CLNS[= <i>virtual-router-id</i>] RA= <i>nsap-prefix</i> CIRCuit= <i>circ-id</i> SOURCE={NONE EXPLICIT}] [ETHernetaddress= <i>macadd</i>] [DEFMetricval=1..63] [DEFMType={INTERNAL EXTERNAL}] [DELMetricval=0..63] [DELMType={INTERNAL EXTERNAL}] [EXPMetricval=0..63] [EXPMType={INTERNAL EXTERNAL}] [ERRMetricval=0..63] [ERRMType={INTERNAL EXTERNAL}]	48-16
ADD DECnet EXclusion= <i>dntadd</i>	20-14
ADD DECnet INclusion= <i>dntadd</i>	20-15
ADD DECnet INTERface= <i>interface</i> [COST=1..25]	20-16

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

ADD DECNET LPN= <i>dntadd</i>	20-17
ADD DHCP POLIcy= <i>name</i> [ARPTImeout= <i>seconds</i>] [BOOTFileSize= <i>bootfilesize</i>] [BROADCASTaddress= <i>ipadd</i>] [COOKleserver= <i>ipadd,ipadd...</i>] [DNSServer= <i>ipadd,ipadd...</i>] [DOMAINname= <i>string</i>] [ETHERENcap={ON OFF}] [EXTENSIONpath= <i>string</i>] [FILE= <i>string</i>] [HOSTname= <i>string</i>] [IMPREssserver= <i>ipadd,ipadd...</i>] [INTMTu=68..65535] [IPForwarding={ENABLED DISABLED}] [IPMTU=576..65535] [IPPLAteau= <i>mtu,mtu...</i>] [IPTIMEout= <i>seconds</i>] [IPTTL= <i>ttl</i>] [LOGServer= <i>ipadd,ipadd...</i>] [LPRServer= <i>ipadd,ipadd...</i>] [MASKDiscovery={ON OFF}] [MASKSupplier={ON OFF}] [MERITdumpfile= <i>longstring</i>] [NAMEserver= <i>ipadd,ipadd...</i>] [NBDDservers= <i>ipadd,ipadd...</i>] [NBNameservers= <i>ipadd,ipadd...</i>] [NBNOdetype={B-node P-node M-node H-node}] [NBSCOpe= <i>string</i>] [NISDomain= <i>string</i>] [NIServers= <i>ipadd,ipadd...</i>] [NTPServers= <i>ipadd,ipadd...</i>] [POLICYFiltering= <i>ipadd,ipadd...</i>] [RESOURceserver= <i>ipadd,ipadd...</i>] [ROOTPath= <i>longstring</i>] [ROUTer= <i>ipadd,ipadd...</i>] [ROUTERDiscovery={ON OFF}] [ROUTERSolicit= <i>ipadd</i>] [SERVER= <i>ipadd</i>] [SERVERName= <i>server-name</i>] [SOURCerouting={ENABLED DISABLED}] [STATicroute= <i>ipadd,ipadd...</i>] [SUBLOCAL={ON OFF}] [SUBNetmask= <i>ipadd</i>] [SWAPServer= <i>ipadd</i>] [T1TIme= <i>seconds</i>] [T2TIme= <i>seconds</i>] [TCPGarbage={ON OFF}] [TCPKeepalive= <i>seconds</i>] [TCPTtl= <i>ttl</i>] [TIMEOffset= <i>utc-offset</i>] [TIMEServer= <i>ipadd,ipadd...</i>] [TRAILerencap={ON OFF}] [XDISplayservers= <i>ipadd,ipadd...</i>] [XFONTservers= <i>ipadd,ipadd...</i>]	35-5
ADD DHCP RANGE= <i>name</i> Address= <i>macadd</i> IP= <i>ipadd</i> [POLIcy= <i>name</i>]	35-11
ADD DHCP6 INTERface= <i>interface</i> POLIcy= <i>name</i>	36-10
ADD DHCP6 KEY=0..65535 [CLientid= <i>clientid</i>] [STRict={TRUE FALSE}]	36-11
ADD DHCP6 POLIcy= <i>name</i> [ANTIReplayenabled={TRUE FALSE}] [DNSServer= <i>ipv6add[,ipv6add]</i>] [DOMAINname= <i>domain-name[,...]</i>] [PDLease= <i>seconds</i>] [PREference=0..255] [SERVER= <i>ipv6add</i>] [T1TIme= <i>seconds</i>] [T2TIme= <i>seconds</i>] [REPLAywindowsize={32 64 128 256}]	36-12
ADD DHCP6 RANGE= <i>name</i> IP= <i>ipv6add</i> CLientid= <i>clientid</i> IAid= <i>iaid</i> [INTERface= <i>interface</i>]	36-13
ADD DVMrp INTERface= <i>interface</i> [DLC=1..1024] [METric=1..32] [TTLThreshold=1..255]	17-38
ADD FIREwall POLIcy= <i>policy-name</i> APPRule= <i>app-rule-id</i> ACTION={ALLOW DENY} INTERface= <i>interface</i> APPLICATION={FTP TELnet SMTP TIME DNS BOOTPS BOOTPC TFTP GOPHer FINGER WWW HTTP KERBeros RTELnet POP2 POP3 RTSP SNMPTRap SNMP VDOLive REALAudio REALVideo CUSEeme XING QUICKtime MMS BBMS} [COMmand={GET PUT}] [PORT= <i>port</i>]	41-31
ADD FIREwall POLIcy= <i>policy-name</i> DYNAMIC= <i>template</i> {FILE= <i>filename.txt</i> USER={username ANY NONE}}	41-33
ADD FIREwall POLIcy= <i>policy-name</i> HTTPFilter= <i>filename</i> [DIRECTION={IN OUT}]	41-33
ADD FIREwall POLIcy= <i>policy-name</i> INTERface= <i>interface</i> TYPE={PUBLIC PRIVATE} [METHOD={DYNAMIC PASSall}] [TRUSTPRIVATE={FALSE NO YES TRUE}] [UPNPTYPE={LAN WAN}]	41-36
ADD FIREwall POLIcy= <i>policy-name</i> LIST= <i>list-name</i> FILE= <i>filename</i> TYPE={IP ADDRESS}	41-38
ADD FIREwall POLIcy= <i>policy-name</i> NAT={ENHanced STANDARD} INTERface= <i>interface</i> [IP= <i>ipadd</i>] GBLInterface= <i>interface</i> [GBLIP= <i>ipadd[-ipadd]</i>]	41-39
ADD FIREwall POLIcy= <i>policy-name</i> PROXY={HTTP SMTP} INTERface= <i>interface</i> GBLInterface= <i>interface</i> DIRECTION={IN OUT BOTH} [IP= <i>ipadd</i>] [DAYS= <i>day-list</i>] [AFTER= <i>hh:mm</i>] [BEFORE= <i>hh:mm</i>]	41-41
ADD FIREwall POLIcy= <i>policy-name</i> RULE= <i>rule-id</i> ACTION={ALLOW DENY NAT NONat} INTERface= <i>interface</i> PROTOCOL={protocol ALL EGP GRE ICMP OSPF SA TCP UDP} [AFTER= <i>hh:mm</i>] [BEFORE= <i>hh:mm</i>] [DAYS={MON TUE WED THU FRI SAT SUN WEEKDAY WEEKEND} ,...] [ENCapsulation={NONE IPSec}] [GBLIP= <i>ipadd</i>] [GBLPort={ALL port[-port] service-name}] [GBLRemoteip= <i>ipadd[-ipadd]</i>] [IP= <i>ipadd[-ipadd]</i>] [LIST={list-name RADIUS}] [NATType={DOUBLE ENHanced REVERSE STANDARD}] [NATMask= <i>ipadd</i>] [PORT={ALL port[-port] service-name}] [REMoteip= <i>ipadd[-ipadd]</i>] [SOURCEport={ALL port[-port]}] [TTL= <i>hh:mm</i>]	41-43
ADD FIREwall POLIcy= <i>policy-name</i> SPAMsources= <i>filename</i>	41-50
ADD FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i> [COMPRESSION={DEFAULT ON OFF}] [ENCapsulation={DEFAULT IETF CISCO}] [ENCryption={DEFAULT ON OFF}]	10-26
ADD FRamerelay= <i>fr-interface</i> LI= <i>logical-interface</i> [TYPE={NBMA PTP}]	10-28
ADD GRE TUNnel REMote= <i>ipadd</i> [KEY={keyval NONE}]	29-12
ADD GRE= <i>gre-number</i> TARget= <i>ipadd</i> {INTERface= <i>interface</i> SOURCE= <i>ipadd</i> [SMask= <i>ipadd</i>] [DESTination= <i>ipadd</i>] [DMask= <i>ipadd</i>]} [ENTry= <i>entry-number</i>]	29-10
ADD IGMP Snooping ROUTERAddress= <i>ipaddr</i> [,...]	17-39



ADD IP ADVERTISE interface=interface [ADVERTISEaddress={ALL LIMITED}] [MAXadvertisementinterval=4..1800] [MINadvertisementinterval=3..MAXadvertisementinterval] [LIFETIME=MAXadvertisementinterval..9000]	14-63
ADD IP ARP=ipadd interface=interface [{CIRCUIT=miox-circuit DLCI=dlci ETHERnet=macadd PORT=port-number}]	14-64
ADD IP ASPATHlist=1..99 [ENTRY=1..4294967295] EXCLUDE=aspath-reg-exp	49-62
ADD IP ASPATHlist=1..99 [ENTRY=1..4294967295] INCLUDE=aspath-reg-exp	49-62
ADD IP COMMUNITYlist=1..99 [ENTRY=1..4294967295] EXCLUDE={INTERNET NOEXPORT NOADVERTISE NOEXPORTSubconfed 1..4294967295}[,...]	49-64
ADD IP COMMUNITYlist=1..99 [ENTRY=1..4294967295] INCLUDE={INTERNET NOEXPORT NOADVERTISE NOEXPORTSubconfed 1..4294967295}[,...]	49-64
ADD IP DNS [DOMAIN={ANY domain-name}] {INTERFACE=interface PRIMARY=ipadd [SECONDARY=ipadd]}	14-65
ADD IP EGP=ipadd	14-67
ADD IP FILTER=filter-number SOURCE=ipadd [SMASK=ipadd] [SPORT={port-name port-id}] [DESTINATION=ipadd [DMASK=ipadd]] [DPORT={port-name port-id}] [ICMPCode={icmp-code-name icmp-code-id}] [ICMPTYPE={icmp-type-name icmp-type-id}] [LOG={4..1600 Dump Header None}] [OPTIONS={False OFF ON NO True YES}] [PROTOCOL={protocol Any Egp Icmp Ospf Tcp Udp}] [SESSION={Any Established Start}] [SIZE=size] [ENTRY=1..255] {ACTION={INCLUDE EXCLUDE} POLICY=0..15 PRIORITY=P0..P7}	14-68
ADD IP HELPER DESTINATION=ipadd INTERFACE=interface PORT=port-number	14-74
ADD IP HOST=name IPADDRESS=ipadd	14-76
ADD IP INTERFACE=interface IPADDRESS={ipadd DHCP} [ADVERTISE={YES NO}] [BROADCAST={0 1}] [DIRECTEDbroadcast={False NO OFF ON True YES}] [FILTER={0..99 NONE}] [FRAGMENT={NO OFF ON YES}] [GRATUITOUSarp={ON OFF}] [GRE={0..100 NONE}] [IGMPProxy={OFF UPstream DOWNstream}] [INVERSEarp={ON OFF}] [MASK=ipadd] [METRIC=1..16] [MULTICAST={BOTH NO OFF ON RECEIVE SEND YES}] [OSPFmetric=1..65534] [POLICYfilter={100..199 NONE}] [PREFERENCElevel={-2147483648..2147483647 NOTDEFAULT}] [PRIORITYfilter={200..299 NONE}] [[PROXYarp={False NO OFF ON True YES STRICT DEFROUTE}] [RIPMetric=1..16] [SAMode={Block Passthrough}] [VJC={False NO OFF ON True YES}] [VLANTAG={1..4094 NONE}]	14-77
ADD IP LOCAL=[1..15][FILTER={filter-number NONE}] [GRE=[0..100 NONE]][IPADDRESS=ipadd] [POLICYFILTER={filter-numbering}] [PRIORITYFILTER={filter-number NONE}]	14-82
ADD IP NAT IP=ipadd [MASK=ipadd] [GBLIPAddress=ipadd] [GBLMASK=ipadd] [GBLPORT=port] [GBLINTERFACE=interface] [PORT=port] [PROTOCOL={protocol ALL EGP GRE ICMP OSPF SA TCP UDP}] ..	14-83
ADD IP PREFIXList=name ENTRY=1..65535 [ACTION={MATCH NOMATCH}] [MASKlength=range] [PREFIX=ipadd]	49-66
ADD IP RIP INTERFACE=interface [CIRCUIT=miox-circuit] [DLCI=dlci] [IP=ipadd] [NEXTHop=ipadd] [SEND={NONE RIP1 RIP2 COMPATIBLE}] [RECEIVE={NONE RIP1 RIP2 BOTH}] [DEMAND={False NO OFF ON True YES}] [AUTH={NONE PASSWORD MD5}] [PASSWORD=password] [STATICexport={YES NO}]	14-86
ADD IP ROUTE FILTER=[filter-id] IP=ipadd MASK=ipadd ACTION={INCLUDE EXCLUDE} [DIRECTION={RECEIVE SEND BOTH}] [INTERFACE=interface] [NEXTHop=ipadd] [POLICY=0..7] [PROTOCOL={ANY EGP OSPF RIP}]	14-90
ADD IP ROUTE TEMPLATE=name INTERFACE=interface NEXTHop=ipadd [CIRCUIT=miox-circuit] [DLCI=dlci] [METRIC=1..16] [METRIC1=1..16] [METRIC2=1..65535] [POLICY=0..7] [PREFERENCE=0..65535]	14-92
ADD IP ROUTE=ipadd INTERFACE=interface NEXTHop=ipadd [CIRCUIT=miox-circuit] [DLCI=dlci] [MASK=ipadd] [METRIC=1..16] [METRIC1=1..16] [METRIC2=1..65535] [POLICY=0..7] [PREFERENCE=0..65535] [TAG=1..65535]	14-88
ADD IP ROUTEMAP=routemap ENTRY=1..4294967295 [ACTION={INCLUDE EXCLUDE}]	49-68
ADD IP ROUTEMAP=routemap ENTRY=1..4294967295 [ACTION={INCLUDE EXCLUDE}] MATCH ASPath=1..99	49-68
ADD IP ROUTEMAP=routemap ENTRY=1..4294967295 [ACTION={INCLUDE EXCLUDE}] MATCH COMMUNITY=1..99 [EXACT={NO YES}]	49-68
ADD IP ROUTEMAP=routemap ENTRY=1..4294967295 [ACTION={INCLUDE EXCLUDE}] MATCH LOCALPREF=0..4294965295[-0..4294965295]	49-68

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAtch NEXThop=ipadd	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAtch ORIGin={EGP IGP INCOmplete}	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAtch PREFIXList=name	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAtch TAG=1..65535	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion=INCLude] SET ASPath={1..65534[,...]} ..	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion=INCLude] SET COMMunity={NOExport NOAdvertise NOEXPORTSubconfed 1..4294967295[,...]} [ADD={NO YES}]	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion=INCLude] SET LOCALpref=0..4294967295	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion=INCLude] SET MED={0..4294967295 REMOVE}	49-68
ADD IP ROUTEMap=routeMap ENTry=1..4294967295 [ACtion=INCLude] SET ORIGIN={IGP EGP INCOmplete}	49-68
ADD IP SA=sa-id INTERface=interface	14-94
ADD IP TRusted=ipadd	14-95
ADD IPV6 6TO4 IP=ipv4add	15-34
ADD IPV6 FILter=filter-id SORuce=ipv6add/prefix-length [ACtion={INCLude EXCLude}]PRiority=P0..P7 [DEStination=ipv6add/prefix-length] [DPort={port-name port-id ANY}] [ENTry=entry-number [ICMPCode={icmp-code-name icmp-code-id ANY}] [ICMptype={icmp-type-name icmp-type-id ANY}] [LOG={4..1950 Dump Header None}] [Options={YES NO ON OFF ENAbLe DISAbLe}] [PROTocol={protocol Any Egp Icmp Ospf Tcp Udp}] [SEssion={Any Established Start}][Size={size ANY}] [SPort={port-name port-id ANY}]	15-35
ADD IPV6 HOst=name IPAddress=ipv6add [INTERface=interface]	15-40
ADD IPV6 INTERface=interface IPAddress=ipv6add/prefix-length DHCP DHCPTEMP PD} [APPINTERface=app-interface[,...]] [DECrement={YES NO ON OFF ENAbLe DISAbLe}] [FILter=0..99] [HInt=ipv6add/prefix-length] [KEY=key-id] [PREFerred=1..4294967295 INFinite] [PRiorityfilter=200..299] [PUBLish={YES NO ON OFF ENAbLe DISAbLe}] [TYPe={ANYcast UNICast}] [VALid=1..4294967295 INFinite]	15-41
ADD IPV6 ND=ipv6add INTERface=interface ETHernet=macadd [ISRouter={YES NO}] [Port=port-number]	15-43
ADD IPV6 PREFIX=ipv6add/prefix-length INTERface=interface [AUTOonomous={YES NO}] [ONlink={YES NO}] [PREFerred=1..4294967295 INFinite] [VALid=1..4294967295 INFinite]	15-44
ADD IPV6 RIP INTERface=interface POIsonreverse={ON OFF True False}	15-45
ADD IPV6 ROute=ipv6add/prefix-length INTERface=interface [NEXThop=ipv6add] [METric=1..16] [PREFerence=0..65535]	15-46
ADD IPV6 TUNnel LOcal=ipv4add TArget=ipv4add [INTERface=tunnel-interface] [IPAddress=ipv6add] ...	15-48
ADD IPX CIRCUIT=circuit INTERFACE=interface NETWORK=network [COST=1..999] [DEMAND={ON OFF YES NO TRUE FALSE}] [DLCI=dhci] [ENCAPSULATION={802.2 802.3 ETHII SNAP}] [INRIP=filter-number NONE] [OUTRIP=filter-number NONE] [INSAP=filter-number NONE] [OUTSAP=filter-number NONE] [KEEPALIVE={ON OFF YES NO TRUE FALSE ENDLESSLY FOREVER INFINITE INFINITELY INDEFINITELY NONSTOP 1..1440}] [MIOXCIRCUIT=circuit-name] [RIPCHANGE={ON OFF YES NO TRUE FALSE}] [RIPTIMER=0..99999] [SAPCHANGE={ON OFF YES NO TRUE FALSE}] [SAPTIMER=0..99999] [SPXSPOOF={ON OFF YES NO TRUE FALSE ENDLESSLY FOREVER INFINITE INFINITELY INDEFINITELY NONSTOP 0..1440}] [SPXENDSPOOF={UPLINK DONOTHING}] [SPXCONFAL={UPLINK DONOTHING}] [TYPE20={ON OFF YES NO TRUE FALSE}]	19-30
ADD IPX EXCLUSION=network[:station]	19-34
ADD IPX INCLUSION=network[:station]	19-35



ADD IPX RIP=filter-number NETWORK=network ACTION={INCLUDE EXCLUDE} [ENTRY=entry-number]	19-36
ADD IPX ROUTE=network CIRCUIT=circuit NEXTHOP=network:station [HOPS=1..15] [COST=1..999]	19-37
ADD IPX SAP=filter-number SERVICE=service [TYPE=service-type] ACTION={INCLUDE EXCLUDE} [ENTRY=entry-number]	19-38
ADD IPX SERVICE=service ADDRESS=network:station:socket TYPE=service-type CIRCUIT=circuit [HOPS=1..15]	19-39
ADD ISDN CALL=name NUMber=number PRECedence={IN OUT} [ALNumber=number] [BUMPdelay=0..100] [CALLBACK={ON OFF YES NO True False}] [CALLINGNumber=number] [CALLINGSubaddress=calling-subaddress] [CBDelay=0..100] [CHECKCLI={OFF PRESent REQuired}] [CHECKSub={OFF LOCAL REMote}] [CHECKUser={OFF LOCAL REMote}] [CLList=0..99] [Direction={IN OUT BOTH}] [DOV={ON OFF YES NO True False}] [HOLDUP=0..7200] [INANY={ON OFF YES NO True False}] [INTPRef={NONE interface}] [INTREQ={NONE interface}] [KEEPUP={ON OFF YES NO True False}] [LOGIn={ALL NONE CHAP PAP-RADIUS PAP-TACACS RADIUS TACACS USER}] [MAXDURATION=0..36000] [OUTCLI={OFF CALLing INTERface NONumber}] [OUTSUB={OFF LOCAL REMote}] [OUTUSER={OFF LOCAL REMote}] [PASSword={NONE CLI CALLEdsub NAME USER}] [PPPTemplate=template] [PRIOrity=0..99] [RAte={56K 64K}] [REMotecall=name remote-number] [RN1=0..10] [RN2=0..5] [RT1=5..120] [RT2=300..1200] [SEARCHCLI={ON OFF YES NO True False CALled 0..99}] [SEARCHSub={OFF LOCAL REMote}] [SEARCHUser={OFF LOCAL REMote}] [SUBaddress=number] [USer={ATTach PPP}] [USERName={NONE CLI CALLEdsub NAME USER}]	11-60
ADD ISDN CLList=0..99 NUMBER=number	11-66
ADD ISDN DOMAINname=domain-name	11-67
ADD L2TP CALL=name TYPE={ASYNc ISDN Virtual} IP=ipadd REMotecall=name [DIAL=number] [Number={ON OFF STARTup}] [PASSword=password] [PRE13={ON OFF}] [PRECedence={IN OUT}] [Speed=speed] [SUBAddress=subaddress]	37-13
ADD L2TP IP=ipadd[-ipadd] PPPTemplate=ppp-template [NUMber={ON OFF STARTup}] [PRE13={ON OFF}]	37-15
ADD L2TP PASSword={password NONE} [IP=ipadd[-ipadd]]	37-16
ADD L2TP User={mapping ALL LOCAL NONE REMote} Action={DATABase DNSLookup IGNore RADIUS} [IP=ipadd] [PORT=port] [NUMber={ON OFF}] [PASSword=password] [PRE13={ON OFF}] [PREFIX=prefix] [TIMEOut=timeout]	37-16
ADD LAPD=interface TEI=tei	11-67
ADD LAPD=interface XSPID=spid-index	11-68
ADD LAPD=interface XTEI=tei	11-68
ADD LOADBalancer RESource=resourcenam IP=ipadd PORT=0..65535 [RESPool=resourcepoolname] [WEIght=0..4294967295]	50-20
ADD LOADBalancer RESPool=resourcepoolname [FAIlLast={YES NO}] [SElectmethod={ROundrobin WLEastconnect WLOttery FAstestresponse}]	50-21
ADD LOADBalancer VIRTUalbalancer=virtualbalancename [Affinity={YES NO}] [COokieheader=cookiedetectorstring] [DOMAInname=domainname] [POLIcy=policyName] [PUBLICIp=ipadd] [PUBLICPort=0..65535] [RESPool=resourcepoolname] [SSL={ON OFF}] [SSLKey=key-id] [SSLToresource={ON OFF}] [TYpe={ROute TCp SSL HTtp}]	50-22
ADD LOADBalancer VIRTUalbalancer=virtualbalancename HTTPErrorcode=httperrorcodelist	50-25
ADD LOG OUTput={Temporary output-id} [ACTION={Process Ignore}] [ALL] [DATE=[op]dd-mmm-yyyy] [DEvice=[op]device] [FIle=[op]filename] [FIlter=filter-id] [MASK=ipadd] [MSGtext=[op]string] [MODule=[op]module-id] [ORIGIn=ipadd] [REFerence=[op]string] [SEVerity=[op]0..7] [SOURceline=[op]line] [SUBType=[op]subtype-id] [TIme=[op]hh:mm:ss] [TYpe=[op]type-id]	33-12
ADD LOG RECeive={ipadd ANY} [ALLOW={False NO OFF ON True YES}] [MASK=ipadd] [PASSword={password NONE}] [PROTOcol={ALL BOTH NEW OLD SYSlog}]	33-15



ADD MIOX=x25t-interface CIRCUIT=circuit-name {DTEADDRESS=dteaddress PVC=1..4095} [CPAR=1..8] [ENCAP={APPLE IP IPX NULL MULTIPLE PPP}] [COMMENT=comment] COMP={ON OFF} [TCPCOMP={ON OFF}]	12-40
ADD NTP PEer= <i>ipadd</i>	27-7
ADD OSPF AREa={Backbone area-number} [AuthentIcation={NONE PASSword}] [STUBArea={ON OFF YES NO NSSA True False}] [STUBMetric=0..16777215] [SUMmary={SEND NONE OFF NO False}]	23-20
ADD OSPF HOSt= <i>ipadd</i> [METric=0..65535]	23-21
ADD OSPF INTErface= <i>interface</i> AREa={Backbone area-number} [BOOST1=0..1023] [DEadinterval=2..2147483647] [DEMAND={ON OFF YES NO True False}] [HELlointerval=1..65535] [PASSword=password] [POLLIinterval=1..2147483647] [PRIOrity=0..255] [RXmtinterval=1..3600] [TRansitdelay=1..3600] [Virtuallink= <i>router-id</i>]	23-22
ADD OSPF NEIghbour= <i>ipadd</i> PRIOrity=0..255	23-26
ADD OSPF RANGe= <i>ipadd</i> AREa={Backbone area-number} [MASK= <i>ipadd</i>] [EFFect={ADVertise DONotadvertise}]	23-27
ADD OSPF STUB= <i>ipadd</i> MASK= <i>ipadd</i> [METric=0..65535]	23-28
ADD PERM= <i>perm-name</i> LPORT= <i>lport</i> RPORT= <i>rport</i> IP= <i>ipadd</i>	22-13
ADD PIM BSRCandidate [PREference=0..255] [HASHMASKLENGTH=0..32] [BSMinterval={10..15000 DEFAULT}] [INTERFACE={local-interface vlan-interface}]	17-39
ADD PIM INTErface= <i>interface</i> [DLCi=1..1024] [DRPriority=0..4294967295] [ELectby={DRPriority IPaddress}] [HELlointerval={10..15000 DEFAULT 65535}] [MODE={Dense Sparse}] [SRCapable={Yes No}]	17-40
ADD PIM RPCandidate[= <i>rp-address</i>] GROUp= <i>group-address</i> [MASK= <i>ipaddress</i>] [PRIOrity=0..255] [ADVinterval={10..15000 DEFAULT}]	17-42
ADD PIM6 BSRCandidate [SCOpe=SITE GLOBAL ALL] [PREference=0..255]	18-24
ADD PIM6 INTErface= <i>interface</i> [DRPriority=0..4294967295] [ELectby={DRPriority IPaddress}] [HELlointerval={10..15000 DEFAULT 65535}] [MODE={Dense Sparse}] [SRCapable={Yes No}]	18-24
ADD PIM6 RPCandidate[= <i>rp-address</i>] GROUp= <i>ipv6address</i> [/prefixlength] [PRIOrity=0..255]	18-26
ADD PING POLl= <i>poll-id</i> IPaddress={ <i>ipadd</i> <i>ipv6add</i> % <i>interface</i> } [CRIticalinterval=1..65535] [DESCRiption= <i>poll-description</i>] [FALLcount=1..100] [Length=4..1500] [NORMalinterval=1..65535] [SIPEndpoint={ <i>ipadd</i> <i>ipv6add</i> } [TIMEOut=1..30] [UPCount=1..100] [SAMPlesize=1..100]	16-9
ADD PKI CERTificate= <i>name</i> LOCation={url localfile} [PASSword= <i>password</i>] [PROXYAddress={hostname <i>ipadd</i> }] [PROXYPort= <i>port</i>] [TRusted={True False YES NO ON OFF}] [TYpe={CA Self ENDentity EE}] [USERname= <i>username</i>]	46-15
ADD PKI CRL= <i>name</i> LOCation={url localfile} [PASSword= <i>password</i>] [PROXYAddress={hostname <i>ipadd</i> }] [PROXYPort=1..65535] [USERname= <i>username</i>]	46-16
ADD PKI LDaprepository= <i>name</i> LOCation= <i>ldap-url</i> [PASSword= <i>password</i>] [USERname= <i>username</i>]	46-17
ADD PPP ACSERVICE= <i>service-name</i> TEMPLATE= <i>ppp-template</i> [ACRADIUS={OFF ON}] [MAXSESSIONS=1..512] [VLAN={NONE 0..4094}]	9-53
ADD PPP=ppp-interface OVER=physical-interface [AUTHENTICATION={CHAP EITHER PAP NONE}] [AUTHMODE={IN OUT INOUT}] [CBDELAY=1..100] [CBMODE={ACCEPT OFF REQUEST}] [CBNUMBER=e164number] [CBOperation={E164NUMBER USERAUTH}] [COMPALGORITHM={PREDICTOR STACLZS}] [COMPRESSION={LINK OFF}] [CONFIGURE={value CONTINUOUS}] [ECHO={OFF ON period}] [LQR={ON OFF period}] [MAGIC={ON OFF}] [MODEM={ON OFF}] [NUMBER=number] [PREDCHECK={CRC16 CRCCITT}] [RECHALLENGE={ON OFF 360..3600}] [RESTART=time] [STACCHECK={LCB SEQUENCE}] [TERMINATE={value CONTINUOUS}] [TYPE={DEMAND PRIMARY SECONDARY}]	9-49
ADD RADius SERVER= <i>ipadd</i> SECRet= <i>secret</i> Port= <i>port-number</i> ACCPort= <i>port-number</i> [LOCAL={NONE 1..15}]	1-62
ADD SA= <i>sa-id</i> MEMber={LOCAL REMote} IPaddress= <i>ipadd</i> MASK= <i>ipadd</i>	45-46
ADD SCript= <i>filename</i> TEXT= <i>text</i> [Line= <i>line</i>]	34-7
ADD SNMP COMMUNITY= <i>name</i> [TRAPHOST= <i>ipadd</i>] [MANAGER= <i>ipadd</i>] [V1TRAPHOST= <i>ipadd</i>] [V2CTRAPHOST= <i>ipadd</i>]	38-23



ADD SNMP GROUP= <i>group-name</i> SECURITYLEVEL={AUTHNOPRIV NOAUTHNOPRIV AUTHPRIV [READVIEW= <i>view-name</i>] [WRITEVIEW= <i>view-name</i>] [NOTIFYVIEW= <i>view-name</i>]	38-24
ADD SNMP TARGETADDR= <i>address-name</i> IP= <i>target-ipadd</i> [UDP= <i>udp-port</i>] PARAMS= <i>params-name</i>	38-26
ADD SNMP TARGETPARAMS= <i>params-name</i> SECURITYLEVEL={NOAUTHNOPRIV AUTHNOPRIV AUTHPRIV} USER= <i>user-name</i>	38-27
ADD SNMP USER= <i>user-name</i> [GROUP= <i>group-name</i>] [AUTHPROTOCOL={NONE MD5 SHA}] [AUTHPASSWORD= <i>password</i>] [PRIVPROTOCOL={NONE DES}] [PRIVPASSWORD= <i>password</i>]	38-28
ADD SNMP VIEW= <i>view-name</i> {OID= <i>oid-tree</i> MIB= <i>mib-name</i> } [TYPE={INCLUDE EXCLUDE}]	38-29
ADD SQOS INTERface= <i>interface</i> DAR= <i>id-list</i>	6-86
ADD SQOS POLIcy=0..9999 TRafficclass= <i>id-list</i>	6-87
ADD SQOS TRafficclass=0..9999 CLASSifier= <i>id-list</i>	6-88
ADD SQOS TRafficclass=0..9999 DAR= <i>id-list</i>	6-89
ADD SQOS TRafficclass=0..9999 SUBClass= <i>id-list</i>	6-90
ADD SSH USER= <i>username</i> [PASSword= <i>password</i> KEYid= <i>key-id</i>] [IPaddress= <i>ipadd</i> <i>ipv6add</i>] [MASK= <i>mask</i>]	43-9
ADD STReam= <i>stream-name</i> Port= <i>port</i>	22-14
ADD STT= <i>sttname</i> LSYN= <i>localsyn</i> RSYN=0..7 IP= <i>ipadd</i> [DATALEN= <i>maxlength</i>]	13-4
ADD TACacs SERVER= <i>ipadd</i>	1-63
ADD TACPlus SERVer= <i>ipaddress</i> [Key= <i>key</i>] [PORT= <i>port</i>] [SINGLEconnection={Yes No}] [TIMEOUT=1..10][LOCAL={NONE 1..15}]	1-64
ADD TDM GROUp= <i>groupname</i> SLOTS= <i>slotlist</i>	32-8
ADD TPAD= <i>name</i> ASYN= <i>port-number</i>	39-17
ADD TRIGger= <i>trigger-id</i> SCRipt= <i>filename</i> ... [NUMBER= <i>index</i>]	30-6
ADD USEr RSO IP= <i>ipadd</i> [MASK= <i>ipadd</i>]	1-67
ADD USEr RSO IP= <i>ipadd</i> [- <i>ipadd</i>]	1-67
ADD USEr RSO IP= <i>ipv6add</i> /[<i>prefix-length</i>]	1-67
ADD USEr RSO IP= <i>ipv6add</i> [- <i>ipv6add</i>]	1-67
ADD USEr=login-name Login={True False ON OFF Yes No} PASSword= <i>password</i> [CALLingnumber= <i>number</i>] [CBNUMBER= <i>e164number</i>] [Description= <i>description</i>] [MASK= <i>ipadd</i>] [IPaddress= <i>ipadd</i>] [IPXnetwork= <i>network</i>] [NETmask= <i>ipadd</i>] [MTu=40..1500] [PRivilege={User MANager SEcurityofficer}] [TElnet={Yes No}]	1-65
ADD VLAN={ <i>vlannam</i> 1..4094} PORT={ <i>port-list</i> ALL} [FRAME={TAGged UNTAgged}]	2-13
ADD VLAN={ <i>vlan-name</i> 1..4094} PORT={ <i>port-list</i> ALL} [FRAME={TAGged UNTAgged}]	3-23
ADD VRRP= <i>vr-identifier</i> IPaddress= <i>ipadd</i>	47-11
ADD VRRP= <i>vr-identifier</i> MONItoredinterface= <i>monitored-interface</i> [Newpriority={1..254}]	47-12
ADD X25C HUNTGROUp= <i>huntnam</i> FORWARD= <i>ipadd</i>	12-42
ADD X25C ROUTE= <i>dteaddress</i> IPADDRESS= <i>ipadd</i> [INDEX= <i>route-index</i>]	12-43
ADD X25C=x25-interface DTEADDRESS= <i>dteaddress</i>	12-41
ADD X25T CPAR= <i>call-index</i> [COPY= <i>call-index</i>] [MAXDATA={128 256 512 1024}] [NUI= <i>nu</i>] [RMAXDATA={128 256 512 1024}] [RWINDOW=1..127] [TMAXDATA={128 256 512 1024}] [TWINDOW=1..127] [USERDATA= <i>hex-string</i>] [WINDOW=1..127]	12-44
Clear FLash TOTally	1-69
CONNECT ASYN= <i>asyn-number</i>	7-25
Connect ASYN= <i>port-number</i>	21-15
Connect <i>service-name</i>	21-15
COPY <i>filename1.ext filename2.ext</i>	1-69
CREate ATM=0..9 OVer= <i>phys-interface</i>	8-25
CREate CLASSifier=1..9999 [IPDScp={ <i>dscp-list</i> ANY}] [IPTOs={0..7 ANY}] [VLANPriority={ <i>priority-list</i> ANY}]	5-4



CREate CLASSifier=1..9999 [IINTERface= <i>interface</i> NONE] [IPDAddr={ <i>ipadd</i> [/0..32] <i>ipv6add</i> [/0..128] ANY}] [IPSAddr={ <i>ipadd</i> [/0..32] <i>ipv6add</i> [/0..128] ANY}] [IPDScp={ <i>dscp-list</i> ANY}] [IPTOs={0..7 ANY}] [IPFRAg={YES NO ANY}] [IPOptions={YES NO ANY}] [IPFLowlabel={ <i>flow-label-range</i> ANY}] [IPPRotocol={TCP UDP ICMp IGMp OSPf NONTcpudp ANY <i>ip-protocol</i> } [ICMptype={Any ECHO Rply Unreachable Quench Redirect ECHO Advertisement Solicitation Tlmeexceed Parameter TSTAMP TSTAMP Rply INFOREQ INFOREP ADDRREQ ADDRREP NAMEReq NAMERply <i>icmp-type</i> }] [ICMPCode={Any Filter FRAGMent FRAGReasm HOSTComm HOSTIsolated HOSTPrec HOSTREdirect HOSTRTos HOSTTos HOSTUNKnown HOSTUNReach NETComm NETREdirect NETRTos NETTos NETUNKnown NETUNReach NOptr PORTunreach PREcedent PROtunreach PTRproblem Sourceroute Ttl <i>icmp-code</i> }] [TCPFlags={{URG ACK RST SYN FIN},...} ANY}] [TCPDport={ <i>port-range</i> ANY}] [TCPSport={ <i>port-range</i> ANY}] [UDPdport={ <i>port-range</i> ANY}] [UDPSport={ <i>port-range</i> ANY}] 5-5
CREate CLASSifier=1..9999 [IINTERface= <i>interface</i> NONE] [EPort= <i>port</i> ANY] [IPort= <i>port</i> ANY] [SVlan={ <i>vlan-name</i> 1..4094 ANY}] [DVlan={ <i>vlan-name</i> 1..4094 ANY}] [VLANPriority={ <i>priority-list</i> ANY}] [ETHFormat={802.2 802.2-Tagged 802.2-Untagged Ethii ETHII-Tagged ETHII-Untagged Netwareraw NETWARERAW-Tagged NETWARERAW-Untagged Snap SNAP-Tagged SNAP-Untagged ANY}] [MACDaddr={ <i>macadd</i> ANY}] [MACSaddr={ <i>macadd</i> ANY}] [MACType={L2Ucast L2BMcast ANY}] [ATMVCi={ <i>vci-list</i> ANY}] [ATMVPI={ <i>vpi-list</i> ANY}] [DLCi={ <i>dldi-range</i> ANY}] [PPPIIndex=0..1023] [PPPProtocolid={ <i>ppp-protocol-id</i> IP IPv6 ANY}] [PROTocol={ <i>protocol-type</i> ARP IP IPv6 IPX ANY}] [IPDAddr={ <i>ipadd</i> [/0..32] <i>ipv6add</i> [/0..128] ANY}] [IPSAddr={ <i>ipadd</i> [/0..32] <i>ipv6add</i> [/0..128] ANY}] [IPDScp={ <i>dscp-list</i> ANY}] [IPTOs={0..7 ANY}] [IPFRAg={YES NO ANY}] [IPOptions={YES NO ANY}] [IPFLowlabel={0..1048575 ANY}] [IPPRotocol={TCP UDP ICMp IGMp OSPf NONTcpudp ANY <i>ip-protocol</i> } [ICMptype={Any ECHO Rply Unreachable Quench Redirect ECHO Advertisement Solicitation Tlmeexceed Parameter TSTAMP TSTAMP Rply INFOREQ INFOREP ADDRREQ ADDRREP NAMEReq NAMERply <i>icmp-type</i> }] [ICMPCode={Any Filter FRAGMent FRAGReasm HOSTComm HOSTIsolated HOSTPrec HOSTREdirect HOSTRTos HOSTTos HOSTUNKnown HOSTUNReach NETComm NETREdirect NETRTos NETTos NETUNKnown NETUNReach NOptr PORTunreach PREcedent PROtunreach PTRproblem Sourceroute Ttl <i>icmp-code</i> }] [TCPFlags={{URG ACK RST SYN FIN},...} ANY}] [TCPDport={ <i>port-range</i> ANY}] [TCPSport={ <i>port-range</i> ANY}] [UDPdport={ <i>port-range</i> ANY}] [UDPSport={ <i>port-range</i> ANY}] 5-4
CREate CONfig= <i>filename</i> 1-70
CREate DHCP POLIcy= <i>name</i> LEASetime={ <i>lease-time</i> INFinity} [INHerit= <i>name</i>] 35-11
CREate DHCP RANge= <i>name</i> IP= <i>ipadd</i> NUMber= <i>number</i> POLIcy= <i>name</i> [GATEway= <i>ipadd</i>] [PRObe={ARP ICMP}] 35-12
CREate DHCP6 POLIcy= <i>name</i> [INHerit= <i>name</i>] 36-14
CREate DHCP6 RANge= <i>name</i> IP= <i>ipv6add</i> [- <i>ipv6add</i>] POLIcy= <i>name</i> [TYPe={NORMAL TEMPorary PD}] 36-15
CREate ENCo KEY= <i>key-id</i> TYPe={AES128 AES192 AES256 DES 3DES2key 3DESInner GENeral RSA} [DEScRiption= <i>description</i>] [FIle= <i>filename</i>] [FORmat={HEX NIQ SSH}] [IPaddress= <i>ipadd</i>] [LENGth= <i>length</i>] [MODule= <i>module-id</i>] [{RANDom VALue= <i>value</i> }] 25-20
CREate ETH=0..9 Over= <i>interface</i> 7-26
CREate FIREwall POLIcy= <i>policy-name</i> 41-51
CREate FIREwall POLIcy= <i>policy-name</i> DYnamic= <i>template</i> 41-51
CREate FRamerelay= <i>fr-interface</i> OVER= <i>physical-interface</i> [DEFATencap={Appleoui Ietfoui}] [BECNLimit=2..4294967295] [BECNTimeout=1..4294967295] [CDETection={BECN CLLM BOTH}] [CTICK=1..60] [DECreasefactor={0.025 0.05 0.1 0.2}] [DEFCcompression={ON OFF}] [DEFENCapsulation={IETF CISCO}] [DEFEncryption={ON OFF}] [DROPOFFthreshold=1..100] [INCreasefactor={0.05 0.1 0.2}] [LMIscheme={LMIREV1 Q933A ANNEXA T1617B ANNEXB T1617D ANNEXD NONE}] [MAXTXQlength=1..4294967295] [NN1= <i>nn1</i>] [NN2= <i>nn2</i>] [NN3= <i>nn3</i>] [NT1= <i>nt1</i>] [RECOverytime=1..4294967295] 10-28



CREate H323 ENTry ENGiNE= <i>engine</i> HOSTip= <i>ipaddr</i> PHonenumbeR= <i>number</i> [Port= <i>tcpport</i>]	52-27
CREate H323 INTErface= <i>interface</i> PHonenumbeR= number [CAPABility={ALL PCMU PCMA G723R53 G723R63 G729A} ...] [CLIP={ON OFF}] [DSCP= <i>dscp</i> priority] [DTMFrelay={H245 RTP NONE}] [RTCP={ON OFF}] [TOS= <i>tos</i> priority]	52-26
CREate IP POOL= <i>pool-name</i> IP= <i>ipadd</i> [- <i>ipadd</i>]	14-96
CREate IPSeC BUNDlespecification= <i>bundlespecification-id</i> KEYmanagement={ISakmp MANual} STRing="bundle-string" [EXPIRYKbytes=1..2000000000] [EXPIRYSeconds=300..31449600]	45-46
CREate IPSeC POLIcy= <i>name</i> INTErface= <i>interface</i> ACtion={DEny IPsec PErmit} [IPVersion={4 6}] [BUNDlespecification= <i>bundlespecification-id</i>] [DFBit={SEt COpy CLear}] [GROup={0 1 2}] [ICmptype={list NDALL}] [IPROUtetemplate= <i>template-name</i>] [ISAkmpolicy= <i>isakmp-policy-name</i>] [KEYmanagement={ISakmp MANual}] [LADdress={Any <i>ipv4add</i> [- <i>ipv4add</i>] <i>ipv6add</i> /prefix-length <i>ipv6add-ipv6add</i>]} [LMAsk= <i>ipv4add</i>] [LName={Any system-name}] [LPort={Any OPaque port}] [PEERaddress={ <i>ipv4add</i> <i>ipv6add</i> Any DYnamic}] [POSition= <i>pos</i>] [RADdress={Any <i>ipv4add</i> [- <i>ipv4add</i>] <i>ipv6add</i> /prefix-length <i>ipv6add-ipv6add</i>]} [RMAsk= <i>ipv4add</i>] [RName={Any system-name}] [RPort={Any port OPaque}] [SASElectorfrompkt={ALL LADdress LPort NONE RADdress RPort TRANsportprotocol}] [SRCInterface= <i>interface</i>] [TRANsportprotocol={Any EGp ESp GRE ICmp OPaque OSpf RSvp TCp UDp protocol}] [UDPHearbeat={True False}] [UDPPort= <i>port</i>] [UDPTunnel={True False}] [USEPFSKey={True False}]	45-48
CREate IPSeC SASpecification= <i>spec-id</i> KEYmanagement={ISakmp MANual} PROTOcol={AH COmp ESp} [ANTIReplayenabled={True False}] [COMPAIg=LZS] [ENCAlg={3DES2key 3DESOuter 3DESInner DES AES128 AES192 AES256 NUL}] [ENCKey= <i>key-id</i>] [HASHAlg={DESMac MD5 NUL SHA}] [HASHKey= <i>key-id</i>] [INSPI= <i>spi</i>] [MODE={TRANsport TUNnel}] [OUTSPI= <i>spi</i>] [REPLAywindowsize={32 64 128 256}]	45-52
CREate IPV6 INTErface= <i>interface</i> [DUPtrans=1..16] [RETRans=0..4294967295]	15-49
CREate ISAkmp POLIcy= <i>name</i> PEer={ <i>ipv4add</i> <i>ipv6add</i> Any} [AUTHType={PREshared RSAEncr RSASig}] [DELETedelay=10] [DHExponentlength=160..1023] [ENCAlg={3DES2key 3DESInner 3DESOuter DES AES128 AES192 AES256}] [EXPIRYKbytes=1..1000] [EXPIRYSeconds=600..31449600] [GROup={0 1 2}] [HASHalg={SHa MD5}] [HEARtbeatmode={Both None Receive Send}] [HYBRIDxauth={ON OFF True False}] [IPVersion={4 6}] [KEY=0..65535] [LOCALID={ <i>ipv4add</i> <i>ipv6add</i> domainname user-domainname dist-name}] [LOCALRsaKey=0..65535] [MODE={MAIn AGGressive}] [MSGREtrylimit=0..1024] [MSGTImeout=1..86400] [NATTraversal={ON OFF True False}] [PHASE2xchglimit={None 1..1024}] [POLIcyFilename= <i>filename</i>] [PREnegotiate={ON OFF True False}] [REMOTEId={ <i>ipv4add</i> <i>ipv6add</i> domainname user-domainname dist-name}] [SENDDeletes={ON OFF True False}] [SENDNotify={ON OFF True False}] [SENDIdalways={ON OFF True False}] [SETCommitbit={ON OFF True False}] [SRCInterface= <i>interface</i>] [XAuth={Client Server NONE}] [XAUTHName= <i>username</i>] [XAUTHPasswd= <i>password</i>] [XAUTHType={GENeric RADIUS}]	45-53
CREate LAPB= <i>lapb-interface</i> OVER={SYNn ISDN-callname} [DOD={ON OFF YES NO}] [MAXDATA=1080..32792] [MODULUS={8 128}] [N2=0..65535] [ROLE={DCE DTE DXE}] [WINDOW=1..127] [RMAXDATA=1080..32792] [TMAXDATA=1080..32792] [T1=1..120] 500..10000] [T3=3..120]	12-45
CREate LOG OUTput={Temporary output-id} DESTination={Email Memory ASYN Router Syslog} [ASYN= <i>port-number</i>] [FACILITY={DEFAULT LOCAL1...LOCAL7}] [FORMAt={Full MSGOnly Summary}] [MAXQueueseverity= <i>severity</i>] [MESSages= <i>message-count</i>] [PASSword={password NONE}] [QUEueonly={False NO OFF ON True YES}] [SECure={False NO OFF ON True YES}] [SERVER= <i>ipadd</i>] [SYSlogformat=Extended Normal] [TO= <i>email-address</i>] [Zone={time-zone-name utc-offset}][LOCAL={NONE 1..15}]	33-17
CREate LPD= <i>queue-name</i> ASYN=port [Banner={ON OFF}] [Insertff={ON OFF}] [ExpandIf={ON OFF}]	22-15
CREate PKI CERTificate= <i>name</i> KEYpair= <i>id</i> SERialnumbeR= <i>number</i> [FORMAt=DER PEM BASE64] [Subject= <i>dist-name</i>]	46-18
CREate PKI ENRollmentrequest= <i>name</i> KEYpair= <i>key-id</i> [FORMAt={DER PEM BASE64}] [LOCation={domainname ipadd}] [PROTOcol={CMP MANual}] [REFerencenumbeR= <i>refnum</i>] [SECretvalue= <i>secretvalue</i>] [TYpe={PKCS10 PKIX}]	46-19

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

CREate PKI KEYUpdaterequest= <i>name</i> CERTificate= <i>name</i> KEYpair= <i>key-id</i> [LOCation={ <i>domainname</i> <i>ipadd</i> }]	46-20
CREATE PPP TEMPLATE= <i>template</i> [COPY= <i>template</i>] [AUTHENTICATION={CHAP EITHER PAP NONE}] [BAP={ON OFF}] [BAPMODE={CALL CALLBACK}] [CBDELAY=1..100] [CBMODE={ACCEPT OFF REQUEST}] [CBNUMBER= <i>e164number</i>] [CBOperation={E164NUMBER USERAUTH}] [COMPALGORITHM={PREDICTOR STACLZS}] [COMPRESSION={ON OFF LINK}] [DEBUGMAXBYTES=16..256] [DESCRIPTION= <i>description</i>] [DOWNRATE=0..100] [DOWNTIME= <i>time</i>] [ECHO={ON OFF <i>period</i> }] [ENCRYPTION={ON OFF}] [FRAGMENT={ON OFF}] [FRAGOVERHEAD=0..100] [IDLE={ON OFF <i>time</i> }] [INDATALIMIT={NONE 1..65535}] [IPPOOL={ <i>pool-name</i> NONE}] [IPREQUEST={ON OFF}] [LOGIN={ALL RADIUS TACACS USER}] [LQR={ON OFF <i>period</i> }] [MAGIC={ON OFF}] [MAXLINKS=1..64] [MRU={ON OFF 256..1656}] [MTU=256..1500 256..1492] [MULTILINK={ON OFF}] [NULLFRAGTIMER= <i>time</i>] [ONLINELIMIT={NONE 1..65535}] [OUTDALIMIT={NONE 1..65535}] [PASSWORD= <i>password</i>] [PREDCHECK={CRC16 CRCCITT}] [RECHALLENGE={ON OFF 360..3600}] [RESTART= <i>time</i>] [STACCHECK={LCB SEQUENCE}] [STARENTITY=1..255] [TERMINATE={ <i>value</i> CONTINUOUS}] [TOTALDALIMIT={NONE 1..65535}] [UPRATE=0..100] [UPTIME= <i>time</i>] [USERNAME= <i>username</i>]	9-62
CREATE PPP=ppp-interface OVER=physical-interface [AUTHENTICATION={CHAP EITHER PAP NONE}] [AUTHMODE={IN OUT INOUT}] [BAP={ON OFF}] [BAPMODE={CALL CALLBACK}] [CBDELAY=1..100] [CBMODE={ACCEPT OFF REQUEST}] [CBNUMBER= <i>e164number</i>] [CBOperation={E164NUMBER USERAUTH}] [COMPALGORITHM={PREDICTOR STACLZS}] [COMPRESSION={ON OFF LINK}] [CONFIGURE={ <i>value</i> CONTINUOUS}] [DEBUGMAXBYTES=16..256] [DESCRIPTION= <i>description</i>] [DOWNRATE=0..100] [DOWNTIME= <i>time</i>] [ECHO={ON OFF <i>period</i> }] [ENCRYPTION={ON OFF}] [FRAGMENT={ON OFF}] [FRAGOVERHEAD=0..100] [IDLE={ON OFF <i>time</i> }] [INDATALIMIT={NONE 1..65535}] [IPPOOL={ <i>pool-name</i> NONE}] [IPREQUEST={ON OFF}] [LQR={ON OFF <i>period</i> }] [MAGIC={ON OFF}] [MODEM={ON OFF}] [MRU={ON OFF 256..1656}] [NULLFRAGTIMER= <i>time</i>] [NUMBER= <i>number</i>] [ONLINELIMIT={NONE 1..65535}] [OUTDALIMIT={NONE 1..65535}] [PASSWORD= <i>password</i>] [PREDCHECK={CRC16 CRCCITT}] [RECHALLENGE={ON OFF 360..3600}] [RESTART= <i>time</i>] [STACCHECK={LCB SEQUENCE}] [STARENTITY=1..255] [TERMINATE={ <i>value</i> CONTINUOUS}] [TOTALDALIMIT={NONE 1..65535}] [TYPE={DEMAND PRIMARY SECONDARY}] [UPRATE=0..100] [UPTIME= <i>time</i>] [USERNAME= <i>username</i>]	9-55
CREate RSVP PROXY= <i>name</i> TYPE=PATH PATH= <i>ipadd</i> /[<i>port</i>] [PMask= <i>ipadd</i>] TSPEC= <i>tspec</i> [TIMEout=10..1800] SSession= <i>protocol,ipadd</i> /[<i>port</i> [- <i>port</i>]] [SMask= <i>ipadd</i>]	40-8
CREate RSVP PROXY= <i>name</i> TYPE=RESV INTERface= <i>interface</i> STYLE={WF SE FF} FLOWspec= <i>flowspec</i> SSession= <i>protocol,ipadd</i> /[<i>port</i> [- <i>port</i>]] [SMask= <i>ipadd</i>]	40-8
CREate SA= <i>sa-id</i> ENCKey= <i>key-id</i> SPI= <i>spi</i> [ENCAlg={DES 3DES2key 3DESInner}] [DIRECTION={IN OUT BOTH}]	45-58
CREate SERvice= <i>service-name</i> DESCRiption=" <i>description</i> " TYPE={Interactive TElBin Telnet} [IPAddress= <i>ipadd</i>] [VISible={ON OFF}]	21-16
CREate SIP INTERface= <i>interface</i> PHOnenumber= <i>number</i> DOWain= <i>domain</i> PROXYserver= <i>ipaddr</i> : <i>udpport</i> [<i>tcpport</i>][: <i>ipaddr</i> : <i>udpport</i> [<i>tcpport</i>]] [CAPability={ALL PCMU PCMA G723R53 G723R63 G729A}{,...}] [DSCP= <i>dscp</i> priority] [DTMFrelay={RTP NONE}] [LOCAtionserver= <i>ipaddr</i> : <i>udpport</i> [<i>tcpport</i>][: <i>ipaddr</i> : <i>udpport</i> [<i>tcpport</i>]] [PASSword={NONE <i>password</i> }] [RTPport= <i>udpport</i>] [TOS= <i>tos</i> priority] [USERName={NONE <i>username</i> }]	52-28
CREATE SNMP COMMUNITY= <i>name</i> [ACCESS={READ WRITE}] [TRAPHOST= <i>ipadd</i>] [MANAGER= <i>ipadd</i>] [OPEN={ON OFF YES NO TRUE FALSE}] [V1TRAPHOST= <i>ipadd</i>] [V2CTRAHOST= <i>ipadd</i>]	38-30
CREate SQOS DAR= <i>id-list</i> [CODEC={AUDIO VIDEO ANY}] [DESCRiption= <i>description</i>] [DSTIp={ <i>ipadd</i> /0..32 <i>ipv6add</i> /0..128}] [SRCIp={ <i>ipadd</i> /0..32 <i>ipv6add</i> /0..128}] [INACTivetimeout={1..3600 NONE}] [PROTOcol={SIP RTSP H323 ALL}] [H323Port=1..65535] [RTSPPort=1..65535] [SIPPort=1..65535]	6-91
CREate SQOS DSCPMap= <i>id-list</i> [DESCRiption= <i>description</i>]	6-93
CREate SQOS METer= <i>id-list</i> [DESCRiption= <i>description</i>] [IGNorebwclass={Yes No}] [MINbandwidth= <i>rate</i> [Kbps Mbps Gbps]] [MAXbandwidth= <i>rate</i> [Kbps Mbps Gbps]] [MINBUrstsize= <i>burstsize</i> [Bytes Kbytes Mbytes Gbytes]] [MAXBUrstsize= <i>burstsize</i> [Bytes Kbytes Mbytes Gbytes]] [TYPE={SRtcm TRtcm}]	6-94

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

CREate SQOS POLIcy= <i>id-list</i> [BWClass3action={DROP PAUSE NONE}] [DEFAulttrafficclass={0..9999 NONE}] [DESCRiption= <i>description</i>] [DSCPMaP={0..9999 NONE}] [IGNOREPrenatinfo={YES NO}] [METer={0..9999 NONE}] [PAUSEAction={NONE Log TRap BOth}] [PAUSETIme={1..30}] [REMarking={0..63 USEDscpmap NONE}] [REMARKVlanpri={0..7 NONE}] [SYSTEMTraffic={5..50}] [VIRTbw={ <i>bandwidth</i> [Kbps Mbps Gbps] NONE}] [WEIGhtscheduler={WRR DWrr}]	6-97
CREate SQOS RED= <i>id-list</i> [AVERaging=0..99] [DESCRiption= <i>description</i>] [START1=0..100] [STOP1=0..100] [DROP1=0..100] [START2=0..100] [STOP2=0..100] [DROP2=0..100] [START3=0..100] [STOP3=0..100] [DROP3=0..100]	6-100
CREate SQOS TRAfficclass= <i>id-list</i> [BWClass3action={DRop PAuse NONE}] [DESCRiption= <i>description</i>] [MAXQlen=1..1023] [METer={0..9999 NONE}] [PAUSEAction={NONE LOG TRap BOth}] [PAUSETIme={1..30}] [PREMARKBwcl={1..3 USEDscpmap}] [PREMARKDscp={0..63 USEDscpmap NONE}] [{PRIOrity=0..15 WEIght=0..100}] [QLIMITExceedaction={NONE Log TRap BOth}] [QUEUEDrop={Head Tail}] [RED={0..9999 NONE}] [REMarking=0..63 USEDscpmap NONE}] [REMARKVlanpri={0..7 NONE}] [VIRTbw={ <i>bandwidth</i> [Kbps Mbps Gbps] NONE}] [WEIGhtscheduler={WRR DWrr}]	6-102
CREate STAR= <i>entity-id</i> MODe={MAStEr SLAVe STAndby} ENCAlgorithm={DES 3DES2key 3DESInner}	44-12
CREate TDM GROUp= <i>groupname</i> INTERface= <i>interface</i> {SLOTs= <i>slotlist</i> UNStructured}	32-9
CREate TPAD= <i>name</i> OVER= <i>x25-interface</i> [CALLretry= <i>number-retries</i>] [CHECKSum={ON OFF YES NO}] [FAStdisconnect={ON OFF}] [ISDncall= <i>isdn-call-name</i>] [MAXconnections= <i>connections</i>] [MAXTransfers= <i>transfers</i>] [NOCarrierresponse={ON OFF}] [SILEntretry={ON OFF}] [Source={ASYNc TCP ALL}] [TCPport= <i>port</i>] [TRansfertype={MULTIThread MULTIVc NORMAl TRANSParent}]	39-17
CREate TRIGger= <i>trigger-id</i> CPU= <i>value</i> [DIRECTION={UP DOWN ANY}] [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> FIREWall={ALL DOSAttack FRAGattack HOSTscan PORTscan SMTPATTACK SMURfattack SYNAttack TCPAttack} [MODE={STARt END BOTH}] [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> INTERface= <i>interface</i> EVent={UP DOWN FAIL ANY} [CIRCuit= <i>miox-circuit</i>] [CP={APPLE ATCP BCP CCP DCP DNCP IPcp IPXcp LCP}] [DLCi= <i>dLCi</i>] [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> MEMOrY= <i>value</i> [DIRECTION={UP DOWN ANY}] [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> MODUle= <i>module</i> EVent= <i>event</i> [<i>module-parameters</i> ...] [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> PERiodic= <i>minutes</i> [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> REBoot={REStArT CRASH ALL} [AFTER= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [SCRIPT= <i>filename</i> ...] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate TRIGger= <i>trigger-id</i> TIme= <i>hh:mm</i> [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [SCRIPT= <i>filename</i> ...] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [STATE={ENABled DisABled}] [TEST={YES NO ON OFF True False}]	30-7
CREate VLAN= <i>vlanname</i> VID=2..4094	2-14
CREate VLAN= <i>vlan-name</i> VID=2..4094	3-24

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

CREate VRRP= <i>vr-identifier</i> OVER= <i>physical-interface</i> IPaddress= <i>ipadd</i> [ADINTERval=1..255] [ADOPTvip={ON OFF}] [AUTHentication={NONE PLAINtext}] [PASSword= <i>password</i>] [PORTMonitoring={ON OFF}] [STEPVAlue={ <i>stepvalue</i> PROportional}] [PREEmpt={ON OFF}] [PRIOrity=1..254]	47-13
CREATE X25C HUNTGROUP= <i>huntname</i> IPADDRESS= <i>ipadd</i> DTEADDRESS= <i>dteadd</i> [FORWARDTIME=1..360] [RECONNECTTIME=1..360]	12-48
CREATE X25C=x25-interface OVER=LAPBn [DEFPKT={128 256 512 1024 2048 4096}] [DEFTHROUGH={75 150 300 600 1200 2400 4800 9600}] [DEFWIN=2..7] [HGROUP= <i>huntname</i>] [INLCGN=0..15] [INLCN=0..128] [MAXACTIVE=0..128] [OUTLCGN=0..15] [OUTLCN=0..128] [PACKETSIZE={ON OFF}] [THROUGHPUT={ON OFF}] [TWOLCGN=0..15] [TWOLCN=0..128] [WINDOW={ON OFF}]	12-46
CREATE X25T=x25-interface OVER={LAPBn LAPDn} [MAXACTIVE=0..4095] [MODULUS={8 128}] [T20=1..360] [T21=1..360] [T22=1..360] [T23=1..360] [T24={1..360 OFF}] [T27={1..360 OFF}] [MINRECALL=1..360] [R20=0..65535] [R22=0..65535] [R23=0..65535] [R27=0..65535] [NPVC=0..4095] [DEFCPAR=0..8] [DTEADDRESS= <i>dteaddress</i>] [LIC=0..4095] [HIC=0..4095] [LTC=0..4095] [HTC=0..4095] [LOC=0..4095] [HOC=0..4095] [ROLE={DYNAMIC DCE DTE}]	12-49
DEACTivate ACC CALL= <i>name</i>	28-21
DEACTivate ISDN CALL={ <i>acnum</i> <i>name</i> }	11-69
DEACTivate L2TP CALL={ <i>name</i> <i>callid</i> }	37-18
DEACTIVATE MIOX=x25t-interface CIRCUIT= <i>circuit-name</i> [USER={APPLE IP IPX PPP}]	12-50
DEACTivate SScript= <i>filename</i>	34-8
DELeTe ACC CALL= <i>name</i> [ASYN= <i>asyn-number</i>]	28-22
DELeTe ACC DOMainname[= <i>domain-name</i>]	28-22
DELeTe ACC SScript= <i>script-name</i> [LIne= <i>line-number</i>]	28-23
DELeTe ALlas= <i>name</i>	1-71
DELeTe APPlE CIRCUit= <i>circuit</i> PORT= <i>port</i>	31-33
DELeTe APPlE DLCi= <i>dlci</i> PORT= <i>port</i>	31-34
DELeTe APPlE PACKETFilter= <i>filter-id</i> [ENTry= <i>entry</i>]	31-35
DELeTe APPlE PORT= <i>port</i>	31-35
DELeTe APPlE ROUTe= <i>network</i>	31-36
DELeTe APPlE ROUTEfilter= <i>filter-id</i> [ENTry= <i>entry</i>]	31-36
DELeTe APPlE ZONE= <i>zone-name</i> PORT= <i>port</i>	31-37
DELeTe APPlE ZONEFilter= <i>filter-id</i> [ENTry= <i>entry</i>]	31-38
DELeTe ATM=0..9 CHANnel=1..30	8-26
DELeTe BGP AGGRegate= <i>prefix</i> [MASK= <i>ipadd</i>]	49-73
DELeTe BGP CONFEDerationpeer=1..65534	49-74
DELeTe BGP IMPort={INTERface OSPF RIP STATIC}	49-75
DELeTe BGP NETwork= <i>prefix</i> [MASK= <i>ipadd</i>]	49-76
DELeTe BGP PEer= <i>ipadd</i>	49-77
DELeTe BGP PEERTemplate=1..30	49-77
DELeTe BOOTp RELAY= <i>ipadd</i>	14-96
DELeTe BRIDge FILter=1..99 [ENTry= <i>entry</i>]	24-25
DELeTe BRIDge GROUp={ <i>groupname</i> 1..32}	24-25
DELeTe BRIDge PORT=1..32	24-26
DELeTe BRIDge PROTOcol[= <i>protocolname</i> <i>index</i>]	24-26
DELeTe BRIDge STation= <i>macadd</i> PORT=1..32	24-26
DELeTe CLNS[= <i>virtual-router-id</i>] ADJacency= <i>nsap-system-id</i>	48-17
DELeTe CLNS[= <i>virtual-router-id</i>] AREa= <i>nsap-area-address</i>	48-18
DELeTe CLNS[= <i>virtual-router-id</i>] CIRCUit= <i>circ-id</i>	48-18
DELeTe CLNS[= <i>virtual-router-id</i>] CIRCUit= <i>circ-id</i> RA= <i>nsap-prefix</i>	48-19
DELeTe DECnet EXclusion={ <i>dntadd</i> ALL}	20-18



DELeTe DECnet INclusion={ <i>dntadd</i> ALL}	20-19
DELeTe DECnet INTERface= <i>interface</i>	20-20
DELeTe DECnet LPN={(<i>dntadd</i> ALL)}	20-21
DELeTe DHCP POLIcy= <i>name</i> [ARPTImeout] [BOOTFilesize] [BROADCastaddress] [COOKIeserver] [DNSServer] [DObainname] [ETHERENcap] [EXTENSionpath] [File] [HOSTName] [IMPRESsserver] [INTMTu] [IPForwarding] [IPMTU] [IPPLAteau] [IPTIMEout] [IPTTL] [LOGServer] [LPRServer] [MASKDiscovery] [MASKSupplier] [MERITdumpfile] [NAMEserver] [NBDDservers] [NBNAMEServers] [NBNOdetype] [NBSCOpe] [NISDomain] [NIServers] [NTPServers] [POLICYFiltering] [RESOURceserver] [ROOTPath] [ROUter] [ROUTERDiscovery] [ROUTERSolicit] [SERVER] [SERVERName] [SOURCerouting] [STATicroute] [SUBLOcal] [SUBNetmask] [SWAPServer] [T1TIme] [T2TIme] [TCPGarbage] [TCPKeepalive] [TCPTtl] [TIMEOffset] [TIMEServer] [TRAILerencap] [XDISplayservers] [XFONTservers]	35-13
DELeTe DHCP RANge= <i>name</i> IP= <i>ipadd</i>	35-17
DELeTe DHCP6 INTERface= <i>interface</i>	36-16
DELeTe DHCP6 KEY={0..65535}	36-16
DELeTe DHCP6 POLIcy= <i>name</i> [DNSServer] [DObainname] [PDLease] [PREFeRence] [SERVER] [T1TIme] [T2TIme]	36-17
DELeTe DHCP6 RANge= <i>name</i> IP= <i>ipv6add</i>	36-18
DELeTe DVMrp INTERface= <i>interface</i> [DLC=1..1024]	17-43
DELeTe File= <i>filename</i>	1-71
DELeTe FIREwall POLIcy= <i>policy-name</i> APPRule= <i>app-rule-id</i>	41-52
DELeTe FIREwall POLIcy= <i>policy-name</i> DYnamic= <i>template</i> {File= <i>filename.txt</i> USer={ <i>username</i> ANY} NONE}}	41-52
DELeTe FIREwall POLIcy= <i>policy-name</i> HTTPFilter= <i>filename</i> [DIRECTION={IN OUT}]	41-53
DELeTe FIREwall POLIcy= <i>policy-name</i> INTERface= <i>interface</i>	41-54
DELeTe FIREwall POLIcy= <i>policy-name</i> LISt= <i>list-name</i>	41-55
DELeTe FIREwall POLIcy= <i>policy-name</i> NAT={ENHanced STANDARD} INTERface= <i>interface</i> GBLIInterface= <i>interface</i> [IP= <i>ipadd</i>]	41-55
DELeTe FIREwall POLIcy= <i>policy-name</i> PROXY={HTTP SMTP} INTERface= <i>interface</i> GBLIInterface= <i>interface</i> DIRECTION={IN OUT BOTH} [IP= <i>ipadd</i>]	41-57
DELeTe FIREwall POLIcy= <i>policy-name</i> Rule= <i>rule-id</i>	41-58
DELeTe FIREwall POLIcy= <i>policy-name</i> SPAMsources= <i>filename</i>	41-58
DELeTe FIREwall SEssion={ <i>session-number</i> ALL}	41-59
DELeTe FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i>	10-31
DELeTe FRamerelay= <i>fr-interface</i> LI= <i>logical-interface</i>	10-32
DELeTe GRE TUNnel REMote= <i>ipadd</i>	29-13
DELeTe GRE= <i>gre-number</i> ENTry={ <i>entry-number</i> ALL}	29-13
DELeTe IGMPsNooping ROUTERAddress= <i>ipaddr</i> [,...]	17-44
DELeTe INSTall={TEMPorary PREFeRred DEFault}	1-72
DELeTe IP ADVERTISE INTERface= <i>interface</i>	14-97
DELeTe IP ARP= <i>ipadd</i>	14-97
DELeTe IP ASPATHlist=1..99 [ENTry=1..4294967295]	49-78
DELeTe IP COMMunitylist=1..99 [ENTry=1..4294967295]	49-79
DELeTe IP DNS [DObain={ANY <i>domain-name</i> }]	14-97
DELeTe IP EGP= <i>ipadd</i>	14-98
DELeTe IP FILTer=0..399 ENTry={ <i>entry-number</i> ALL}	14-99
DELeTe IP HELPer DESTination= <i>ipadd</i> INTERface= <i>interface</i> PORT= <i>port-number</i>	14-100
DELeTe IP HOSt= <i>name</i>	14-101
DELeTe IP INTERface= <i>interface</i>	14-101
DELeTe IP LOCal=1..15	14-102



DELeTe IP NAT IP= <i>ipadd</i> GLBIPAddress= <i>ipadd</i> [MASK= <i>ipadd</i>] [GBLMask= <i>ipadd</i>] [GBLPort= <i>port</i>] [Port= <i>port</i>] [PROToCol={ <i>protocol</i> ALL EGP GRE ICmp OSPF SA TCp UDp}]	14-103
DELeTe IP NAT IP= <i>ipadd</i> MASK= <i>ipadd</i> GBLInterface= <i>interface</i> [GBLMask= <i>ipadd</i>] [GBLPort= <i>port</i>] [Port= <i>port</i>] [PROToCol={ <i>protocol</i> ALL EGP GRE ICmp OSPF SA TCp UDp}]	14-103
DELeTe IP PREFIXList= <i>name</i> [ENTry=1..65535]	49-79
DELeTe IP RIP INTERface= <i>interface</i> [CIRCuit= <i>miox-circuit</i>] [DLCi= <i>dlci</i>] [IP= <i>ipadd</i>]	14-104
DELeTe IP ROUte FILter=1..100	14-106
DELeTe IP ROUte TEMPlate= <i>name</i>	14-107
DELeTe IP ROUte= <i>ipadd</i> MASK= <i>ipadd</i> INTERface= <i>interface</i> NEXThop= <i>ipadd</i>	14-105
DELeTe IP ROUTEMap= <i>routemap</i>	49-80
DELeTe IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295	49-80
DELeTe IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 MATCH={ASPath COMMunity NEXThop ORIGin PREFIXList TAG}	49-80
DELeTe IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 SET={ASPath COMMunity LOCALpref MED ORIGin TAG}	49-80
DELeTe IP SA= <i>sa-id</i> INTERface= <i>interface</i>	14-107
DELeTe IP TRusted= <i>ipadd</i>	14-108
DELeTe IPV6 6TO4 IP= <i>ipv4add</i>	15-50
DELeTe IPV6 FILter= <i>filter-id</i> ENTry={ <i>entry-number</i> ALL}	15-50
DELeTe IPV6 HOSt= <i>name</i>	15-51
DELeTe IPV6 INTERface= <i>interface</i> IPAddress= <i>ipv6add</i>	15-51
DELeTe IPV6 ND= <i>ipv6add</i> INTERface= <i>interface</i>	15-52
DELeTe IPV6 PREFIX= <i>ipv6add/prefix-length</i> INTERface= <i>interface</i>	15-53
DELeTe IPV6 RIP INTERface= <i>interface</i>	15-53
DELeTe IPV6 ROUte= <i>ipv6add</i> INTERface= <i>interface</i> NEXThop= <i>ipv6add</i>	15-54
DELeTe IPV6 TUNNel= <i>ipv6add</i> INTERface= <i>tunnel-interface</i>	15-55
DELeTe IPX CIRCUIT= <i>circuit</i>	19-41
DELeTe IPX EXCLUSION= <i>network[:station]</i>	19-41
DELeTe IPX INCLUSION= <i>network[:station]</i>	19-42
DELeTe IPX RIP= <i>filter-number</i> ENTry={ <i>entry-number</i> ALL}	19-43
DELeTe IPX ROUTE= <i>network</i>	19-44
DELeTe IPX SAP= <i>filter-number</i> ENTry={ <i>entry-number</i> ALL}	19-44
DELeTe IPX SERVICE= <i>service</i> TYPE= <i>service-type</i>	19-45
DELeTe ISDN CALL= <i>name</i>	11-69
DELeTe ISDN CLIList=0..99 NUMber= <i>number</i>	11-70
DELeTe ISDN DOMainname[= <i>domain-name</i>]	11-70
DELeTe L2TP CALL= <i>name</i>	37-19
DELeTe L2TP IP= <i>ipadd</i> [- <i>ipadd</i>]	37-19
DELeTe L2TP PASSword [IP= <i>ipadd</i> [- <i>ipadd</i>] ALL]	37-20
DELeTe L2TP USer={ <i>mapping</i> ALL LOCAL NONE REMote}	37-20
DELeTe LAPD= <i>interface</i> TEI= <i>tei</i>	11-71
DELeTe LAPD= <i>interface</i> XSPid= <i>spid-index</i>	11-71
DELeTe LAPD= <i>interface</i> XTEI= <i>tei</i>	11-72
DELeTe LOADBAlancer RESource= <i>resourcenam</i>	50-26
DELeTe LOADBAlancer RESPool= <i>resourcepoolname</i>	50-27
DELeTe LOADBAlancer VIRTUAlbalancer= <i>virtualbalancename</i>	50-27
DELeTe LOADBAlancer VIRTUAlbalancer= <i>virtualbalancename</i> HTTPErrorcode= <i>httperrorcodelist</i>	50-29
DELeTe LOG OUTput={Temporary <i>output-id</i> } FILter={ALL <i>filter-id</i> }	33-21
DELeTe LOG RECeive={ <i>ipadd</i> ANY}	33-21
DELeTe MAIL= <i>id</i>	1-73



DELETE MIOX=x25t-interface CIRCUIT=circuit-name	12-51
DELeTe NTP PEer= <i>ipadd</i>	27-7
DELeTe OSPF AREa={Backbone area-number}	23-29
DELeTe OSPF HOSt= <i>ipadd</i>	23-29
DELeTe OSPF INTErface= <i>interface</i>	23-30
DELeTe OSPF NEIghbour= <i>ipadd</i>	23-31
DELeTe OSPF RANge= <i>ipadd</i>	23-31
DELeTe OSPF STUB= <i>ipadd</i> MASK= <i>ipadd</i>	23-32
DELeTe PERM= <i>perm-name</i>	22-16
DELeTe PIM BSRCandidate	17-44
DELeTe PIM INTErface= <i>interface</i> [DLCi=1..1024]	17-45
DELeTe PIM RPCandidate[= <i>rp-address</i>] GROUp= <i>group-address</i> [MASK= <i>ipaddress</i>]	17-45
DELeTe PIM6 BSRCandidate [SCOpe=SITE Global ALL]	18-27
DELeTe PIM6 INTErface= <i>interface</i>	18-27
DELeTe PIM6 RPCandidate[= <i>rp-address</i>] GROUp= <i>ipv6address</i> [/ <i>prefixlength</i>]	18-28
DELeTe PING POLl= <i>poll-id</i>	16-11
DELeTe PKI CERTificate={ <i>name</i> ALL}	46-21
DELeTe PKI CRL={ <i>name</i> ALL}	46-22
DELeTe PKI LDaprepository={ <i>name</i> ALL}	46-22
DELETE PPP ACSERVICE=service-name [VLAN={NONE 0..4094}]	9-70
DELETE PPP=ppp-interface OVER=physical-interface [NUMBER=number] [TYPE={DEMAND PRIMARY SECONDARY}]	9-69
DELeTe RADius SERVer= <i>ipadd</i>	1-73
DELeTe SA= <i>sa-id</i> MEMber={LOCAL REMOte} IPaddress= <i>ipadd</i> MASK= <i>ipadd</i>	45-59
DELeTe SCRipt= <i>filename</i> [LIne= <i>line</i>]	34-9
DELETE SNMP COMMUNITY=name [TRAPHOST= <i>ipadd</i>] [MANAGER= <i>ipadd</i>] [V1TRAPHOST= <i>ipadd</i>] [V2CTRAHOST= <i>ipadd</i>]	38-31
DELETE SNMP GROUP= <i>group-name</i>	38-32
DELETE SNMP TARGETADDR= <i>address-name</i>	38-32
DELETE SNMP TARGETPARAMS= <i>params-name</i>	38-33
DELETE SNMP USER= <i>user-name</i>	38-33
DELETE SNMP VIEW= <i>view-name</i> {OID= <i>oid-tree</i> MIB={ <i>mib-name</i> ALL}}	38-34
DELeTe SQOS INTErface= <i>interface</i> DAR={ <i>id-list</i> ALL}	6-106
DELeTe SQOS POLIcy=0..9999 TRafficclass={ <i>id-list</i> ALL}	6-107
DELeTe SQOS TRafficclass=0..9999 CLASSifier={ <i>id-list</i> ALL}	6-108
DELeTe SQOS TRafficclass=0..9999 DAR={ <i>id-list</i> ALL}	6-109
DELeTe SQOS TRafficclass=0..9999 SUBCclass={ <i>id-list</i> ALL}	6-110
DELeTe SSH USER= <i>username</i>	43-10
DELeTe STReam= <i>stream-name</i>	22-16
DELeTe STT= <i>sttname</i>	13-5
DELeTe TACacs SERVer= <i>ipadd</i>	1-74
DELeTe TACPlus SERVer= <i>ipaddress</i>	1-74
DELeTe TCP= <i>tcb</i>	14-109
DELeTe TDM GROUp= <i>groupname</i> SLOTS= <i>slotlist</i>	32-10
DELeTe TPAD= <i>name</i> ASYn= <i>port-number</i>	39-19
DELeTe TRIGger= <i>trigger-id</i> NUMber= <i>index</i>	30-13
DELeTe USEr RSO IP= <i>ipadd</i> [- <i>ipadd</i>]	1-76
DELeTe USEr RSO IP= <i>ipv6add</i> [/ <i>prefix-length</i>]	1-76
DELeTe USEr RSO IP= <i>ipv6add</i> [- <i>ipv6add</i>]	1-76



DELEte USEr= <i>login-name</i>	1-75
DELEte VLAN={ <i>vlanname</i> 1..4094} Port={ <i>port-list</i> ALL}	2-15
DELEte VLAN={ <i>vlan-name</i> 1..4094} PORT={ <i>port-list</i> ALL}	3-25
DELEte VRRP= <i>vr-identifier</i> IPaddress= <i>ipadd</i>	47-15
DELEte VRRP= <i>vr-identifier</i> MONitoredinterface= <i>monitored-interface</i>	47-16
DELETE X25C HUNTGROUp= <i>huntname</i> FORWARD= <i>ipadd</i>	12-53
DELETE X25C ROUTE= <i>dteaddress</i>	12-53
DELETE X25C=x25-interface DTEADDRESS= <i>dteaddress</i>	12-52
DELETE X25T CPAR= <i>call-index</i>	12-54
DESTroy ATM=0..9	8-26
DESTroy CLASSifier={ <i>rule-list</i> ALL}	5-14
DESTroy DHCP POLIcy= <i>name</i>	35-18
DESTroy DHCP RANge= <i>name</i>	35-18
DESTroy DHCP6 POLIcy= <i>name</i>	36-18
DESTroy DHCP6 RANge= <i>name</i>	36-19
DESTroy ENCo KEY= <i>key-id</i> LOCation=FLAsh	25-22
DESTroy ETH=0..9	7-27
DESTroy FIREwall POLIcy= <i>policy-name</i>	41-60
DESTroy FIREwall POLIcy= <i>policy-name</i> DYnamic= <i>template-name</i>	41-60
DESTroy FRamerelay= <i>fr-interface</i>	10-32
DESTroy H323 ENTry ENGIne= <i>engine</i> PHonenumber= <i>number</i> HOSTip= <i>ipaddr</i> [PORT= <i>tcpport</i>]	52-30
DESTroy H323 INTerface= <i>interface</i>	52-30
DESTroy IP POOL= <i>pool-name</i>	14-109
DESTroy IPSec BUNDlespecification= <i>bundlespecification-id</i>	45-59
DESTroy IPSec POLIcy= <i>name</i> [SABundle= <i>bundle-id</i>]	45-60
DESTroy IPSec SASpecification= <i>spec-id</i>	45-61
DESTroy IPV6 INTerface= <i>interface</i>	15-55
DESTroy ISAkmp POLIcy= <i>name</i>	45-61
DESTROY LAPB= <i>lapb-interface</i>	12-54
DESTroy LOG OUTput={Temporary <i>output-id</i> }	33-22
DESTroy LPD= <i>queue-name</i>	22-17
DESTroy PKI ENRollmentrequest={ <i>name</i> ALL}	46-23
DESTroy PKI KEYUpdaterequest={ <i>name</i> ALL}	46-23
DESTROY PPP TEMPLATE= <i>template</i>	9-71
DESTROY PPP=ppp-interface	9-71
DESTroy RSVP PROXY= <i>name</i>	40-11
DESTroy SA= <i>sa-id</i>	45-62
DESTroy SERvice= <i>service-name</i>	21-17
DESTroy SIP INTerface= <i>interface</i>	52-31
DESTROY SNMP COMMUNITY= <i>name</i>	38-35
DESTroy SQOS DAR= <i>id-list</i>	6-111
DESTroy SQOS DSCPMap= <i>id-list</i>	6-111
DESTroy SQOS METer= <i>id-list</i>	6-112
DESTroy SQOS POLIcy= <i>id-list</i>	6-112
DESTroy SQOS RED= <i>id-list</i>	6-113
DESTroy SQOS TRAfficclass= <i>id-list</i>	6-113
DESTroy STAR= <i>entity-id</i> [NETkey MKT]	44-13
DESTroy TDM GROUp= <i>groupname</i>	32-11
DESTroy TPAD= <i>name</i>	39-20
DESTroy TRIGger= <i>trigger-id</i>	30-14

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

DESTroy VLAN={ <i>vlannname</i> 2..4094 ALL}	2-16
DESTroy VLAN={ <i>vlan-name</i> 2..4094 ALL}	3-26
DESTroy VRRP={ <i>vr-identifier</i> ALL}	47-17
DESTROY X25C HUNTGROUp= <i>huntname</i>	12-55
DESTROY X25C=x25-interface	12-55
DESTROY X25T=x25-interface	12-55
DISable ACC CALL= <i>name</i>	28-23
DISable ACC CALL= <i>name</i> DEbug={UTILisation DEMAND PACKet PKT ASYn SCRipts DIALin ALL}	28-24
DISable ADSL={ <i>interface</i> ALL}	8-27
DISable ADSL={ <i>interface</i> ALL} DEbug={TRAINing ALL}	8-27
DISable APple	31-38
DISable APple DEbug={ALL AARP PACKet PKT ROUte ZIp ZOne}	31-39
DISable ASYn= <i>asyn-number</i>	7-27
DISable ATM=0..9 CHANnel={1..30 ALL}	8-28
DISable BGP AUTOsoftupdate	49-81
DISable BGP DEbug={ALL MSG STATE UPDATE}[,...] [PEer= <i>ipadd</i>]	49-82
DISable BGP PEer={ALL <i>ipadd</i> }	49-83
DISable BOOTp RELAy	14-109
DISable BRI=instance CTest	11-72
DISable BRI=instance Test[=test-number]	11-73
DISable BRI[=instance] DEbug={ERRORs INDICATIONs STATes EVENTs ALL}	11-73
DISable BRIDge	24-27
DISable BRIDge LEarning	24-27
DISable BRIDge SPanning	24-28
DISable CLNS[= <i>virtual-router-id</i>] CIRCUit= <i>circ-id</i>	48-19
DISable CLNS[= <i>virtual-router-id</i>] DEbug={ALL ENGDEBUG ENGTRACE PACKET PKT TRACE TRACEMORE}[,...]	48-20
DISable DECnet	20-21
DISable DHCP [BOOTp] [DEbug]	35-19
DISable DHCP6	36-19
DISable DHCP6 DEbug={PACKET STATE ALL}	36-19
DISable DHCP6 RAPid	36-20
DISable DVMrp	17-46
DISable DVMrp DEbug={ALL GRAft PRObe PRUne REPort}[,...] INTerface= <i>interface</i> [DLC=1..1024]	17-46
DISable ENCo COMPSTatistics	25-23
DISable ENCo DEbugging=PACKet	25-23
DISable FEAture={ <i>featurename</i> index}	1-77
DISable FIREwall	41-61
DISable FIREwall NOTify={ALL MAIL MANager PORT SNMP}	41-61
DISable FIREwall POLIcy= <i>name</i> [ACCcouting]	
[DEbug={ALL ARP HTTP PACKET PKT PROCESS PROXY SMTP UPNP}] [FRAGment={ICMP UDP OTHER}[,...]] [ICMP_Forwarding={ALL PARAMETER PING SOURCEQUENCH TIMEEXCEEDED Timestamp UNREACHABLE}][LOG={ALLOW DENY DENYDUMP EVERYDENY INAICMP INALLOW INAOOTHER INATCP INAUDP INDDICMP INDDOTHER INDDTCP INDDUDP INDDUMP INDENY INDICMP INDOTHER INDTCP INDUDP OUTAICMP OUTALLOW OUTAOTHER OUTATCP OUTAUDP OUTDDICMP OUTDDOTHER OUTDDTCP OUTDDUDP OUTDDUMP OUTDENY OUTDICMP OUTDOTHER OUTDTCP OUTDUDP}][Options={ALL RECORD_ROUTE SECURITY SOURCEROUTING Timestamp}] [PING]	41-62
DISable FIREwall POLIcy= <i>policy-name</i> HTTPCookies	41-64
DISable FIREwall POLIcy= <i>policy-name</i> IDentproxy	41-64
DISable FIREwall POLIcy= <i>policy-name</i> SMTPRelay	41-65



DISable FIREwall POLlcy= <i>policy-name</i> TCPsetupproxy	41-65
DISable FRamerelay= <i>fr-interface</i>	10-33
DISable FRamerelay= <i>fr-interface</i> CONgestioncontrol	10-34
DISable FRamerelay= <i>fr-interface</i> DEBUg={ALL CLLMPkt LMISate LMIPkt UTILisation}	10-34
DISable FRamerelay= <i>fr-interface</i> DLC={ <i>dlci</i> ALL} DEBUg={ALL ATKpkt BRGpkt CCPPkt CCPState CNGSTstate COMPPkt DLCState DNTPkt ECPpkt ECPState ENCO ENCpkt IPpkt IPXPkt PKT PLLCstate}}	10-35
DISable FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i>	10-35
DISable FRamerelay= <i>fr-interface</i> LI= <i>logical-interface</i> DEBUg=USER	10-37
DISable FRamerelay= <i>fr-interface</i> SLOWstart	10-37
DISable GRE	29-14
DISable GRE DEBUg	29-14
DISable GUI	1-78
DISable HTTP DEBUg={ALL AUTH MSG SESSion STATE}	1-78
DISable HTTP SERVer	1-79
DISable IGMPsNooping	17-47
DISable INTerface={ifIndex <i>interface</i> DYnamic} Llnktrap	7-28
DISable INTerface={ifIndex <i>interface</i> } DEBUg=PRIOrityqueue	7-28
DISable IP	14-110
DISable IP ADVertise	14-110
DISable IP ARP LOG	14-111
DISable IP DEBUg	14-111
DISable IP DNSRelay	14-111
DISable IP ECHoreply	14-112
DISable IP EGP	14-112
DISable IP EXPortrip	14-112
DISable IP FOFilter	14-113
DISable IP FORwarding	14-114
DISable IP HELper	14-114
DISable IP ICMPrepy[={ALL NETunreach HOSTunreach REDirect}]	14-115
DISable IP IGMP	17-48
DISable IP IGMP ALLGroup=[<i>port-list</i> ALL]	17-48
DISable IP IGMP DEBUg	17-49
DISable IP IGMP INTerface= <i>interface</i> [DLC=1..1024]	17-49
DISable IP INTerface= <i>interface</i>	14-115
DISable IP NAT [FRagment={ICMP UDP OTHER}[,...]] [LOG={ALL FAILS INTCP INUDP OUTTCP OUTUDP}[,...]]	14-116
DISable IP REMoteassign	14-117
DISable IP ROUte [CAChe COUnt MULTipath DEBUg]	14-117
DISable IP SRCRoute[={LOOSE STRICT ALL}]	14-118
DISable IPSec	45-62
DISable IPSec OLDSa INTerface= <i>interface</i>	45-63
DISable IPSec POLIcy={ALL <i>name</i> } DEBUg={ALL FIlter Packet TRace} [DIRECTION={ALL IN OUT}] [DISPLAY={ALL BUFFERHEADER DATA IPHEADER}] [RESult={ALL FAIL PASS}] [SElector={ALL LAddress LName LPort RAddress RName RPort TRANsportprotocol}] [WHERE={ALL IPSec PROTOcol}]	45-63
DISable IPV6	15-56
DISable IPV6 ADVertise [INTerface= <i>interface</i>]	15-56
DISable IPV6 DEBUg	15-57
DISable IPV6 MLD	18-28



DISable PRI=instance CTest[=test-number]	11-75
DISable PRI=instance TEST[=test-number]	11-76
DISable PRI[=instance] DEBUg[={Errors Indications States Events ALL}]	11-76
DISable Q931=interface DEBUg={MDECODE MRAW SDLC SINTERFACE SSPID SSPIDFILE STATE TRACE}	11-77
DISable RADius DEBUg={ALL PKT DECODE ERROR} [,...]	1-80
DISable RELease= <i>release-name</i>	1-80
DISable RSVP	40-11
DISable RSVP DEBUg[={ALL EVEnt PKT RESv STAtE}] [INTERface={ <i>interface</i> DYNAMIC}]	40-12
DISable RSVP INTERface={ <i>interface</i> DYNAMIC}	40-12
DISable RSVP PROXY[= <i>name</i>]	40-13
DISable RTElnet	21-18
DISable RTElnet DEBUg={ALL CONFIg ERRORcode OPTions TRACE}	21-18
DISable SA= <i>sa-id</i> DEBUg={All Pkt Search}	45-66
DISABLE SNMP	38-35
DISABLE SNMP AUTHENTICATE_TRAP	38-35
DISABLE SNMP COMMUNITY= <i>name</i> TRAP	38-36
DISable SQOS	6-114
DISable SQOS DEBUg={ALL DAR DARData ENGine ERRor INFo MARK PKT}	6-114
DISable SSH SERVer	43-11
DISable SSH USER= <i>username</i>	43-11
DISable SSL DEBUg[={ALL PACKet STAtE TRAcE}]	51-8
DISable STAR DEBUgging	44-13
DISable SWItch AGEingtimer	2-16
DISable SWItch AGEingtimer	3-26
DISable SWItch DEBUg	2-16
DISable SWItch DEBUg={ARL DMA M6 PHY ALL}	3-27
DISable SWItch LEarning	3-27
DISable SWItch PORT={ <i>port-list</i> ALL}	2-17
DISable SWItch PORT={ <i>port-list</i> ALL} [AUTOMDI]	3-28
DISable SWItch PORT={ <i>port-list</i> ALL} [FLOW]	3-28
DISable SYN= <i>n</i>	7-29
DISable SYN= <i>n</i> DEBUg	7-30
DISable SYStem SECurity_mode	1-81
DISable TACacs DEBUg={ALL PKT DECode ERRor} [,...]	1-81
DISable TACPlus	1-82
DISable TACPlus DEBUg	1-82
DISable TELnet SERver	14-118
DISABLE TELnet SERver	21-19
DISable TEST INTERface= <i>interface</i>	26-11
DISable TPAD= <i>name</i> DEBUg	39-21
DISable TPAD[= <i>name</i>]	39-21
DISable TRIGger[= <i>trigger-id</i>]	30-14
DISABLE UPNP	42-11
DISABLE UPNP FWPOLICY= <i>name</i> INTERFACE= <i>interface</i> ACTION= <i>action-name</i>	42-12
DISABLE UPNP L4PORT={0-65535}	42-13
DISable USEr RSO	1-83
DISable USEr= <i>login-name</i>	1-82
DISable VLAN={ <i>vlanname</i> 1..4094 ALL} DEBUg={PKT ALL}	2-17
DISable VLAN={ <i>vlan-name</i> 1..4094 ALL} DEBUg={PKT ALL}	3-28



DISable VOIP DEBUg={ALL IP H323 SIP PHONE RTP DSP}[,...] [ENGine= <i>engine</i>]	52-32
DISable VOIP PROToCol={H323 SIP} [ENGine= <i>engine</i>]	52-31
DISable VRRP={ <i>vr-identifier</i> ALL} DEBUg	47-18
DISable VRRP[= <i>vr-identifier</i> ALL]	47-17
DISABLE X25C= <i>x25-interface</i> DEBUg	12-56
Disconnect <i>session-number</i>	21-19
DUMP [ADDR= <i>address</i>] [LEN= <i>length</i>] [SIZE={BYTE LONG WORD}] [SPace={SD SP UD UP UR}]	1-83
Duration=dec(0-36000)	11-60
Duration=dec(0-36000)	11-95
EDit [<i>filename</i>]	1-85
ENAable PING POLl= <i>poll-id</i>	16-13
ENable	1-87
ENable ACC CALL= <i>name</i>	28-24
ENable ACC CALL= <i>name</i> DEBUg={UTILisation DEMaNd PAcket PKT ASYN SCRipts DIALin ALL} [ASYN= <i>asyn-number</i>]	28-24
ENable ADSl={ <i>interface</i> ALL}	8-28
ENable ADSl={ <i>interface</i> ALL} DEBUg={ALL TRaining} [TTy= <i>tty-num</i>]	8-29
ENable APPlE	31-39
ENable APPlE DEBUg={ALL AARP PAcket PKT ROUte ZIp ZOne}	31-39
ENable ASYN= <i>asyn-number</i>	7-30
ENable ATM= <i>instance</i> CHANnel={1..30 ALL}	8-30
ENable BGP AUTOsoftupdate	49-83
ENable BGP DEBUg={ALL MSG STAtE UPdate}[,...] [PEer= <i>ipadd</i>]	49-84
ENable BGP PEer={ALL <i>ipadd</i> }	49-85
ENable BOOTp RELAy	14-119
ENable BRI= <i>instance</i> CTest= <i>test-number</i>	11-78
ENable BRI= <i>instance</i> TEST= <i>test-number</i>	11-80
ENable BRI[= <i>instance</i>] DEBUg[={Errors Indications States Events ALL}]	11-79
ENable BRIDGe	24-28
ENable BRIDGe LEarning	24-28
ENable BRIDGe SPanning	24-29
ENable CLNS[= <i>virtual-router-id</i>] AREa= <i>nsap-area-address</i> SYStemid= <i>nsap-system-id</i>	48-20
ENable CLNS[= <i>virtual-router-id</i>] CIRCuit= <i>circ-id</i>	48-21
ENable CLNS[= <i>virtual-router-id</i>] DEBUg={ALL ENGDEBUg ENGTRACE PACKET PKT TRACE TRACEMORE}[,...]	48-22
ENable DECnet	20-22
ENable DHCP [BOOTp] [DEBUg]	35-19
ENable DHCP6	36-20
ENable DHCP6 DEBUg[={PACKET STATE ALL}]	36-20
ENable DHCP6 RAPid	36-21
ENable DVMrp	17-51
ENable DVMrp DEBUg={ALL GRAft PRObe PRUne REPort}[,...] INTerface= <i>interface</i> [DLC=1..1024]	17-51
ENable ENCo COMPStatistics	25-23
ENable ENCo DEBUgging=PAcket	25-24
ENable FEAture= <i>featurename</i> PASSword= <i>password</i>	1-88
ENable FIREwall	41-66
ENable FIREwall NOTify={ALL MAIL MANager PORT SNMP}[,...] [Port= <i>port-number</i>] [TO= <i>address</i>]	41-66



ENABle FIREwall POLIcy= <i>policy-name</i> [ACCounting] [DEBUg={ALL ARP HTTP PACKET PKT PROCESS PROXY SMTP RADIus TCP UPNP}] [FRAgment={ICMP UDP OTHER}{,...}] [ICMP_Forwarding={ALL PARAMETER PING SOURCEQUENCH TIMEEXCEEDED Timestamp UNREACHABLE}] [LOG={ALLOW DENY DENYDUMP EVERYDENY INAICMP INALLOW INAOTHER INATCP INAUDP INDDICMP INDDOTHER INDDTCP INDDUDP INDDUMP INDENY INDICMP INDOTHER INDTCP INDUDP OUTAICMP OUTALLOW OUTAOTHER OUTATCP OUTAUDP OUTDDICMP OUTDDOTHER OUTDDTCP OUTDDUDP OUTDDUMP OUTDENY OUTDICMP OUTDOTHER OUTDTCP OUTDUDP}] [OPTions={ALL RECORD_ROUTE SECURITY SOURCEROUTE Timestamp}] [PING]	41-67
ENABle FIREwall POLIcy= <i>policy-name</i> HTTPCookies	41-70
ENABle FIREwall POLIcy= <i>policy-name</i> IDentproxy	41-70
ENABle FIREwall POLIcy= <i>policy-name</i> SMTPRelay	41-71
ENABle FIREwall POLIcy= <i>policy-name</i> TCPsetupproxy	41-71
ENABle FRamerelay= <i>fr-interface</i>	10-38
ENABle FRamerelay= <i>fr-interface</i> CONgestioncontrol	10-38
ENABle FRamerelay= <i>fr-interface</i> DEBUg={ALL CLLMPkt LMISate LMIPkt UTILisation} [ASyn= <i>port-number</i>]	10-38
ENABle FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i>	10-39
ENABle FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i> DEBUg={ALL ATKPkt BRGPkt CCPPkt CCPState CNGSTstate COMPPkt DLCState DNTPKt ECPPkt ECPState ENCO ENCPkt IPPKt IPXPkt PKT PLLCstate}} [ASyn= <i>port-number</i>]	10-40
ENABle FRamerelay= <i>fr-interface</i> LI= <i>logical-interface</i> DEBUg=USER [ASyn= <i>port-number</i>]	10-41
ENABle FRamerelay= <i>fr-interface</i> SLOWstart	10-42
ENABle GRE	29-14
ENABle GRE DEBUg	29-15
ENABle GUI	1-88
ENABle HTTP DEBUg={ALL AUTH MSG SESSion STATe}	1-89
ENABle HTTP SERVer	1-89
ENABle IGMP Snooping	17-52
ENABle INTerface={ <i>ifIndex</i> <i>interface</i> } DYnamic Lnktrap	7-31
ENABle INTerface={ <i>ifIndex</i> <i>interface</i> } DEBUg=PRIOrityqueue	7-31
ENABle IP	14-119
ENABle IP ADVertise	14-120
ENABle IP ARP LOG	14-120
ENABle IP DEBUg[=PACket]	14-120
ENABle IP DNSRelay	14-121
ENABle IP ECHoreply	14-121
ENABle IP EGP	14-121
ENABle IP EXPortrip	14-122
ENABle IP FOFilter	14-122
ENABle IP FORwarding	14-123
ENABle IP HEIper	14-123
ENABle IP ICMPPrely[={ALL NETunreach HOSTunreach REDirect}]	14-124
ENABle IP IGMP	17-53
ENABle IP IGMP ALLGroup=[<i>port-list</i> ALL]	17-53
ENABle IP IGMP DEBUg [DEStination={ALL <i>ipaddress</i> }] [SOURCEipaddress={ALL <i>ipaddress2</i> }]	17-53
ENABle IP IGMP INTerface= <i>interface</i> [DLC=1..1024]	17-54
ENABle IP INTerface= <i>interface</i>	14-124
ENABle IP NAT [FRAgment={ICMP UDP OTHER}{,...}] [LOG={ALL FAILS INTCP INUdp OUTTCP OUTUDP}{,...}]	14-125



ENABle IP REMoteassign	14-126
ENABle IP ROUte [CACHe COUnT MULTipath DEBug]	14-126
ENABle IP SRCRoute[={LOOSE STRICT ALL}]	14-127
ENABle IPSec	45-66
ENABle IPSec OLDsa INTERface= <i>interface</i>	45-67
ENABle IPSec POLIcy[= <i>name</i>] DEBUg={AL Filter PACKet TRAcE} [DIrection={AL IN OUT}] [DISPlay={AL BUFFERHEADER DATA IPHEADER}] [RESult={AL FAIL PASS}] [SELEctor={AL LADdress LNAme LPort RADdress RNAme RPort TRANsportprotocol}] [WHERe={AL IPSec PROTOcol}]	45-67
ENABle IPV6	15-58
ENABle IPV6 ADVertise [INTERface= <i>interface</i>]	15-58
ENABle IPV6 DEBUg	15-59
ENABle IPV6 MLD	18-30
ENABle IPV6 MLD DEBUg	18-31
ENABle IPV6 MLD INTERface= <i>interface</i> [QUERYversion={1 2}]	18-31
ENABle IPV6 MTUdiscovery	15-59
ENABle IPV6 RIP	15-60
ENABLE IPX	19-46
ENABLE IPX CIRCUIT= <i>circuit</i>	19-46
ENABle ISAKmp [LOCALRsakey= <i>key-id</i>] [POLICYServerenabled={ON OFF TRUE FALSE}] [POLICYFilename= <i>filename</i>] [UDPPort=1..65535]	45-69
ENABle ISAKmp DEBUg={AL DEFAULT PACKet PKT PKTRaw STATE TRAcE TRACEMore}	45-70
ENABle ISDN CALL= <i>name</i>	11-81
ENABle ISDN LOG	11-82
ENABle L2TP	37-22
ENABle L2TP DEBUg={ALL PKT STATE} {CALL[= <i>callid</i>] TUNNel[= <i>tunnelid</i>]}	37-23
ENABle L2TP SERVER={BOTH LAC LNS}	37-24
ENABle LDAP DEBUg	1-90
ENABle LOADBalancer	50-33
ENABle LOADBalancer DEBUg={AL HTTp Firewall REDun TRAcE}	50-33
ENABle LOADBalancer HEALThpings	50-34
ENABle LOADBalancer REDUNDancy	50-34
ENABle LOADBalancer RESource={ALL <i>resourcename</i> }	50-35
ENABle LOADBalancer VIRTUalbalancer={AL <i>virtualbalancename</i> }	50-36
ENABle LOG	33-24
ENABle LOG GENeration	33-24
ENABle LOG OUTput[={TEMPORARY <i>output-id</i> }]	33-24
ENABle LOG RECEption	33-25
ENABle LPD= <i>queue-name</i>	22-18
ENABle MAIL DEBUg	1-90
ENABLE MIOX=x25t-interface CIRCUIT= <i>circuit-name</i>	12-57
ENABle NTP	27-8
ENABle OSPF	23-35
ENABle OSPF DEBUg={ALL IFState NBRState PACKet STATE} [DETail={BRief HEADer LSAFull LSASummary}]	23-35
ENABle OSPF INTERface= <i>interface</i>	23-36
ENABle OSPF LOG	23-36
ENABle PIM	17-55
ENABle PIM DEBUg={ALL ASSERT BSR C-RP-ADV GRAft HELLO JOInt REGister STATerefresh}[,...]	17-55
ENABle PIM6	18-32



ENable PIM6 DEBug={ALL ASSERT BSR C-RP-ADV GRAFT HELLO JOIN REGISTER STATErefresh}{,...}	18-32
ENable PING POLl= <i>poll-id</i> DEBug	16-13
ENable PKI DEBug={ALL CERTTRACE CMDTRACE CRTDBTRACE CRTRUTRACE CRTVGSTATE CRTVGTRACE CRTVUSTATE CRTVUTRACE MPPACKET MPPKT MPSTATE MPTRACE OPHTTPTRACE OPLDAPTRACE OPPACKET OPPKT PACKET PKT STATE TRACE}{,...}	46-24
ENable PORTAuth	4-20
ENable PORTAuth DEBug={ALL PACket StAte} PORT={ALL <i>port-name</i> }	4-21
ENable PORTAuth PORT={ALL <i>port-name</i> } TYpe=Authenticator [CONTRol={AUTHorised AUTO UNauthorised}} [MAXReq=1..10] [MODE={MULTi Single}} [PIGgyback={TRue False}} [QUIETperiod=0..65535] [REAUTHENabled={TRue False}} [REAUTHMax=1..10] [REAUTHPeriod=1..86400] [SERVERTimeout=1..60] [SUPPTimeout=1..60] [TXperiod=1..65535]	4-22
ENable PORTAuth PORT={ALL <i>port-name</i> } TYpe=Both [AUTHPeriod=1..60] [CONTRol={AUTHorised UNauthorised AUTO}} [HELDPeriod=0..65535] [MAXReq=1..10] [MAXStart=1..10] [MODE={MULTi Single}} [PIGgyback={TRue False}} [QUIETperiod=0..65535] [REAUTHENabled={TRue False}} [REAUTHMax=1..10] [REAUTHPeriod=1..86400] [SERVERTimeout=1..60] [STARTperiod=1..60] [SUPPTimeout=1..60] [TXperiod=1..65535] [USERName= <i>login-name</i> PASSword= <i>password</i> [METHod={OTP[ENCryption={MD4 MD5}} STandard}}]]	4-22
ENable PORTAuth PORT={ALL <i>port-name</i> } TYpe=Supplicant [AUTHPeriod=1..60] [HELDPeriod=0..65535] [MAXStart=1..10] [STARTperiod=1..60] [USERName= <i>login-name</i> PASSword= <i>password</i> [METHod={OTP[ENCryption={MD4 MD5}} STandard}}]]	4-22
ENABLE PPP ACCESSCONCENTRATOR	9-75
ENABLE PPP TEMPLATE= <i>template</i> DEBUG={ALL AUTH BAPSTATE CALLBACK CTRLPKT DATAPKT DECODE DEMAND ENCO LCP LQR NCP PACKET PKT PPPOE UTILISATION}{,...} [ASYN= <i>port-number</i>] [TIMEOUT={NONE 1..4000000000}] [NUMPKTS={CONT 1..4000000000}]	9-78
ENABLE PPP=ppp-interface	9-75
ENABLE PPP=ppp-interface DEBUG={ALL AUTH BAPSTATE CALLBACK CTRLPKT DATAPKT DECODE DEMAND ENCO LCP LQR NCP PACKET PKT PPPOE UTILISATION}{,...} [ASYN= <i>port-number</i>] [TIMEOUT={NONE 1..4000000000}] [NUMPKTS={CONT 1..4000000000}]	9-76
ENable PRI=instance CTest=test-number	11-82
ENable PRI=instance TEST=test-number	11-84
ENable PRI[=instance] DEBug[={ERRORs Indications StAteS EVENts ALL}]	11-83
ENable Q931=interface ASPid=index[,index...]	11-85
ENable Q931=interface DEBug={MDECODE MRAW SDLC SINTERFACE SSPID SSPIDFILE STATE TRACE}	11-86
ENable RADIUS DEBug={ALL PKT DECODE ERROR} [,...]	1-91
ENable RElease= <i>release-name</i> [PASSword= <i>password</i>] NUMber= <i>release-number</i>	1-92
ENable RSVP	40-14
ENable RSVP DEBug[={ALL EVENt PKT RESv StAte}] [INTerface={ <i>interface</i> DYNAMIC}]	40-14
ENable RSVP INTerface={ <i>interface</i> DYNAMIC}	40-15
ENable RSVP PROXy[= <i>name</i>]	40-15
ENable RTelnet	21-20
ENable RTelnet DEBug={ALL CONFIg ERRORcode OPTions TRACE}	21-20
ENable SA= <i>sa-id</i> DEBug={All Pkt Search}	45-71
ENABLE SNMP	38-36
ENABLE SNMP AUTHENTICATE_TRAP	38-37
ENABLE SNMP COMMUNITY=name TRAP	38-37
ENable SQOS	6-115
ENable SQOS DEBug={ALL DAR DARDATA ENGine ERRor INFo MARK PKT}	6-115
ENable SSH SERVer HOSTkey= <i>key-id</i> SERVERkey= <i>key-id</i> [EXPIrytime= <i>hours</i>] [LOGintimeout= <i>seconds</i>]	43-12



ENABle SSH USER= <i>username</i>	43-13
ENABle SSL DEBUg[={ALL PACKet STATe TRAcE}]	51-9
ENABle STAR DEBUgging	44-14
ENABle STAR MKTTransfer= <i>sernum</i>	44-14
ENABle SWItch AGEingtimer	2-18
ENABle SWItch AGEingtimer	3-29
ENABle SWItch DEBUg [OUTput=CONSOLE]	2-18
ENABle SWItch DEBUg={ARL DMA M6 PHY ALL} [OUTPUT=CONSOLE] [TIMEOUT={1..4000000000 NONE}]	3-30
ENABle SWItch LEarning	3-31
ENABle SWItch PORT={ <i>port-list</i> ALL}	2-18
ENABle SWItch PORT={ <i>port-list</i> ALL} [AUTOMdi]	3-31
ENABle SWItch PORT={ <i>port-list</i> ALL} [FLOW]	3-31
ENABle SYN= <i>n</i>	7-32
ENABle SYN= <i>n</i> DEBUg	7-32
ENABle SYStem SECurity_mode	1-93
ENABle TACacs DEBUg={ALL PKT DECode ERRor} [,...]	1-94
ENABle TACPlus	1-94
ENABle TACPlus DEBUg	1-95
ENABle TELnet Server	14-127
ENABle TELnet Server	21-21
ENABle TEST INTERface= <i>interface</i> [TIme= <i>time</i> CONT] [MORE]	26-12
ENABle TPAD[= <i>name</i>]	39-22
ENABle TPAD[= <i>name</i>] DEBUg	39-22
ENABle TRIGger[= <i>trigger-id</i>]	30-15
ENABLE UPNP	42-13
ENABLE UPNP FWPOLICY= <i>name</i> INTERFACE= <i>interface</i> ACTION= <i>action-name</i>	42-14
ENABLE UPNP L4PORT={0-65535}	42-14
ENABle USEr RSO	1-95
ENABle VLAN={ <i>vlanname</i> 1..4094 ALL} DEBUg={PKT ALL} [OUTput=CONSOLE] [TIMEOut={1..4000000000 NONE}]	2-19
ENABle VLAN={ <i>vlan-name</i> 1..4094 ALL} DEBUg={PKT ALL} [OUTput=CONSOLE] [TIMEOut={1..4000000000 NONE}]	3-32
ENABle VOIP DEBUg={ALL IP H323 SIP PHONE RTP DSP}[,...] [ASYN= <i>port-number</i>] [ENGine= <i>engine</i>]	52-33
ENABle VOIP PROTOcol={H323 SIP} [ENGine= <i>engine</i>]	52-32
ENABle VRRP={ <i>vr-identifier</i> ALL} DEBUg	47-19
ENABle VRRP[= <i>vr-identifier</i> ALL}]	47-18
ENABLE X25C= <i>x25-interface</i> DEBUG	12-58
FINGER [<i>username</i>]@ <i>host</i> [@ <i>host</i>]... [DETail={Hlgh LOW}]	14-128
FLUsh LOG OUTput[={Temporary <i>output-id</i> }]	33-25
HELP [<i>topic</i>]	1-95
IF <i>string1</i> {EQ NE} <i>string2</i> THEN <i>commands</i> [ELSE <i>commands</i>] ENDIF	34-9
LOAD [METhod={HTTP WEB WWW}] [DELAy= <i>delay</i>] [DESTFile= <i>destfilename</i>] [DESTination={BOOTblock FLASH}] [{File SRCFile}= <i>filename</i>] [HTTPproxy={ <i>hostname</i> <i>ipadd</i> } [PASSword= <i>password</i>] [PROxyport=1..65535]] [SErver={ <i>hostname</i> <i>ipadd</i> <i>ipv6add</i> } [SERVPort={1..65535 DEFAult}] [USERName= <i>username</i>]	1-96
LOAD [METhod=LDAP] [ATTRibute={CERT CRL CACERT}] [BASEobject= <i>dist-name</i>] [DELAy= <i>delay</i>] [DESTFile= <i>destfilename</i>] [DESTination={BOOTblock FLASH}] [PASSword= <i>password</i>] [SErver={ <i>hostname</i> <i>ipadd</i> } [SERVPort={1..65535 DEFAult}] [USERName= <i>username</i>]	1-96
LOAD [METhod=NONE] [ASYN= <i>port</i>] [DELAy= <i>delay</i>] [DESTFile= <i>destfilename</i>] [DESTination={BOOTblock FLASH}] [{File SRCFile}= <i>filename</i>]	1-96



LOAD [METhod=TFtp] [DElay= <i>delay</i>] [DESTFile= <i>destfilename</i>] [DEStination={BOOTblock Flash}] [{File SRCFile}= <i>filename</i>] [SErver={hostname ipadd ipv6add}]	1-96
LOAD [METhod=ZModem] [ASyn= <i>port</i>] [DElay= <i>delay</i>] [DESTFile= <i>destfilename</i>] [DEStination={BOOTblock Flash}] [{File SRCFile}= <i>filename</i>]	1-96
LOGIn [<i>login-name</i>]	1-101
LOGoff	1-102
MAIL TO= <i>destination</i> {File= <i>filename</i> MESSAge= <i>message</i> } [SUBject= <i>subject</i>] [ETRN= <i>mail-domain</i>]	1-102
MODify ADDR= <i>address</i> Size={Byte Long Word} VAL= <i>value-list</i> [SPace={SD SP UD UP UR}]	1-104
PING [APPLEAddress=] <i>network.node</i> [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMber={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SAPpleaddress= <i>network.node</i>] [SCReenoutput={Off ON NO YES}] [TIMEOut=1..65535]	14-129
PING [IPAddress=]{ <i>ipadd ipv6add</i> [% <i>interface</i>] <i>host</i> } [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMber={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SIPAddress={ <i>ipadd ipv6add</i> }] [SCReenoutput={Off ON NO YES}] [TIMEOut=1..65535] [TOS=0..255]	14-129
PING [IPXAddress=] <i>network:station</i> [DElay= <i>seconds</i>] [LENGTH= <i>number</i>] [NUMBER={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SIPXaddress= <i>network:station</i>] [SCReenoutput={Off ON NO YES}] [TIMEOut=1..65535]	14-129
PING [OSIAddress=] <i>nsap</i> [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMber={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SOSIaddress= <i>nsap</i>] [SCReenoutput={Off ON NO YES}] [TIMEOut=1..65535] ...	14-129
PURge ACC	28-25
PURge ACC SScript={ <i>script-name</i> ALL}	28-25
PURge APPLE	31-40
PURge ASyn={ <i>asyn-number</i> ALL}	7-33
PURge BOOTp RELay	14-131
PURge BRIDge	24-29
PURge CLNS[= <i>virtual-router-id</i>]	48-23
PURge DECnet	20-22
PURge DVMrp	17-56
PURge File Translationtable={ALL UPdate}	1-105
PURge GRE	29-15
PURge IP	14-131
PURge IPSec	45-71
PURGE IPX	19-47
PURge LDAP	1-105
PURge LOG[={Temporary <i>output-id</i> }]	33-26
PURge NTP	27-8
PURge OSPF	23-37
PURge PIM	17-56
PURge PIM6	18-33
PURge PKI	46-25
PURge PORTAuth PORT={ALL <i>port-name</i> }	4-26
PURGE PPP	9-79
PURGE SNMP	38-38
PURge SQOS {DAR INTErface POLIcy TRAfficclass}	6-116
PURge TDM GROup	32-11
PURge TRIGger	30-15
PURge USER	1-106
Reconnect <i>session-number</i>	21-21
REName <i>src-filename dest-filename</i>	1-106
RESET ADSI={ <i>interface</i> ALL}	8-30
RESET ADSI={ <i>interface</i> ALL} COUnTer	8-31



RESET APPLE	31-40
RESET ASYn= <i>asyn-number</i>	7-33
RESET ASYn= <i>asyn-number</i> COUnters[={Diagnostic Interface Rs232}]	7-34
RESET ASYn= <i>asyn-number</i> History	7-34
RESET BGP PEer={ALL <i>ipadd</i> }	49-85
RESET BGP PEer={ALL <i>ipadd</i> } Soft={IN OUT AL}	49-86
RESET BRI= <i>instance</i>	11-91
RESET BRI[= <i>instance</i>] COUnters[={INterface BRI}]	11-91
RESET BRIDge	24-30
RESET CLNS[= <i>virtual-router-id</i>]	48-23
RESET CPU UTILisation	1-107
RESET DECnet	20-23
RESET DVMrp INterface= <i>interface</i> [DLC=1..1024]	17-57
RESET ETH= <i>n</i>	7-35
RESET ETH[= <i>n</i>] COUnters[={COLlision DIAGnostic DOT3stat INterface}]	7-35
RESET FRamerelay= <i>fr-interface</i>	10-42
RESET FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i>	10-44
RESET GRE	29-16
RESET GUI	1-107
RESET HTTP SERVer	1-107
RESET INterface[={ <i>ifIndex</i> <i>interface</i> }] COUnters	7-36
RESET IP	14-132
RESET IP COUnter={ALL ARP EGP ICmp INterface IP MULticast ROUte SNmp UDP}	14-132
RESET IP INterface= <i>interface</i>	14-133
RESET IPSec COUnter[={AH ALG COMp ESp MAIn SAD SETUP SPD}]	45-72
RESET IPSec POLicy= <i>name</i> COUnter	45-72
RESET IPSec SA= <i>sa-id</i> COUnter	45-73
RESET IPV6 NDcache	15-60
RESET IPX	19-48
RESET ISAkmp COUnters[={AGGressive GENeral HEARtbeat INFo IPSec MAIn NETwork QUick SAD SPD TRAnSACTION XDB}]	45-73
RESET LAPB= <i>lapb-interface</i>	12-58
RESET LOADBalancer [RESource={ALl <i>resourcename</i> }] [RESPool={ALL <i>resourcepoolname</i> }]	50-36
RESET LOAder	1-108
RESET LPD= <i>queue-name</i> [Entry= <i>entry-number</i>]	22-18
RESET NTP	27-8
RESET OSPF	23-37
RESET OSPF COUnter	23-38
RESET OSPF INterface= <i>interface</i>	23-38
RESET PERM= <i>perm-name</i>	22-19
RESET PIM INterface= <i>interface</i> [DLC=1..1024]	17-58
RESET PIM6 INterface= <i>interface</i>	18-34
RESET PING POLL= <i>poll-id</i>	16-14
RESET PORTAuth Port={ALL <i>port-name</i> } [SUPPLicantmac={ <i>macadd</i> }]	4-27
RESET PORTAuth Port={ALL <i>port-name</i> } MULTImib	4-27
RESET PPP=ppp-interface [COUNTER] [LINKCOUNTER={ONLINE INDATA OUTDATA TOTALDATA ALL}]	9-80
RESET PRI= <i>instance</i>	11-92
RESET PRI[= <i>instance</i>] COUnter[={DIAGnostic INterface LINK PRI STAtE}]	11-92
RESET Q931= <i>interface</i> [CALL={call-index ALL}]	11-93
RESET RSVP PROXY[= <i>name</i>]	40-16



RESET SQOS COunters CLASSifier[= <i>id-list</i>] [DIRECTION={In OUT TUNnel ALL}] [INTERface= <i>interface</i>] [TRafficclass= <i>id-list</i>]	6-117
RESET SQOS COunters DAR[= <i>id-list</i>] [DIRECTION={In OUT TUNnel}] [INTERface= <i>interface</i>]	6-117
RESET SQOS COunters POLlcy[= <i>id-list</i>] [DIRECTION={In OUT TUNnel}] [INTERface= <i>interface</i>]	6-117
RESET SQOS COunters TRafficclass[= <i>id-list</i>] [DIRECTION={In OUT TUNnel ALL}] [INTERface= <i>interface</i>]	6-117
RESET STReam= <i>stream-name</i>	22-19
RESET STT= <i>sttname</i>	13-6
RESET SWlTch	2-20
RESET SWlTch	3-32
RESET SYN= <i>n</i>	7-36
RESET SYN[= <i>n</i>] COunters[={INTERface SYN}]	7-37
RESET TEST INTERface	26-13
RESET TPAD= <i>name</i>	39-23
RESET USER[= <i>login-name</i>] [COUNTER[={ALL GLOBAL USER}]]	1-108
RESET VOIP TYpe={SW HW} [ENGine= <i>engine</i>]	52-34
RESET X25T=x25-interface	12-58
RESTART {REBoot ROuter} [CONfig={filename NONE}]	1-109
RRESET ENCo COunters={AES DES DH HARdware HMac IPSec MAC PRed QUeues RSa SSl STac USer UTil}	25-24
SET [Tlme= <i>time</i>] [DAtE= <i>date</i>]	1-126
SET ACC CALL= <i>name</i> [AUthentication={AUto None PasswOrd}] [CScript= <i>script-name</i>] [DIAL= <i>phone-number</i>] [DIRECTION={ANSwer BOTH ORiginate}] [DScript= <i>script-name</i>] [ENCapsulation={ADaptive AUto CSlip ENquire None OKPPp PPP SLip DIStill}] [IPPool={pool-name None}] [LIne={Direct Modem}] [PPPTemplate= <i>template</i>] [REMOtecall= <i>remote-call</i>] [RScript= <i>script-name</i>]	28-26
SET ACC CALL= <i>name</i> ASYn= <i>asyn-number</i> PHONenumber= <i>phone-number</i>	28-28
SET ACC SScript= <i>script-name</i> LIne= <i>line-number</i> [TExt= <i>script-text</i>] [AFter= <i>line-number</i>] [BEfore= <i>line-number</i>]	28-29
SET ADSl= <i>interface</i> [AUtoRetrain={ON OFF}] [CARRier=EC FDM] [MODE={ANALogloopback CELLloopback DIGitalloopback NORMal}] STandard={AUtoMatic T1.413 G.Dmt G.Lite}]	8-32
SET APPlE PACKETFilter= <i>filter-id</i> [ENTry= <i>entry</i>] [SNetwork={network-range ANY}] [DNetwork={network-range ANY}] [SNOde={node-range ANY}] [DNODE={node-range ANY}] [SSOcket={socket-range ANY}] [DSOcket={socket-range ANY}] [DIRECTION={In OUT}] [LOG={YES NO ON OFF TRUE FALSE}] ACTION={DENY ALLOW}	31-41
SET APPlE Port [DEMAND={ON OFF YES NO}] [HInt= <i>network:node</i>] [SEED= <i>seed</i>] [PACKETFilter={filter-id NONE}] [ROUTEFilter={filter-id NONE}] [ZONEFilter={filter-id NONE}]	31-43
SET APPlE ROUTEConvert={ON OFF YES NO}	31-45
SET APPlE ROUTEFILTER= <i>filter-id</i> ENTry= <i>entry</i> [NETWork= <i>network-range</i>] [DIRECTION={In OUT}] [LOG={YES NO ON OFF}] [ACTION={DENY ALLOW}]	31-46
SET APPlE ZONE= <i>zone-name</i> Port= <i>port</i> [DEFault]	31-47
SET APPlE ZONEFilter= <i>filter-id</i> ENTry= <i>entry</i> [ZONE= <i>zone-name</i>] [LOG={YES NO ON OFF}] [ACTION={DENY ALLOW}]	31-48
SET ASYn[= <i>asyn-number</i>] [ATtention={Break alphabetical control char ^ None}] [CDcontrol={Connect Ignore Online}] [DAtabits={5 6 7 8}] [DEFaultservice={ON OFF YES NO True False}] [DTRcontrol={Connect Off ON}] [Echo={ON OFF YES NO True False}] [Flow={Character HARdware None}] [History=0..99] [INFlow={Character HARdware None}] [IPaddress={ipadd None}] [IPXnetwork= <i>network</i>] [LOGin={ON Off YES NO True False}] [MAXOqlen=0..4294967295] [MTu=40..1500] [NAME= <i>name</i>] [OUTFlow={Character HARdware None}] [PAGE={0..99 OFF}] [PARity={Even Mark None Odd SPace}] [PRompt={prompt DEFault OFF}] [SECure={ON Off YES NO True False}] [SERvice={service-name None}] [SPEED={AUTO 75 110 134.5 150 300 600 1200 1800 2000 2400 4800 9600 14400 14.4K 19200 19.2K 2 8800 28.8K 38400 38.4K 57600 57.6K 115200 115.2K}] [STOpbits={1 2}] [TYpe={Dumb VT100}]	7-37



SET ATM= <i>instance</i> CHANnel= <i>channel</i> [SERViceclass={VBRNrt VBRrt}] [PCR=32..155000] [SCR=32..155000] [MBS=2..10000] [DEScRiption= <i>description</i>] [ENCapsulation={AAL5Snap LLC VCMux}] [VPI=0..255 VCI=32..1023]	8-34
SET ATM= <i>instance</i> CHANnel= <i>channel</i> [SERViceclass=CBR] [PCR=32..155000] [DEScRiption= <i>description</i>] [ENCapsulation={AAL5Snap LLC VCMux}] [VPI=0..255 VCI=32..1023]	8-34
SET ATM= <i>instance</i> CHANnel= <i>channel</i> [SERViceclass=UBR] [PCR=0 32..155000] [DEScRiption= <i>description</i>] [ENCapsulation={AAL5Snap LLC VCMux}] [VPI=0..255 VCI=32..1023]	8-34
SET BGP [CONfederationid={NONE 1..65534}] [LOCAlpref={DEFAult 0..4294967295}] [MED={NONE 0..4294967294}] [PREFExt={DEFAult 1..255}] [PREFInt={DEFAult 1..255}] [ROuterid= <i>ipadd</i>] [SELEction_timer=3..60] [TABlemap[= <i>routermap</i>]	49-87
SET BGP AGGregate= <i>prefix</i> [MASK= <i>ipadd</i>] [SUMmary={NO YES}] [ROUTEMap[= <i>routermap</i>]	49-90
SET BGP BACKoff[=0..100] [BASEtime=0..100] [CONSecutive=1..20] [MULtiplier=0..1000] [STep=0..1000] [TOTAlimit=0..1000]	49-91
SET BGP IMPort={INTerface OSPF RIP Static} [ROUTEMap[= <i>routermap</i>]	49-92
SET BGP MEMlimit[=0..100]	49-93
SET BGP PEer= <i>ipadd</i> [AUthentication={MD5 NONE}] [CONnectretry={DEFAult 0..4294967295}] [DEScRiption= <i>description</i>] [EHops={DEFAult 1..255}] [HOLdtime={DEFAult 0 3..65535}] [INFIter={NONE 300..399}] [INPathfilter={NONE 1..99}] [INROUTemap[= <i>routermap</i>] [KEEpalive={DEFAult 1..21845}] [LOCAl={NONE 1..15}] [MAXPREFIX={OFF 1..4294967295}] [MAXPREFIXAction={Terminate Warning}] [MINAsoriginated={DEFAult 0..3600}] [MINRouteadvert={DEFAult 0..3600}] [NEXthopself={NO YES}] [OUTFilter={NONE 300..399}] [OUTPathfilter={NONE 1..99}] [OUTROUTemap[= <i>routermap</i>] [PASSword= <i>password</i>] [REMoteas=1..65534] [SENdcommunity={NO YES}]	49-94
SET BGP PEer= <i>ipadd</i> [POLICYTemplate=1..30] [AUthentication={MD5 NONE}] [DEScRiption= <i>description</i>] [EHops={DEFAult 1..255}] [PASSword= <i>password</i>] [REMoteas=1..65534]	49-94
SET BGP PEer= <i>ipadd</i> POLICYTemplate=	49-94
SET BGP PEERTemplate=1..30 [CONnectretry={DEFAult 0..4294967295}] [DEScRiption= <i>description</i>] [HOLdtime={DEFAult 0 3..65535}] [INFIter={NONE 300..399}] [INPathfilter={NONE 1..99}] [INROUTemap[= <i>routermap</i>] [KEEpalive={DEFAult 1..21845}] [LOCAl={NONE 1..15}] [MAXPREFIX={OFF 1..4294967295}] [MAXPREFIXAction={Terminate Warning}] [MINAsoriginated={DEFAult 0..3600}] [MINRouteadvert={DEFAult 0..3600}] [NEXthopself={NO YES}] [OUTFilter={NONE 300..399}] [OUTPathfilter={NONE 1..99}] [OUTROUTemap[= <i>routermap</i>] [SENdcommunity={NO YES}]	49-100
SET BOOTp MAXHops=1..16	14-133
SET BRI= <i>instance</i> [ACTivation={NOrmal ALways}] [ISDNSlots=slot-list] [MODE={ISDN TDM MIXed}] [TDMSlots=slot-list]	11-93
SET BRIDgE AGEingtimer=10..1000000	24-30
SET BRIDgE FILter=1..99 ENTry= <i>entry</i> [SAddress<sep1> <i>macadd</i>] [SMask= <i>macadd</i>] [DAddress<sep1> <i>macadd</i>] [DMask= <i>macadd</i>] [ENCapsulation<sep1>{802 EthII Snap NOVell}] [Discriminator<sep1> <i>protocoltype</i>] [Size<sep2>1..65535] [Offset=1..1500 Data<sep1> <i>datastring</i>] [TYpe<sep1>{UNICAST MULTICAST BROADCAST ANY}] Port={ALL NONE 1..32[,1..32]...}	24-30
SET BRIDgE GROup={groupname 1..32} REclustering=0..15	24-33
SET BRIDgE Port=1..32 ACcesspriority=0..7 [Pathcost=1..1000000] [PRIOrity=0..255] [STAtE={DisAbled BLocking}] [GROup={groupname 1..32}]	24-33
SET BRIDgE PROTOcol[= <i>protocolname</i> index] [PRIOrity=0..4]	24-34
SET BRIDgE SPanning [PRIOrity=0..65535] [MAxage=6..40] [HEllotime=1..10] [FOrwarddelay=4..30] [DEBUg={ON OFF}]	24-35
SET CLASSifier=1..9999 [IPDScp={dscp-list ANY}] [IPTOs={0..7 ANY}] [VLANPriority={priority-list ANY}]	5-15



SET CLASSifier=1..9999 [IInterface=*interface*|NONE] [EPort=*port*|ANY] [IPort=*port*|ANY]
 [SVlan=*vlan-name*|1..4094|ANY] [DVlan=*vlan-name*|1..4094|ANY] [VLANPriority=*priority-list*|ANY]
 [ETHFormat={802.2|802.2-Tagged|802.2-Untagged|Ethii|
 ETHII-Tagged|ETHII-Untagged|Netwareraw|
 NETWARERAW-Tagged|NETWARERAW-Untagged|Snap|SNAP-Tagged|
 SNAP-Untagged|ANY}]
 [MACDaddr={*macadd*|ANY}] [MACSaddr={*macadd*|ANY}] [MACType={L2Ucast|L2BMcast|ANY}]
 [ATMVCi={*vci-list*|ANY}] [ATMVPI={*vpi-list*|ANY}] [DLCi={*dlci-range*|ANY}] [PPPIIndex=0..1023]
 [PPPProtocolid={*ppp-protocol-id*|IP|IPv6|ANY}] [PROTocol={*protocol-type*|ARP|IP|IPv6|IPX|ANY}]
 [IPDAddr={*ipadd*|/0..32|*ipv6add*|/0..128|ANY}] [IPSAAddr={*ipadd*|/0..32|*ipv6add*|/0..128|ANY}]
 [IPDScp={*dscp-list*|ANY}] [IPTOs={0..7|ANY}] [IPFRag={YES|NO|ANY}] [IPOptions={YES|NO|ANY}]
 [IPFLowlabel={0..1048575|ANY}] [IPPRotocol={TCP|UDP|ICMp|IGMp|OSPF|NONTcpudp|ANY|
ip-protocol|ICmptype={Any|ECHO|Reply|Unreachable|Quench|Redirect|
 ECHO|Advertisement|Solicitation|Tlmeexceed|Parameter|
 TSTAMP|TSTAMPReply|INFOREQ|INFOREP|ADDRREQ|ADDRREP|
 NAMEReq|NAMERply|*icmp-type*}] [ICMPCode={Any|Filter|FRAGMent|FRAGReasm|HOSTComm|
 HOSTIsolated|HOSTPrec|HOSTREdirect|HOSTRTos|HOSTTos|
 HOSTUNKnown|HOSTUNReach|NETComm|NETREdirect|NETRTos|
 NETTos|NETUNKnown|NETUNReach|NOptr|PORTunreach|
 PREcedent|PROtunreach|PTRproblem|Sourceroute|Ttl|
icmp-code}] [TCPFlags={{URG|ACK|RST|SYN|FIN|,...}|ANY}] [TCPDport={*port-range*|ANY}]
 [TCPSport={*port-range*|ANY}] [UDPDport={*port-range*|ANY}] [UDPSport={*port-range*|ANY}] 5-15

SET CLASSifier=1..9999 [IInterface=*interface*|NONE] [IPDAddr={*ipadd*|/0..32|*ipv6add*|/0..128|ANY}]
 [IPSAAddr={*ipadd*|/0..32|*ipv6add*|/0..128|ANY}] [IPDScp={*dscp-list*|ANY}] [IPTOs={0..7|ANY}]
 [IPFRag={YES|NO|ANY}] [IPOptions={YES|NO|ANY}] [IPFLowlabel={*flow-label-range*|ANY}]
 [IPPRotocol={TCP|UDP|ICMp|IGMp|OSPF|NONTcpudp|ANY|
ip-protocol|ICmptype={Any|ECHO|Reply|Unreachable|Quench|Redirect|
 ECHO|Advertisement|Solicitation|Tlmeexceed|Parameter|
 TSTAMP|TSTAMPReply|INFOREQ|INFOREP|ADDRREQ|ADDRREP|
 NAMEReq|NAMERply|*icmp-type*}] [ICMPCode={Any|Filter|FRAGMent|FRAGReasm|HOSTComm|
 HOSTIsolated|HOSTPrec|HOSTREdirect|HOSTRTos|HOSTTos|
 HOSTUNKnown|HOSTUNReach|NETComm|NETREdirect|NETRTos|
 NETTos|NETUNKnown|NETUNReach|NOptr|PORTunreach|
 PREcedent|PROtunreach|PTRproblem|Sourceroute|Ttl|
icmp-code}] [TCPFlags={{URG|ACK|RST|SYN|FIN|,...}|ANY}] [TCPDport={*port-range*|ANY}]
 [TCPSport={*port-range*|ANY}] [UDPDport={*port-range*|ANY}] [UDPSport={*port-range*|ANY}] 5-16

SET CLNS[=*virtual-router-id*] [AREAAAddrmax=1..6] [AREAMaxcheck={ON|OFF|YES|NO|True|False}]
 [CSNPInterval=1..600] [ESHelloint=1..65535] [IHelloInt=1..65535] [LEvel={L1|L2}]
 [LSPMAxgenint=1..65535] [LSPMIngenint=1..65535] [LSPmtu=512..1492] [MAXPathsplits=1..3]
 [MINLSptxint=1..65535] [MINBRoadlsptxint=1..65535] [PSNPInterval=1..65535] [WAlttime=1..65535]
 48-24

SET CLNS[=*virtual-router-id*] CIRCuit=*circ-id* [IHPint=1..65535] [L1DEFmetricval=0..63]
 [L1DELmetricval=0..63] [L1EXPmetricval=0..63] [L1ERRmetricval=0..63] [L2DEFmetricval=1..63]
 [L2DELmetricval=0..63] [L2EXPmetricval=0..63] [L2ERRmetricval=0..63] [ISIS={ON|OFF|YES|NO|
 TRue|False}] [L2only={ON|OFF|YES|NO|TRue|False}] [L1Priority=1..127] [L2Priority=1..127]
 [ESIS={ON|OFF|YES|NO|TRue|False}] [ISConfint=1..65535] [ESConfint=1..65535]
 [RDHint=1..65535] [VLantag=1..4094] 48-25

SET CLNS[=*virtual-router-id*] RA=*nsap-prefix* CIRCuit=*circ-id* ETHernetaddress=*macadd* 48-27

SET CONfig=*filename*|none] 1-110

SET DECnet [Address=*dntadd*] [BROadcasttimer=1..65535] [HELLotimer=1..8191]
 [MAXAAddress=1..1023] [PRIOrity=1..127] [ROUtingtimer=1..65535]
 [TYpe={AREa|ROUtingiv|LEVEL1|LEVEL2|1|2}] 20-24

SET DECnet IInterface=*interface* COSt=1..25 20-26

SET DHCP EXTendid={ON|OFF} 35-20



SET DHCP POLICY= <i>name</i> [ARPTlmeout= <i>seconds</i>] [BOOTFilesize= <i>bootfilesize</i>] [BROADcastaddress= <i>ipadd</i>] [COOKleserver= <i>ipadd,ipadd...</i>] [DNSServer= <i>ipadd,ipadd...</i>] [DObainname= <i>string</i>] [ETHERENcap={ON OFF}] [EXTENSionpath= <i>string</i>] [File= <i>string</i>] [HOSTname= <i>string</i>] [IMPRESsserver= <i>ipadd,ipadd...</i>] [INTMTu=68..65535] [IPForwarding={ENAbled Disabled}] [IPMTU=576..65535] [IPPLAteau= <i>mtu,mtu...</i>] [IPTIMEout= <i>seconds</i>] [IPTTL= <i>ttl</i>] [LEASETIME={ <i>lease-time</i> INFINITY}] [LOGServer= <i>ipadd,ipadd...</i>] [LPRServer= <i>ipadd,ipadd...</i>] [MASKDiscovery={ON OFF}] [MASKSupplier={ON OFF}] [MERITdumpfile= <i>longstring</i>] [NAMEserver= <i>ipadd,ipadd...</i>] [NBDDservers= <i>ipadd,ipadd...</i>] [NBNAmeservers= <i>ipadd,ipadd...</i>] [NBNOdetype={B-node P-node M-node H-node}] [NBSCOpe= <i>string</i>] [NISDomain= <i>string</i>] [NIServers= <i>ipadd,ipadd...</i>] [NTPServers= <i>ipadd,ipadd...</i>] [POLICYFiltering= <i>ipadd,ipadd...</i>] [RESOUrceserver= <i>ipadd,ipadd...</i>] [ROOTPath= <i>longstring</i>] [ROUter= <i>ipadd,ipadd...</i>] [ROUTERDiscovery={ON OFF}] [ROUTERSolicit= <i>ipadd</i>] [SERVER= <i>ipadd</i>] [SERVERName= <i>server-name</i>] [SOURcerouting={ENAbled Disabled}] [STATicroute= <i>ipadd,ipadd...</i>] [SUBLOcal={ON OFF}] [SUBNetmask= <i>ipadd</i>] [SWAPServer= <i>ipadd</i>] [T1Tlme= <i>seconds</i>] [T2TIME= <i>seconds</i>] [TCPGarbage={ON OFF}] [TCPKeepalive= <i>seconds</i>] [TCPTtl= <i>ttl</i>] [TIMEOffset= <i>utc-offset</i>] [TIMEServer= <i>ipadd,ipadd...</i>] [TRAILerencap={ON OFF}] [XDISplayservers= <i>ipadd,ipadd...</i>] [XFONtservers= <i>ipadd,ipadd...</i>]	35-21
SET DHCP RANGE= <i>name</i> PRObe={ARP CMP}	35-26
SET DHCP6 KEY=0..65535 [CLlentid= <i>clientid</i>] [STRict={TRue False}]	36-21
SET DHCP6 POLIcy= <i>name</i> [DNSServer= <i>ipv6add[,ipv6add]</i>] [DObainname= <i>domain-name[,...]</i>] [PDlease=0..255] [PREFerence=0..255] [SERVER= <i>ipv6addr</i>] [T1Tlme= <i>seconds</i>] [T2Tlme= <i>seconds</i>]	36-22
SET DVMrp INTERface= <i>interface</i> [DLC=1..1024] [METric=1..32] [TTLThreshold=1..255]	17-58
SET ENCo DHPAdding={ON Off}	25-25
SET ENCo DHPriority={High Medium Low}	25-26
SET ENCo KEY= <i>key-id</i> [DESCription= <i>description</i>] [IPaddress= <i>ipadd</i>] [MODUle= <i>module-id</i>]	25-26
SET ENCo SW [PREDCchannels=0..4] [STACChannels=0..4]	25-27
SET ETH= <i>n</i> MAXbandwidth=0..100000	7-42
SET ETH= <i>n</i> Speed={AUtonegotiate 10MHalf 10MFull 100MHalf 100MFull}	7-43
SET FIREwall MAXFragments=8..50	41-72
SET FIREwall POLIcy= <i>policy-name</i> [MAXUPNPpPORTMAPS={0-1000}] [OTHERTimeout= <i>minutes</i>] [TCPTimeout= <i>minutes</i>] [UDPTIMEout= <i>minutes</i>] [UPNP={ON OFF YES NO ENABLED DISABLED}]	41-73
SET FIREwall POLIcy= <i>policy-name</i> ATTack={DOSFlood FRAGment HOSTScan IPSPoof LAND PINGOfdeath PORTScan SMTPrelay SMURF SMURFAmp SPAM SYNAttack TCPTIny UDPAAttack} [INTrigger= <i>count</i>] [OUTTrigger= <i>count</i>] [DETail= <i>count</i>] [Tlme= <i>minutes</i>]	41-74
SET FIREwall POLIcy= <i>policy-name</i> RULE= <i>rule-id</i> [PROTOcol={ <i>protocol</i> ALL EGP GRE ICmp OSPF SA TCP UDP}] [AFTER= <i>hh:mm</i>] [BEFORE= <i>hh:mm</i>][DAYs={MON TUE WED THU FRI SAT SUN WEEKDAY WEEKEND},{...}] [ENCapsulation={NONE IPSec}] [GBLIP= <i>ipadd</i>] [GBLPort={ALL <i>port</i> [- <i>port</i>]} <i>service-name</i> }] [GBLRemoteip= <i>ipadd</i> [- <i>ipadd</i>]] [IP= <i>ipadd</i> [- <i>ipadd</i>]] [NATMask= <i>ipadd</i>] [Port={ALL <i>port</i> [- <i>port</i>]} <i>service-name</i> }] [REMoteip= <i>ipadd</i> [- <i>ipadd</i>]] [SOurceport={ALL <i>port</i> [- <i>port</i>]}] [TTL= <i>hh:mm</i>]	41-76
SET FIREwall POLIcy= <i>policy-name</i> SMTPdomain={ <i>domain-name</i> NONE}	41-79
SET FRamerelay= <i>fr-interface</i> [DEFATencap={Appleoui Ietfoui}] [BECNLimit=2..4294967295] [BECNTimeout=1..4294967295] [CDETection={BECN CLLM BOTH}] [CTICK=1..60] [DECreasefactor={0.025 0.05 0.1 0.2}] [DEFComPRESSION={ON OFF}] [DEFENCapsulation={IETF CISCO}] [DEFEncryption={ON OFF}] [DROPOFFthreshold=1..100] [INCreasefactor={0.05 0.1 0.2}] [LMIscheme={LMIREV1 Q933A ANNEXA T1617B ANNEXB T1617D ANNEXD NONE}] [MAXTXQlength=1..4294967295] [NN1= <i>nn1</i>] [NN2= <i>nn2</i>] [NN3= <i>nn3</i>] [NT1= <i>nt1</i>] [RECOverytime=1..4294967295]	10-45
SET FRamerelay= <i>fr-interface</i> DLC= <i>dlci</i> [CIR={ <i>cir</i> NONE}] [CIRLIMited=ON OFF YES NO] [COMPRESSION={DEFAult ON OFF}] [EIR={ <i>eir</i> NONE}] [ENCAPsulation={DEFAult IETF CISCO}] [ENCryption={DEFAult ON OFF}] [LI= <i>logical-interface</i>]	10-48
SET GRE TUNnel REMote= <i>ipadd</i> KEY={ <i>keyval</i> NONE}	29-18



SET GRE= <i>gre-number</i> ENTry= <i>entry-number</i> [{INTERface= <i>interface</i> SOurce= <i>ipadd</i> [SMask= <i>ipadd</i>] [DEStination= <i>ipadd</i>] [DMask= <i>ipadd</i>]}] [TARget= <i>ipadd</i>]	29-16
SET H323 ENTry ENGiNe= <i>engine</i> PHOnenumber= <i>number</i> [HOSTip= <i>ipaddr</i>] [PORt= <i>tcpport</i>]	52-35
SET H323 GATEWay[CONNeCttout= <i>time</i>] [GATEKeeper= <i>ipaddr[:ipport]</i> [-id][: <i>ipaddr[:ipport]</i> [-id]]] AUTO NONE}] [NAME= <i>alias</i>] [Q931port= <i>tcpport</i>] [RASport= <i>udpport</i>] [RESPOnsetout= <i>time</i>] [TIMEtolive= <i>time</i>]	52-36
SET H323 INTERface= <i>interface</i> [CAPABility={ALL PCMU PCMA G723R53 G723R63 G729A}[,...]] [CLIP={ON OFF}] [DSCP= <i>dscp</i> priority] [DTMFrelay={H245 RTP NONE}] [PHOnenumber= <i>number</i>] [RTCP={ON OFF}] [TOS= <i>tos</i> priority]	52-34
SET HELP= <i>helpfile</i>	1-111
SET HTTP SERVer [PORt= <i>port</i>] [SECurity=ON OFF ENABled DisABled True False] [SSLKey= <i>key-id</i>]	1-112
SET IGMPsNooping ROUTERMode={ALL DEFAult IP MULTICAstrouter NONE}	17-60
SET INSTAll={TEMPorary PREFerred DEFAult} [GUI= <i>file-name</i>] [RELease= <i>release-name</i>] [PATch= <i>patch-name</i>]	1-113
SET INTERface={ifIndex <i>interface</i> DYNamic} TRaplimit=1..60	7-45
SET INTERface={ifIndex <i>interface</i> } MTU= <i>value</i>	7-44
SET IP ADVERTISE INTERface= <i>interface</i> [ADVERTISEmentaddress=ALL LIMited] [MAXadvertisementinterval=4..1800] [MINadvertisementinterval=3..MAXadvertisementinterval] [LIFetime=MAXadvertisementinterval..9000]	14-134
SET IP ARP TIMEOut= <i>multiplier</i>	14-136
SET IP ARP= <i>ipadd</i> INTERface= <i>interface</i> {CIRCuit= <i>miox-circuit</i> DLCi= <i>dLCi</i> ETHernet= <i>macadd</i>] PORt= <i>port-number</i> }	14-135
SET IP AUtonomous=1..65534	49-105
SET IP DNS [DOMain={ANY <i>domain-name</i> }] {INTERface= <i>interface</i> [PRIMary= <i>ipadd</i>] [SECOnDary= <i>ipadd</i>]}	14-137
SET IP DNS CACHe [Size= <i>cache-entries</i>] [TIMEout= <i>cache-max-age</i>]	14-138
SET IP DNSRelay INTERface={ <i>interface</i> NONE}	14-139
SET IP FILter=0..399 SOurce= <i>ipadd</i> [SMask= <i>ipadd</i>] [SPort={ <i>port-name</i> <i>port-id</i> }] [DEStination= <i>ipadd</i>] [DMask= <i>ipadd</i>] [DPort={ <i>port-name</i> <i>port-id</i> }] [ICMPCode={ <i>icmp-code-name</i> <i>icmp-code-id</i> }] [ICMptype={ <i>icmp-type-name</i> <i>icmp-type-id</i> }] [LOG={4..1600 Dump Header None}] [OPTions={False OFF ON NO True YES}] [PROTOcol={ <i>protocol</i> Any Egp Icmp Ospf Tcp Udp}] [SEssion={Any Established Start}] [Size= <i>size</i>] [ENTry= <i>entry-number</i>] {ACtion={INCLude EXCLude} POLIcy=0..15 PRIOrity=P0..P7}	14-140
SET IP HOst= <i>name</i> IPAddress= <i>ipadd</i>	14-144
SET IP IGMP [LMQi=1..255] [LMQC=1..5] [QUERyinterval=1..65535] [QUERYREsponseinterval=1..255] [ROBustness=1..5] [TIMEOut=1..65535]	17-59
SET IP INTERface= <i>interface</i> [ADVERTISE={YES NO}] [PREferencelevel={-2147483648..2147483647 NOTDEFAULT}] [BROadcast={0 1}] [DIRectedbroadcast={False NO OFF ON True YES}] [FILter={0..99 NONE}] [FRAgment={NO OFF ON YES}] [GRAuitousarp={ON OFF}] [GRE={0..100 NONE}] [IGMPProxy={OFF UPstream DOWNstream}] [INVersearp={ON OFF}] [IPAddress= <i>ipadd</i> DHCP] [MASK= <i>ipadd</i>] [METric=1..16] [MULTicast={BOTH OFF ON RECeive SEND}] [OSPFmetric=1..65534 DEFAULT] [POLIcyfilter={100..199 NONE}] [PRIorityfilter={200..299 NONE}] [PROxyarp={False NO OFF ON True YES Strict DEFRoute}] [RIPMetric=1..16] [SAMode={Block Passthrough}] [VJC={False NO OFF ON True YES}] [VLANTAG={1..4094 NONE}]	14-145
SET IP LOCal={DEFAULT 1..15}] [FILter={0..299 NONE}] [GRE={0..100 NONE}] [IPAddress= <i>ipadd</i>] [POLIcyfilter={0..299 None}] [PRIorityfilter={0..299 None}]	14-149
SET IP NAMEserver= <i>ipadd</i>	14-151
SET IP NAT MAXFragments=8..50	14-152
SET IP RIP INTERface= <i>interface</i> [CIRCuit= <i>miox-circuit</i>] [DLCi= <i>dLCi</i>] [IP= <i>ipadd</i>] [NEXThop= <i>ipadd</i>] [SEND={None RIP1 RIP2 COMPATible}] [RECeive={None RIP1 RIP2 BOTH}] [DEMAND={False NO OFF ON True YES}] [AUTH={None PASSword MD5}] [PASSword= <i>password</i>] [STATicesport={YES NO}]	14-153



SET IP RIPTimer [FLush=1..4294967295] [HOlldown=1..4294967295] [INvalid=1..4294967295] [UPdate=1..4294967295]	14-155
SET IP ROUte FILTER= <i>filter-id</i> [IP= <i>ipadd</i>] [MASK= <i>ipadd</i>] [ACtion={INCLude EXCLude}] [Direction={RECEive SEND BOTH}] [INTErface= <i>interface</i>] [NEXThop= <i>ipadd</i>] [POLIcy=0..7] [PROToCol={ANY EGP OSPF RIP}]	14-158
SET IP ROUte PREFeRence={DEFAult 1..65535} PROToCol={BGP-ext BGP-int OSPF-EXT1 OSPF- EXT2 OSPF-INTER OSPF-INTRA OSPF-Other RIP}	14-160
SET IP ROUte TEMPLate= <i>name</i> [NEXThop= <i>ipadd</i>] [CIRCUit= <i>miox-circuit</i>] [DLCi= <i>dlci</i>] [METRic=1..16] [METRIC1=1..16] [METRIC2=1..65535] [POLIcy=0..7] [PREFeRence=0..65535]	14-161
SET IP ROUte= <i>ipadd</i> INTErface= <i>interface</i> MASK= <i>ipadd</i> NEXThop= <i>ipadd</i> [CIRCUit= <i>miox-circuit</i>] [DLCi= <i>dlci</i>] [METRIC=1..16] [METRic1=1..16] [METRIC2=1..65535] [POLIcy=0..7] [PREFeRence=0..65535] [TAG=1..65535]	14-156
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}]	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth ASPath=1..99	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth COMMunity=1..99 [EXAct={NO YES}]	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth LOCALPREF=0..4294965295[-0..4294965295]	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth NEXThop= <i>ipadd</i>	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth ORIGin={EGP IGP INComplete}	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth PREFIXList= <i>name</i>	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion={INCLude EXCLude}] MAth TAG=1..65535	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion=INCLude] SET ASPath={1..65534[,...]}	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion=INCLude] SET COMMunity={NOExport NOAdvertise NOEXPORTSubconfed 1..4294967295[,...]} [ADD={NO YES}]	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion=INCLude]	
SET LOCALpref=0..4294967295	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion=INCLude] SET MED={0..4294967295 REMOVE}	49-106
SET IP ROUTEMap= <i>routemap</i> ENTry=1..4294967295 [ACtion=INCLude] SET ORIGin={IGP EGP INComplete}	49-106
SET IP SECOndarynameserver= <i>ipadd</i>	14-162
SET IPSec BUNDlespecification= <i>bundlespecification-id</i> [EXPIRYKbytes=1..2000000000] [EXPIRYSeconds=300..31449600]	45-74
SET IPSec POLIcy= <i>name</i> [ACtion={DEny IPSec PERmit}] [BUNDlespecification= <i>bundlespecification-id</i>] [DFBit={SEt COpy CLear}] [GROup={0 1 2}] [ICmptype={list NDall}] [IPROUTetemplate= <i>template-name</i>] [IPVersion={4 6}] [ISAkmppolicy= <i>isakmp-policy-name</i>] [LADdress={Any <i>ipv4add</i> [- <i>ipv4add</i>] <i>ipv6add</i> [/ <i>prefix-length</i>] <i>ipv6add-ipv6add</i>] [LMAsk= <i>ipv4add</i>] [LNAme={Any <i>system-name</i> }] [LPort={Any OPaque <i>port</i> }] [PEERaddress={ <i>ipv4add</i> <i>ipv6add</i> Any] DYNAMIC}] [POsition= <i>pos</i>] [RADdress={Any <i>ipv4add</i> [- <i>ipv4add</i>] <i>ipv6add</i> [/ <i>prefix-length</i>] <i>ipv6add-ipv6add</i>] [RMASK= <i>ipv4add</i>] [RNAme={Any <i>system-name</i> }] [RPort={Any <i>port</i>] OPaque}] [SRCInterface= <i>interface</i>] [TRANsportprotocol={Any EGP ESp GRE ICMP OPaque OSp RSvp TCp UDp <i>protocol</i> }] [UDPHearbeat={True False}] [UDPPort= <i>port</i>] [UDPTunnel={True False}] [USEPFSKey={True False}]	45-75
SET IPSec SASpecification= <i>spec-id</i> [ANTIreplayenabled={True False}] [COMPAlg=LZS] [ENCAlg={3DES2key 3DESInner 3DESOuter DES AES128 AES192 AES256 NUL}] [ENCKey= <i>key-id</i>] [HASHAlg={DESMac MD5 NUL SHA}] [HASHKey= <i>key-id</i>] [INSPI= <i>spi</i>] [MDe={TRANsport TUnnel}] [OUTSPI= <i>spi</i>] [REPLAywindowsize={32 64 128 256}]	45-78



SET IPsec UDPPort= <i>port</i>	45-80
SET IPV6 FILTER= <i>filter-id</i> ENTRY= <i>entry-number</i> SOURCE= <i>ipv6add/prefix-length</i> [ACTION={INCLUDE EXCLUDE}] [PRIORITY=P0..P7] [DESTINATION= <i>ipv6add/prefix-length</i>] [DPORT={ <i>port-name</i> <i>port-id</i> Any}] [ICMPCode={ <i>icmp-code-name</i> <i>icmp-code-id</i> Any}] [ICMPTYPE={ <i>icmp-type-name</i> <i>icmp-type-id</i> Any}] [LOG={4..1950 Dump Header None}] [OPTIONS={YES NO ON OFF True False}] [PROTOCOL={ <i>protocol</i> Any Egp Icmp Ospf Tcp Udp}] [SESSION={Any Established Start}] [SIZE={ <i>size</i> Any}] [SPORT={ <i>port-name</i> <i>port-id</i> Any}]	15-61
SET IPV6 INTERFACE= <i>interface</i> [FILTER=0..99] [IPADDRESS= <i>ipv6add/prefix-length</i>] [PREFERRED=1..4294967295 INFINITE] [PRIORITYfilter=200..299] [PUBLISH={YES NO ON OFF True False}] [VALID=1..4294967295 INFINITE]	15-64
SET IPV6 MLD [ROBUSTNESS={2..65535 DEFAULT}] [QINTERVAL={1..65535 DEFAULT}] [QRIINTERVAL={1..65535 DEFAULT}] [SQINTERVAL={1..65535 DEFAULT}] [SQCOUNT={1..65535 DEFAULT}] [LLQINTERVAL={1..65535 DEFAULT}] [LLQCOUNT={1..65535 DEFAULT}]	18-34
SET IPV6 MLD INTERFACE= <i>interface</i> QUERYversion={1 2}	18-36
SET IPV6 MTU= <i>mtu</i> INTERFACE= <i>interface</i>	15-65
SET IPV6 ND INTERFACE= <i>interface</i> [DUPTRANS=1..16] [HOP=1..255] [LIFE=0 4..9000] [MAXAINT=4..1800] [MCONF={YES NO}] [MINAINT=3..1350] [MTU=1280..65535] [OCONF={YES NO}] [REACH=0..3600000] [RETRANS=0..4294967295]	15-66
SET IPV6 PREFIX= <i>ipv6add/prefix-length</i> INTERFACE= <i>interface</i> [AUTONOMOUS={YES NO}] [ONLINK={YES NO}] [PREFERRED=1..4294967295 INFINITE] [VALID=1..4294967295 INFINITE]	15-68
SET IPV6 ROUTE PREFERENCE={DEFAULT 1..65535} PROTOCOL=RIP	15-69
SET IPX {GRIP GSAP}={ <i>filter-number</i> NONE}	19-52
SET IPX CIRCUIT= <i>circuit</i> [INTERFACE= <i>interface</i>] [NETWORK= <i>network</i>] [COST=1..999] [DEMAND={ON OFF YES NO TRUE FALSE}] [DLCI= <i>dlci</i>] [ENCAPSULATION={802.2 802.3 ETHII SNAP}] [INRIP= <i>filter-number</i> NONE] [OUTRIP= <i>filter-number</i> NONE] [INSAP= <i>filter-number</i> NONE] [OUTSAP= <i>filter-number</i> NONE] [KEEPALIVE={ON OFF YES NO TRUE FALSE ENDLESSLY FOREVER INFINITE INFINITELY INDEFINITELY NONSTOP 1..1440}] [MIOXCIRCUIT= <i>circuit-name</i>] [RIPCHANGE={ON OFF YES NO TRUE FALSE}] [RIPTIMER=0..99999] [SAPCHANGE={ON OFF YES NO TRUE FALSE}] [SAPTIMER=0..99999] [SPXSPOOF={ON OFF YES NO TRUE FALSE ENDLESSLY FOREVER INFINITE INFINITELY INDEFINITELY NONSTOP 0..1440}] [SPXENDSPOOF={UPLINK DONOTHING}] [SPXCONFAL={UPLINK DONOTHING}] [TYPE20={ON OFF YES NO TRUE FALSE}]	19-48
SET IPX RIP= <i>filter-number</i> ENTRY= <i>entry-number</i> [NETWORK= <i>network</i>] [ACTION={INCLUDE EXCLUDE}] [NEWENTRY= <i>entry-number</i>]	19-52
SET IPX SAP= <i>filter-number</i> ENTRY= <i>entry-number</i> [SERVICE= <i>service</i>] [TYPE= <i>service-type</i>] [ACTION={INCLUDE EXCLUDE}] [NEWENTRY= <i>entry-number</i>]	19-53
SET ISAKMP POLICY= <i>name</i> [AUTHType={PREshared RSAEncr RSASig}] [DHExponentlength=160..1023] [DELETEDelay=10] [ENCAlg={3DES2key 3DESInner 3DESOuter DES AES128 AES192 AES256}] [EXPIRYKbytes=1..1000] [EXPIRYSeconds=600..31449600] [GROUP={0 1 2}] [HASHalg={SHA MD5}] [HEARTbeatmode={Both None Receive Send}] [HYBRIDxauth={ON OFF True False}] [IPVversion={4 6}] [KEY=0..65535] [LOCALID={ <i>ipv4add</i> <i>ipv6add</i> <i>domainname</i> <i>user-domainname</i> <i>dist-name</i> }] [LOCALRsakey=0..65535] [MODE={MAIN AGGressive}] [MSGREtrylimit=0..1024] [MSGTimeout=1..86400] [NATTraversal={ON OFF True False}] [PHASE2xchglimit={None 1..1024}] [POLICYFilename= <i>filename</i>] [PREnegotiate={ON OFF True False}] [REMOTEId={ <i>ipv4add</i> <i>ipv6add</i> <i>domainname</i> <i>user-domainname</i> <i>dist-name</i> }] [SENDDeletes={ON OFF True False}] [SENDNotify={ON OFF True False}] [SENDIdalways={ON OFF True False}] [SETCommitbit={ON OFF True False}] [SRCInterface= <i>interface</i>] [XAUTH={Client Server None}] [XAUTHName= <i>username</i>] [XAUTHPasswd= <i>password</i>] [XAUTHType={Generic Radius}]	45-80



SET ISDN CALL=name [NUMber=number] [PREcedence={IN OUT}] [ALTnumber=number] [BUMPdelay=0..100] [CALLBACK={ON OFF YES NO True False}] [CALLINGNumber=number] [CALLINGSubaddress= <i>calling-subaddress</i>] [CBDelay=0..100] [CHECKCLI={OFF PREsent REquired}] [CHECKSub={OFF LOCAL REmote}] [CHECKUser={OFF LOCAL REmote}] [CLList=0..99] [Direction={IN OUT BOTH}] [DOV={ON OFF YES NO True False}] [HOLDUP=0..7200] [INANY={ON OFF YES NO True False}] [INTPRef={NONE interface}] [INTREQ={NONE interface}] [KEEPU= {ON OFF YES NO True False}] [LOGIn={ALL NONE CHAP PAP-Radius PAP-Tacacs RADIus TACAcS USER}] [MAXDURATION=0..36000] [OUTCLI={OFF CALLIng INterface NONUmber}] [OUTSUB={OFF LOCAL REmote}] [OUTUSER={OFF LOCAL REmote}] [PASSword={NONE CLI CALLEdsub NAME USer}] [PPPTemplate= <i>template</i>] [PRIOrity=0..99] [Rate={56K 64K}] [REMotecall=name remote-number] [RN1=0..10] [RN2=0..5] [RT1=5..120] [RT2=300..1200] [SEARCHCLI={ON OFF YES NO True False CALled 0..99}] [SEARCHSub={OFF LOCAL REmote}] [SEARCHUser={OFF LOCAL REmote}] [SUBAddress=number] [USer={ATTach PPP}] [USERName={NONE CLI CALLEdsub NAME USer}] 11-95
SET ISDN DOMainname=domain-name 11-101
SET ISDN LOG [Port={0..23 None}] [LENGth=0..100] 11-101
SET L2TP CALL=name [TYpe={ASYNc ISDN Vrtual}] [IP=ipadd] [REMotecall=name] [DIAL=number] [NUMber={ON OFF STARTup}] [PASSword=password] [PRE13={ON OFF}] [PREcedence={IN OUT}] [Speed=speed] [SUBAddress=subaddress] 37-24
SET L2TP CHECKSum={ON OFF} 37-26
SET L2TP FILTER={filter-number NONE} 37-26
SET L2TP PASSword={password NONE} 37-27
SET L2TP USer={mapping ALL LOCAL NONE REmote} [ACtion={DATABase DNSLookup IGNore RADIus}] [IP=ipadd] [Port=port] [NUMber={ON OFF}] [PASSword=password] [PRE13={ON OFF}] [PREFIX=prefix] [TIMEOut=timeout] 37-27
SET LAPB=lapb-interface [MODULUS={8 128}] [N2=1..40] [ROLE={DCE DTE DXE}] [RMAXDATA=1080..32792] [TMAXDATA=1080..32792] [WINDOW=1..127] [T1=1..120] 500..10000] [T3=3..120] 12-59
SET LAPD=interface [NASMode={NORMAL MASTER SLAVE}] [NASMAster=interface] 11-102
SET LAPD= <i>interface</i> {ATTACH= <i>sap</i> CONNECT= <i>sap</i> DATA= <i>sap</i> CES= <i>ces</i> ESTABLISH= <i>sap</i> CES= <i>ces</i> MDATA= <i>sap</i> CES= <i>ces</i> MUNIT= <i>sap</i> CES= <i>ces</i> RELEASE= <i>sap</i> CES= <i>ces</i> UNIT= <i>sap</i> CES= <i>ces</i> } 11-102
SET LAPD=interface DEBug={OFF STATE PACKET} 11-102
SET LAPD=interface MODE={AUTOMATIC NONAUTOMATIC} 11-102
SET LAPD=interface SAP= <i>sap</i> {N200 N201 N202}=time... 11-102
SET LAPD=interface SAP= <i>sap</i> {T200 T201 T202 T203}=time... 11-102
SET LAPD=interface SAP= <i>sap</i> K=value 11-102
SET LOADBalancer [Affinitytimeout=0..4294967295] [CRITicalrst=0..100] [ORPHAntimeout=0..65535] 50-37
SET LOADBalancer REDUNDancy [LISTenport=0..65535] [PEERip= <i>ipadd</i>] [PUBLICint= <i>interface</i>] [REDUNip= <i>ipadd</i>] [REDUNMask= <i>ipadd</i>] 50-38
SET LOADBalancer RESource= <i>resourcenam</i> e [IP= <i>ipadd</i>] [Port=0..65535] [RESPool= <i>resourcepoolname</i>] [WEIght=0..4294967295] 50-39
SET LOADBalancer RESPool= <i>resourcepoolname</i> [FAIlLast={YES NO}] [SElectmethod={ROundrobin WLEastconnect WLOttery FAstestresponse}] 50-40
SET LOADBalancer VIRTualbalancer= <i>virtualbalancename</i> [AFFinity={YES NO}] [COOkieheader= <i>cookiedetectorstring</i>] [DOMAinname= <i>domainname</i>] [POLicy= <i>policyName</i>] [PUBLICIp= <i>ipadd</i>] [PUBLICPort=0..65535] [RESPool= <i>resourcepoolname</i>] [SSL={ON Off}] [SSLKey= <i>key-id</i>] [SSLToresource={ON Off}] [TYpe={ROute TCp SSl HTtp}] 50-41



SET LOAdEr [ATTRibute={Cert CRI CAcert DEFAult}] [BASeobject={ <i>dist-name</i> DEFAult}] [DElay={ <i>delay</i> DEFAult}] [DESTFile= <i>destfilename</i>] [DESTination={BOOTblock Flash}] [HTTPproxy={ <i>hostname</i> <i>ipadd</i> DEFAult}] [METhod={HTTP LDAP Tftp WEB WWW ZModem NONE DEFAult}] [PASSword= <i>password</i>] [ASYN={ <i>port</i> DEFAult}] [PROxyport={1..65535 DEFAult}] [SRCFile File= <i>filename</i>] [SErver={ <i>hostname</i> <i>ipadd</i> <i>ipv6add</i> DEFAult}] [SERVport={1..65535 DEFAult}] [USername= <i>username</i>] 1-114
SET LOG OUTput={Temporary <i>output-id</i>] [ASYN= <i>port-number</i>] [DESTination={Email Memory ASYN Router Syslog}] [FACILITY={DEFAULT LOCAL1...LOCAL7}] [FORMat={Full MSGOnly SUMMARY}] [MAXQueueseverity= <i>severity</i>] [MESSages= <i>message-count</i>] [PASSword={ <i>password</i> NONE}] [QUEueonly={False NO OFF ON True YES}] [SECure={False NO OFF ON True YES}] [SERVER= <i>ipadd</i>] [SYSlogformat=Extended Normal] [TO= <i>email-address</i>] [ZOne={ <i>time-zone-name</i> <i>utc-offset</i> }] [LOCAL={NONE 1..15}] 33-26
SET LOG OUTput={Temporary <i>output-id</i>] FILTER= <i>filter-id</i> [ACtion={Process Ignore}] [ALL] [Date={ <i>op</i> <i>dd-mmm-yyyy</i>] [DEvice={ <i>op</i> <i>device</i>] [File={ <i>op</i> <i>filename</i>] [MASK= <i>ipadd</i>] [MSGtext={ <i>op</i> <i>string</i>] [MODule={ <i>op</i> <i>module-id</i>] [ORIGin= <i>ipadd</i>] [REFerence={ <i>op</i> <i>string</i>] [SEVerity={ <i>op</i> <i>severity</i>] [SOURceline={ <i>op</i> <i>line</i>] [SUBType={ <i>op</i> <i>subtype-id</i>] [TIme={ <i>op</i> <i>hh:mm:ss</i>] [Type={ <i>op</i> <i>type-id</i>] [LOCAL={NONE 1..15}] 33-26
SET LOG RECEive={ <i>ipadd</i> ANY} [ALLow={False NO OFF ON True YES}] [MASK= <i>ipadd</i>] [PASSword={ <i>password</i> NONE}] [PROTocol={ALL BOTH NEW OLD SYSlog}] 33-32
SET LOG UTCOffset={ <i>time-zone-name</i> <i>utc-offset</i>] 33-33
SET LPD= <i>queue-name</i> ASYN= <i>port</i> [Banner={ON OFF}] [Insertff={ON OFF}] [ExpandIf={ON OFF}] 22-20
SET MAIL HOSTname= <i>hostname</i> [SMTPserver= <i>ipadd</i>] 1-118
SET MANager ASYN={ <i>port-number</i> NONE} 1-119
SET MIOX=x25t-interface [MINOPEN=10..360] [INACTIVE=10..360] [HOLDDOWN=10..360] [COLLISION=10..360] [FAILURE=10..360] 12-60
SET MIOX=x25t-interface CIRCUIT= <i>circuit-name</i> [{DTEADDRESS= <i>dteaddress</i> PVC=1..4095}] [CPAR=1..8] [ENCAP={APPLE IP IPX NULL MULTIPLE PPP}] [COMMENT= <i>comment</i>] [COMP={ON OFF}] [TCPCOMP={ON OFF}] 12-61
SET NTP UTCOffset=-24:00:00..+24:00:00 27-9
SET OSPF [ASExternal={ON OFF NSSA}] [BGPFilter={NONE 300..399}] [BGPImport={ON OFF True False YES NO}] [BGPLimit=1..4000] [AUTOCOST={ON OFF}] [DEFRoute={ON OFF True False YES NO}] [TYPE={1 2}] [METRIC=0..16777215] [DYNInterface={STUB ASExternal NONE NO OFF False}] [REFBANDWIDTH=10..10000] [RIP={OFF EXPORT IMPORT BOTH}] [ROuterid= <i>ipadd</i>] [PTPStub={ON OFF YES NO True False}] [STATicexport={YES NO}] 23-39
SET OSPF AREa={Backbone <i>area-number</i>] [AUthentication={NONE PASSword}] [STUBArea={ON OFF YES NO NSSA True False}] [STUBMetric=0..16777215] [SUMmary={SEND NONE OFF NO FALSE}] 23-41
SET OSPF HOst= <i>ipadd</i> METRIC=0..65535 23-42
SET OSPF INTerface= <i>interface</i> [AREa={Backbone <i>area-number</i> }] [BOOST1=0..1023] [DEadinterval=2..2147483647] [DEmand={ON OFF YES NO True False}] [HELlointerval=1..65535] [PASSword= <i>password</i>] [POLLIinterval=1..2147483647] [PRIOrity=0..255] [RXminterval=1..3600] [TRansitdelay=1..3600] [Virtuallink= <i>router-id</i>] 23-43
SET OSPF NEIghbour= <i>ipadd</i> PRIOrity=0..255 23-46
SET OSPF RANge= <i>ipadd</i> [AREa={Backbone <i>area-number</i> }] [MASK= <i>ipadd</i>] [EFFect={ADVertise DONotadvertise}] 23-47
SET OSPF STUB= <i>ipadd</i> MASK= <i>ipadd</i> METRIC=0..65535 23-48
SET PASSword 1-120
SET PERM= <i>perm-name</i> [LPORT= <i>lport</i>] [RPORT= <i>rport</i>] [IP= <i>ipadd</i>] 22-21
SET PIM [ADVinterval={10..15000 DEFAult}] [BSMinterval={10..15000 DEFAult}] [JPIinterval={1..65535 DEFAult}] [KEEPalivetime={10..65535 DEFAult}] [PRObetime={1..65535 DEFAult}] [PRUNEholdtime={1..65535 DEFAult}] [SOURCealivetime={10..65535 DEFAult}] [SRINterval={10..255 DEFAult}] [SUPPressiontime={1..65535 DEFAult}] 17-61
SET PIM BSRCandidate [HASHMASKLENGTH=0..32] [PREference=0..255] 17-63



SET PIM INTERface= <i>interface</i> [DLCi=1..1024] [DRPriority=0..4294967295] [ELectby={DRPriority IPaddress}] [HELlointerval={10..15000 DEFAult 65535}] [MODE={Dense Sparse}] [SRCapable={Yes No}]	17-64
SET PIM LOG={NONE STATus ERRor ALL} [TRap={NONE STATus ERRor ALL}]	17-63
SET PIM RPCandidate GROup= <i>group-address</i> [MASK= <i>ipaddress</i>] [PRIOrity=0..255][INTERFACE={local-interface vlan-interface}]	17-65
SET PIM6 [ADVinterval={10..15000 DEFAult}] [BSMinterval={10..15000 DEFAult}] [JPInterval={1..65535 DEFAult}] [KEEPalivetime={10..65535 DEFAult}] [PRObetime={1..65535 DEFAult}] [PRUNEholdtime={1..65535 DEFAult}] [SOURCealivetime={10..65535 DEFAult}] [SRInterval={10..255 DEFAult}] [SUPPressiontime={1..65535 DEFAult}]	18-36
SET PIM6 BSRCandidate [SCOpe=SITE GLObal ALL] [PREference=0..255]	18-38
SET PIM6 INTERface= <i>interface</i> [DRPriority=0..4294967295] [ELectby={DRPriority IPaddress}] [HELlointerval={10..15000 DEFAult 65535}] [MODE={Dense Sparse}] [SRCapable={Yes No}]	18-38
SET PIM6 RPCandidate GROup= <i>ipv6address/prefixlength</i> [PRIOrity=0..255]	18-39
SET PING [[APPLEAddress= <i>network.node</i>] [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMBER={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SAPpleaddress= <i>network.node</i>] [SCReenoutput={YES NO}] [TIMEOut=1..65535]	14-163
SET PING [[IPAddress={ <i>ipadd ipv6add[%interface] host</i> }] [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMber={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SIPAddress= <i>ipadd ipv6add</i>] [SCReenoutput={YES NO}] [TIMEOut=1..65535] [TOS=0..255]	14-163
SET PING [[IPXAddress= <i>network:station</i>] [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMber={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SIPXaddress= <i>network:station</i>] [SCReenoutput={YES NO}] [TIMEOut=1..65535]	14-163
SET PING [[OSIAddress= <i>nsap</i>] [DElay= <i>seconds</i>] [Length= <i>number</i>] [NUMber={ <i>number</i> CONTInuous}] [PATtern= <i>hexnum</i>] [SOSladdress= <i>nsap</i>] [SCReenoutput={YES NO}] [TIMEOut=1..65535]	14-163
SET PING POLl= <i>poll-id</i> [CRIticalinterval=1..65535] [DESCRiption= <i>poll-description</i>] [FALLcount=1..100] [IPAddress={ <i>ipadd ipv6add[%interface]</i> }] [Length=4..1500] [NORMalinterval=1..65535] [SAMPlesize=1..100] [SIPAddress= <i>ipadd ipv6add</i>] [TIMEOut=1..30] [UPCount=1..100]	16-14
SET PKI [CERTstorelimit= <i>max-certificates</i>] [CMPRETRYMax= <i>retries</i>] [CMPRETRYPeriod= <i>seconds</i>] [CRLUPdateperiod= <i>hours</i>] [SUBjectaltname= <i>ipadd name</i>]	46-26
SET PKI CERTificate= <i>name</i> [TRUsted={TRUE FALSE YES NO ON OFF}] [TYpe={CA SELF ENDentity EE}]	46-27
SET PKI CRL= <i>name</i> [LOCation={ <i>url localfile</i> }] [PASSword= <i>password</i>] [USERname= <i>username</i>]	46-27
SET PKI LDaprepository= <i>name</i> [LOCation= <i>ldap-url</i>] [PASSword= <i>password</i>] [USERname= <i>username</i>]	46-28
SET PORTAuth Port={ALL <i>port-name</i> } SUPPLicantmac= <i>macadd</i> [[[CONTRol={AUTHorised UNauthorised AUTO}] [MAXReq=1..10] [QUIETperiod=0..65535] [REAUTHENabled={TRUE FALSE}] [REAUTHMax=1..10] [REAUTHPeriod=1..86400] [SERVERTimeout=1..60] [SUPPTimeout=1..60] [TXperiod=1..65535]]][DEFAult}]	4-32
SET PORTAuth Port={ALL <i>port-name</i> } TYpe=Authenticator [CONTRol={AUTHorised AUTO UNauthorised}] [MAXReq=1..10] [MODE={MULTI SIngle}] [PIGgyback={TRUE FALSE}] [QUIETperiod=0..65535] [REAUTHENabled={TRUE FALSE}] [REAUTHMax=1..10] [REAUTHPeriod=1..86400] [SERVERTimeout=1..60] [SUPPTimeout=1..60] [TXperiod=1..65535]	4-28
SET PORTAuth Port={ALL <i>port-name</i> } TYpe=BOth [AUTHPeriod=1..60] [CONTRol={AUTHorised UNauthorised AUTO}] [HELDPeriod=0..65535] [MAXReq=1..10] [MAXStart=1..10] [MODE={MULTI SIngle}] [PIGgyback={TRUE FALSE}] [QUIETperiod=0..65535] [REAUTHENabled={TRUE FALSE}] [REAUTHMax=1..10] [REAUTHPeriod=1..86400] [SERVERTimeout=1..60] [STARTperiod=1..60] [SUPPTimeout=1..60] [TXperiod=1..65535] [USERName= <i>login-name</i> PASSword= <i>password</i> [METHod={OTP[ENCryption={MD4 MD5}]]STandard}]]	4-28
SET PORTAuth Port={ALL <i>port-name</i> } TYpe=Supplicant [AUTHPeriod=1..60] [HELDPeriod=0..65535] [MAXStart=1..10] [STARTperiod=1..60] [USERName= <i>login-name</i> PASSword= <i>password</i> [METHod={OTP[ENCryption={MD4 MD5}]]STandard}]]	4-28
SET PORTAuth USERName= <i>login-name</i> PASSword= <i>password</i> [METHod={OTP[ENCryption={MD4 MD5}]]STandard}]	4-34



SET PPP [DNSPRIMARY= <i>ipadd</i>] [DNSSECONDARY= <i>ipadd</i>] [WINSPRIMARY= <i>ipadd</i>] [WINSSECONDARY= <i>ipadd</i>]	9-81
SET PPP ACSERVICE= <i>service-name</i> [ACRADIUS={OFF ON}] [MAXSESSIONS=1...512] [TEMPLATE=ppp-template] [VLAN={NONE 0..4094}]	9-88
SET PPP TEMPLATE= <i>template</i> [AUTHENTICATION={CHAP EITHER PAP NONE}] [BAP={ON OFF}] [BAPMODE={CALL CALLBACK}] [CBDELAY=1..100] [CBMODE={ACCEPT OFF REQUEST}] [CBNUMBER= <i>e164number</i>] [CBOperation={E164NUMBER USERAUTH}] [COMPALGORITHM={PREDICTOR STACLZS}] [COMPRESSION={ON OFF LINK}] [DEBUGMAXBYTES=16..256] [DESCRIPTION= <i>description</i>] [ECHO={ON OFF <i>period</i> }] [ENCRYPTION={ON OFF}] [FRAGMENT={ON OFF}] [FRAGOVERHEAD=0..100] [IDLE={ON OFF <i>time</i> }] [INDATALIMIT={NONE 1..65535}] [IPPOOL={ <i>pool-name</i> NONE}] [IPREQUEST={ON OFF}] [LOGIN={ALL RADIUS TACACS USER}] [LQR={ON OFF <i>period</i> }] [MAGIC={ON OFF}] [MAXLINKS=1..64] [MRU={ON OFF 256..1656}] [MTU=256..1500 256..1492] [[MULTILINK={ON OFF}] [NULLFRAGTIMER= <i>time</i>] [ONLINELIMIT={NONE 1..65535}] [OUTDATALIMIT={NONE 1..65535}] [PASSWORD= <i>password</i>] [PREDCHECK={CRC16 CRCCITT}] [RECHALLENGE={ON OFF 360..3600}] [RESTART= <i>time</i>] [STACCHECK={LCB SEQUENCE}] [STARENTITY=1..255] [TOTALDATALIMIT={NONE 1..65535}] [USERNAME= <i>username</i>]	9-90
SET PPP= <i>ppp-interface</i> [OVER= <i>physical-interface</i>] [AUTHENTICATION={CHAP EITHER PAP NONE}] [AUTHMODE={IN OUT INOUT}] [BAP={ON OFF}] [BAPMODE={CALL CALLBACK}] [CBDELAY=1..100] [CBMODE={ACCEPT OFF REQUEST}] [CBNUMBER= <i>e164number</i>] [CBOperation={E164NUMBER USERAUTH}] [COMPALGORITHM={PREDICTOR STACLZS}] [COMPRESSION={ON OFF LINK}] [CONFIGURE={ <i>value</i> CONTINUOUS}] [DEBUGMAXBYTES=16..256] [DESCRIPTION= <i>description</i>] [DOWNRATE=0..100] [DOWNTIME= <i>time</i>] [ECHO={ON OFF <i>period</i> }] [ENCRYPTION={ON OFF}] [FRAGMENT={ON OFF}] [FRAGOVERHEAD=0..100] [IDLE={ON OFF <i>time</i> }] [INDATALIMIT={NONE 1..65535}] [IPPOOL={ <i>pool-name</i> NONE}] [IPREQUEST={ON OFF}] [LQR={ON OFF <i>period</i> }] [MAGIC={ON OFF}] [MAXLINKS=1..64] [MODEM={ON OFF}] [MRU={ON OFF 256..1656}] [NULLFRAGTIMER= <i>time</i>] [ONLINELIMIT={NONE 1..65535}] [OUTDATALIMIT={NONE 1..65535}] [PASSWORD= <i>password</i>] [PREDCHECK={CRC16 CRCCITT}] [RECHALLENGE={ON OFF 360..3600}] [RESTART= <i>time</i>] [STACCHECK={LCB SEQUENCE}] [STARENTITY=1..255] [TERMINATE={ <i>value</i> CONTINUOUS}] [TOTALDATALIMIT={NONE 1..65535}] [TYPE={DEMAND PRIMARY SECONDARY}] [UPRATE=0..100] [UPTIME= <i>time</i>] [USERNAME= <i>username</i>]	9-81
SET PRI= <i>instance</i> [Clock={INteRnal LIne}] [CODE={STAndard ALteRnate}] [CRC={OFF CHEcking REPorting}] [ENcoding={B8zs B7zs AMi}] [ERROr_threshold= <i>error-frames</i>] [FRAming={ESF SF}] [IDle= <i>character</i>] [INBandloopback={LIne PAYload}] [INteRframe_flags= <i>extra-flags</i>] [ISDNslots= <i>slot-list</i>] [LBO={NONE -7.5db -15db -22.5db}] [LINelength=0..65535] [MODE={ISDN TDM MIXed}] [TDMslots= <i>slot-list</i>]	11-104
SET Q931= <i>interface</i> [DOVnumber= <i>number</i>] [INTid= <i>hex-string</i>] [NONum={ACcept REJect}] [NOSub={ACcept REJect}] [NUM1= <i>number</i>] [NUM2= <i>number</i>] [PROfile={5ESS AUS CHINA DMS-100 ETSI JAPAN KOREA NI1 NZ}] [RAte={56K 64K}] [SPID1= <i>spid</i>] [SPID2= <i>spid</i>] [SUB1= <i>subaddress</i>] [SUB2= <i>subaddress</i>] [timer={OFF <i>time</i> }]	11-107
SET RSVP INteRface={ <i>interface</i> DYNAMIC} [MAXbandwidth=0..100] [ENCapsulation={UDP RAW}]	40-17
SET RSVP PROXY= <i>name</i> [FLOWspec= <i>flowspec</i>] [SEssion= <i>protocol,ipadd[/port[-port]]</i>] [SMask= <i>ipadd</i>]	40-18
SET RSVP PROXY= <i>name</i> [PATH= <i>ipadd[/port]</i>] [PMask= <i>ipadd</i>] [TSPEC= <i>tspec</i>] [TImeout=10..1800] [SEssion= <i>protocol,ipadd[/port[-port]]</i>] [SMask= <i>ipadd</i>]	40-18
SET SA= <i>sa-id</i> [DEBUGPktttype={Short Full}] [DiRection={IN OUT BOTH}] [ENCAlg={DES 3DES2key 3DESInner}] [ENCKey= <i>key-id</i>] [SPi= <i>spi</i>]	45-85
SET SCript= <i>filename</i> LIne= <i>line</i> [AftEr= <i>line</i>] [BEfore= <i>line</i>] [TExt= <i>text</i>]	34-11
SET SERvice= <i>service-name</i> [DESCRiption=" <i>description</i> "] [IPAddress= <i>ipadd</i>] [VISible={ON OFF}]	21-21
SET SIP GATEWay [NATIp= <i>ipaddr</i>] [DEFAULtport={ <i>udpport</i> <i>tcpport</i> }]	52-39
SET SIP INteRface= <i>interface</i> [CAPABility={ALL PCMU PCMA G723R53 G723R63 G729A ,...}] [DOmain= <i>domain</i>] [DSCP= <i>dscp</i> priority] [DTMFrelay={RTP NONE}] [LOCATionserver= <i>ipaddr[:udpport tcpport]</i> [: <i>ipaddr[:udpport tcpport]</i>]] [PASSword={NONE <i>password</i> }] [PHOnenumber= <i>number</i>] [PROXYserver= <i>ipaddr[:udpport tcpport]</i> [: <i>ipaddr [:udpport tcpport]</i>]] [RTPport= <i>udpport</i>] [TOS= <i>tos</i> priority] [USERName={NONE <i>username</i> }]	52-37



SET SKEY [METHod={SKEY OTP}] [ENCryption={MD4 MD5}	1-120
SET SNMP COMMUNITY=name [ACCESS={READ WRITE}] [OPEN={ON OFF YES NO TRUE FALSE}]	38-38
SET SNMP ENGINEID= <i>snmpEngineID</i>	38-39
SET SNMP GROUP= <i>group-name</i> [READVIEW= <i>view-name</i>] [WRITEVIEW= <i>view-name</i>] [NOTIFYVIEW= <i>view-name</i>]	38-40
SET SNMP LOCal={none 1..15}[VERson={V1 V2 V3 ALL}]	38-40
SET SNMP TARGETADDR= <i>address-name</i> [IP= <i>target-ipadd</i>] [UDP= <i>udp-port</i>] [PARAMS= <i>params-name</i>] ..	38-41
SET SNMP TARGETPARAMS= <i>params-name</i> [SECURITYLEVEL={NOAUTHNOPRIV AUTHNOPRIV AUTHPRIV}] [USER= <i>user-name</i>]	38-42
SET SNMP USER= <i>user-name</i> [GROUP= <i>group-name</i>] [AUTHPROTOCOL={NONE MD5 SHA}] [AUTHPASSWORD= <i>password</i>] [PRIVPROTOCOL={NONE DES}] [PRIVPASSWORD= <i>password</i>]	38-43
SET SQOS DAR= <i>id-list</i> [CODEC={AUDIo VIDeo ANY}] [DESCRiption= <i>description</i>] [DSTIp={ <i>ipadd</i> /0..32 <i>ipv6add</i> /0..128}] [SRCIp={ <i>ipadd</i> /0..32 <i>ipv6add</i> /0..128}] [INActivetimeout={1..3600 NONE}] [PROToocol={SIP RTSp H323 ALL}] [H323Port=1..65535] [RTSPPort=1..65535] [SIPPort=1..65535]	6-119
SET SQOS DSCPMap= <i>id-list</i> [DESCRiption= <i>description</i>]	6-120
SET SQOS DSCPMap= <i>id-list</i> Table=PREmark [DESCRiption= <i>description</i>] [DSCP= <i>dscp-list</i>] [NEWBwclass=1..3] [NEWDscp=0..63]	6-120
SET SQOS DSCPMap= <i>id-list</i> Table=REMark [DESCRiption= <i>description</i>] [BWCclass= <i>bwclass-list</i>] [DSCP= <i>dscp-list</i>] [NEWBwclass=1..3] [NEWDscp=0..63]	6-120
SET SQOS INTERface= <i>interface</i> [INpolicy={0..9999 NONE}] [OUTpolicy={0..9999 NONE}] [TUNnelpolicy={0..9999 NONE}]	6-122
SET SQOS METER= <i>id-list</i> [DESCRiption= <i>description</i>] [IGNorebwclass={Yes No}] [MINbandwidth= <i>rate</i> [Kbps Mbps Gbps]] [MAXbandwidth= <i>rate</i> [Kbps Mbps Gbps]] [MINBUrsize= <i>burstsize</i> [Bytes Kbytes Mbytes Gbytes]] [MAXBUrsize= <i>burstsize</i> [Bytes Kbytes Mbytes Gbytes]] [TYPE={SRtcm TRtcm}]	6-123
SET SQOS POLIcy= <i>id-list</i> [BWCclass3action={DROP PAUSE NONE}] [DEFaulttrafficclass={0..9999 NONE}] [DESCRiption= <i>description</i>] [DSCPMap={0..9999 NONE}] [IGNOREPrenatinfo={YES NO}] [METER={0..9999 NONE}] [PAUSEAction={NONE Log TRap BOth}] [PAUSETIme={1..30}] [REMarking={0..63 USEDscpmap NONE}] [REMARKVlanpri={0..7 NONE}] [SYSTEMTraffic={5..50}] [VIRTbw={ <i>bandwidth</i> [Kbps Mbps Gbps] NONE}] [WEIGHtscheduler={WRR DWrr}]	6-130
SET SQOS RED= <i>id-list</i> [AVERaging=0..99] [DESCRiption= <i>description</i>] [START1=0..100] [STOP1=0..100] [DROP1=0..100] [START2=0..100] [STOP2=0..100] [DROP2=0..100] [START3=0..100] [STOP3=0..100] [DROP3=0..100]	6-133
SET SQOS TRafficclass= <i>id-list</i> [BWCclass3action={DRop PAuse NONE}] [DESCRiption= <i>description</i>] [MAXQlen=1..1023] [METER={0..9999 NONE}] [PAUSEAction={NONE Log TRap BOth}] [PAUSETIme={1..30}] [PREMARKBwcl={1..3 USEDscpmap}] [PREMARKDscp={0..63 USEDscpmap NONE}] [{PRIOrity=0..15 WEIght=0..100}] [QLIMITExceedaction={NONE Log TRap BOth}] [QUEUEDrop={Head Tail}] [RED={0..9999 NONE}] [REMarking=0..63 USEDscpmap NONE]] [REMARKVlanpri={0..7 NONE}] [VIRTbw={ <i>bandwidth</i> [Kbps Mbps Gbps] NONE}] [WEIGHtscheduler={WRR DWrr}]	6-135
SET SSH SERVer [HOSTkey= <i>key-id</i>] [SERVERkey= <i>key-id</i>] [EXPIrytime= <i>hours</i>] [IDLEtimeout=0..4294967295] [LOGintimeout= <i>seconds</i>] [MAXSessions=0..30]	43-13
SET SSH USER= <i>username</i> {PASSword= <i>password</i> KEYid= <i>key-id</i> } [IPAddress= <i>ipadd</i> <i>ipv6add</i>] [MASK= <i>mask</i>]	43-15
SET SSL [Cachetimeout= <i>cachetimeout</i>] [DEbugipaddress={ALL <i>ipadd</i> }] [MAXsessions= <i>maxsessions</i>]	51-9
SET STAR= <i>entity-id</i> {MODE={MASter SLave STAndby} NETkey {RANDOM VALue= <i>value</i> } [MKT RANDOM]	44-15
SET STT= <i>sttname</i> [LSYN= <i>localsyn</i>] [RSYN=0..7] [IP= <i>ipadd</i>] [DATALEN= <i>maxlength</i>]	13-6
SET SWITch AGEingtimer=16..4080	3-33
SET SWITch BACKOff={AGGressive NORMal}	2-20
SET SWITch BACKPPressure={ON OFF}	2-20
SET SWITch BROadcastlimit={ON OFF}	2-21



SET SWItch BUfFerpool={Equal ADApTive}	2-21
SET SWItch EXCessivecollision={DROp RETry}	2-22
SET SWItch FLOWcontrol={ON OFF}	2-22
SET SWITCH PORT={ <i>port-list</i> ALL} [DESCription= <i>description</i>] [SPeed={AUTOnegotiate 10MHAlf 10MFUll 100MHAlf 100MFUll}]	2-23
SET SWItch PORT={ <i>port-list</i> ALL} [POLarity={MDI MDIX}] [BCLimit={NONE <i>limit</i> }] [DESCription= <i>description</i>] [DLFLimit={NONE <i>limit</i> }] [INFILTerIng=OFF ON] [MCLimit={NONE <i>limit</i> }] [SPeed={AUTOnegotiate 10MHAlf 10MFUll 10MHAUto 10MFAuto 100MHAlf 100MFUll 100MHAUto 100MFAuto}]	3-34
SET SWItch QOS= <i>P0,P1,P2,P3,P4,P5,P6,P7</i>	3-37
SET SWItch QOS= <i>P1,P2,P3,P4,P5,P6,P7,P8</i>	2-23
SET SYN= <i>n</i> [C={ON OFF I}] [CD={ON OFF DTR}] [CTS={ON OFF RTS}] [DATAsense={NORMAl INVerted}] [DSR={ON OFF DTR}] [DTR={ON OFF DSR}] [I={ON OFF C}] [MAXOqlen= <i>max-queue</i>] [MINTxint= <i>min-interval</i>] [RTS={ON OFF CTS}] [SPeed= <i>speed</i>] [TXClock={FALLing RISing}]	7-46
SET SYStem CONtact= <i>contact-name</i>	1-121
SET SYStem COUntry={AUSTRAlia AUSTRiA BELgium CANAda DENMark EIRE FINLand FRAnce GERmany ICELand ITAlY NETHerlands NEWZealand NORWay PORTUgal SINGapore SPAIn SWITZerland SWEden TURkey UAE UK USA NONE}	1-122
SET SYStem DISTinguihsedname={ <i>dist-name</i> NONE}	1-123
SET SYStem LOCation= <i>location</i>	1-123
SET SYStem NAME= <i>name</i>	1-124
SET SYStem TERRitory={AUStralia CHIna EUROpe JAPan KORea NEWZealand USA}	1-124
SET TACPlus Key= <i>key</i>	1-125
SET TACPlus SERVer= <i>ipaddress</i> [Key= <i>key</i>] [Port= <i>port</i>] [SINGLEconnection={Yes No}] [TIMEOUT=1..10] [LOCAL={NONE 1..15}]	1-125
SET TACPlus TELnet={0..15 None}	1-126
SET TELnet [TErMtype= <i>termstring</i>] [INsertnull={ON OFF}] [LISTEnport= <i>port</i>] [IDLEtimeout=0..4294967295] [MAXSessions=0..30]	21-22
SET TPAD= <i>name</i> [CALLretry= <i>number-retries</i>] [CHECKSum={ON OFF YES NO}] [ISDNcall= <i>isdn-call-name</i>] [FAStdisconnect={ON OFF}] [MAXConnections= <i>connections</i>] [MAXTransfers= <i>transfers</i>] [NOCARRIERresponse={ON OFF}] [SILentretry={ON OFF}] [TCPport= <i>port</i>] [TRansfertype={MULTIThread MULTIVc NORMAl TRANSParent}]	39-23
SET TRAcE [IPIpaddress= <i>ipadd</i>] [ADDROnly={No OFF ON Yes}] [MAXTtl= <i>number</i>] [MINTtl= <i>number</i>] [NUMBER= <i>number</i>] [Port= 1..65535] [SCReenoutput={No OFF ON Yes}] [Source= <i>ipadd</i>] [TIMEOut= <i>number</i>] [TOS=0..25]	14-165
SET TRIGGer= <i>trigger-id</i> [CPU= <i>value</i>] [DIRECTION={UP DOWN ANY}] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{Date= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FOREver count}] [TEST={YES NO ON OFF True False}]	30-16
SET TRIGGer= <i>trigger-id</i> [FIREwall={ALL DOSAttack FRAGattack HOSTscan PORTscan SMUrfattack SYNAttack TCPAttack}]] [MODE={STARt END BOTH}] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{Date= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FOREver count}] [TEST={YES NO ON OFF True False}]	30-16
SET TRIGGER= <i>trigger-id</i> [INTErface= <i>interface</i>] [EVENt={UP DOWN FAIL ANY}] [CIRCUit= <i>miox-circuit</i>] [CP={APPLE ATCP BCP CCP DCP DNCP IPcp IPXcp LCP}] [DLCi= <i>dLCi</i>] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{Date= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FOREver count}] [TEST={YES NO ON OFF True False}]	30-16
SET TRIGGer= <i>trigger-id</i> [MEMory= <i>value</i>] [DIRECTION={UP DOWN ANY}] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{Date= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FOREver count}] [TEST={YES NO ON OFF True False}]	30-16
SET TRIGGer= <i>trigger-id</i> [MODUle] [<i>module-parameters...</i>] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{Date= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FOREver count}] [TEST={YES NO ON OFF True False}]	30-16

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

SET TRIGger= <i>trigger-id</i> [PERiodic[= <i>minutes</i>]] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [TEST={YES NO ON OFF True False}]	30-16
SET TRIGger= <i>trigger-id</i> [REBoot[={REStart CRASH ALL}]] [AFTer= <i>hh:mm</i>] [BEFore= <i>hh:mm</i>] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [TEST={YES NO ON OFF True False}]	30-16
SET TRIGger= <i>trigger-id</i> [Time[= <i>hh:mm</i>]] [{DATE= <i>date</i> DAYS= <i>day-list</i> }] [NAME= <i>name</i>] [REPeat={Yes No ONCe FORever count}] [TEST={YES NO ON OFF True False}]	30-16
SET TTy [History=0..99] [PAge=4..99] [PRompt={string-15 DEfault OFF}] [TYpe={Dumb Vt100}]	21-23
SET USEr [LOGINFail=1..10] [LOCKoutpd=0..30000] [MANpwdfail=1..5] [Securedelay=10..600] [MInpwdlen=1..23] [TACRetries=0..10] [TACTimeOut=1..60] [LOgin={True False ON OFF Yes No}]	1-127
SET USEr= <i>login-name</i> [CALLingnumber= <i>number</i>] [CBNUmber= <i>e164number</i>] [DESCRiption= <i>description</i>] [Ipaddress= <i>ipaddr</i>] [IPXnetwork= <i>network</i>] [LOgin={True False ON OFF Yes No}] [MASK= <i>ipaddr</i>] [MTu=40..1500] [NETMASK= <i>ipaddr</i>] [Password= <i>password</i>] [PRIVilege={User MANager SEcurityofficer}] [TELnet={Yes No}]	1-127
SET VLAN={ <i>vlanname</i> 1..4094} Port={port-list ALL} FRAMe={UNTAGged TAGged}	2-25
SET VLAN={ <i>vlan-name</i> 1..4094} Port={port-list ALL} FRAMe={UNTAGged TAGged}	3-38
SET VOIP AP INTERFACE=interface [BUFFLen= <i>blen</i>] [BUFFThr= <i>bthr</i>] [CAPABILITY={ALL PCMU PCMA G723R53 G723R63 G729A T38} [,...]] [COUNTRY={ITALY JAPAN EUROPE HOLLAND AUSTRALIA NEWZEALAND USA CHINA KOREA}] [CRITICALDIGITTIME= <i>msec</i>] [IMPEDANCE={600R 600C 900C CPLX1 CPLX2}] [INTERDIGITTIME= <i>msec</i>] [LEC= <i>lecframe</i>] [OFFHOOKTIME= <i>msec</i>] [ONHOOKTIME= <i>msec</i>] [RTPPORT= <i>udpport</i>] [RXGAIN= <i>gain</i>] [TXGAIN= <i>gain</i>]	52-40
SET VOIP BOOTcode= <i>filename</i> SERVER={ <i>ipaddr</i> flash}	52-42
SET VOIP ENGIne= <i>engine</i> IP= <i>ipaddr</i> [GATEway= <i>ipaddr</i>]	52-39
SET VOIP File= <i>filename</i> PROTOcol={H323 SIP} Type={FXS FXO}	52-42
SET VOIP PHOne INTERface=interface [[BUFFLen= <i>blen</i>] [BUFFThr= <i>bthr</i>] [COUNTRYname={AUSTria AUStria CHIna FRance GERMANY1 GERMANY2 HOLland ITALy JAPan KORea NEWZealand SPain UK USA1 USA2}]] [CADence={RING TRING TDIAL TBUSY TDISC TWAIT}] [CFreq= <i>frequency-value</i>] CValue={cadence-values}[,...] [DIGITtout= <i>dtout</i>] [FValue= <i>frequency-value</i>] [IMPEDance={600R 600C1 600C2 900R 900C1 900C2 900C3 CPLX1 CPLX2 CPLX3 CPLX4 CPLX5 CPLX6 CPLX7 CPLX8 GLOBALcplx}] [LEC= <i>lecframe</i>] [RXgain= <i>gain</i>] [TXgain= <i>gain</i>] [VAD={ON OFF}]	52-43
SET VOIP PUBLIC INTERface=interface	52-50
SET VRRP= <i>vr-identifier</i> [ADINTERval=1..255] [ADOPTvrip={ON OFF}] [AUTHentication={NONE PLAINtext}] [PASSword= <i>password</i>] [PORTMOnitoring={ON OFF}] [STEPVALue={stepvalue PRoportional}] [PREEmpt={ON OFF}] [PRIOrity=1..254]	47-19
SET X25C HUNTGROUp= <i>huntname</i> [IPADDRESS= <i>ipaddr</i>] [DTEADDRESS= <i>dteaddr</i>] [FORWARDTIME=1..360] [RECONNECTTIME=1..360]	12-65
SET X25C TCPKEEPALIVE [TXINT=5..180] [FAILNUMBER=2..10]	12-66
SET X25C=x25-interface [DEFPKT={128 256 512 1024 2048 4096}] [DEFTHROUGH={75 150 300 600 1200 2400 4800 9600}] [DEFWIN=2..7] [HGROUp[= <i>huntname</i>]] [INLCGN=0..15] [INLCN=0..128] [MAXACTIVE=0..128] [OUTLCGN=0..15] [OUTLCN=0..128] [PACKETSIZE={ON OFF}] [THROUGHPUT={ON OFF}] [TWOLCGN=0..15] [TWOLCN=0..128] [WINDOW={ON OFF}]	12-63
SET X25T CPAR=call-index [MAXDATA={128 256 512 1024}] [NUI= <i>nui</i>] [RMAXDATA={128 256 512 1024}] [RWINDOW=1..127] [TMAXDATA={128 256 512 1024}] [TWINDOW=1..127] [USERDATA= <i>hex-string</i>] [WINDOW=1..127]	12-68
SET X25T=x25-interface [MAXACTIVE=0..4095] [MODULUS={8 128}] [T20=1..360] [T21=1..360] [T22=1..360] [T23=1..360] [T24={1..360 OFF}] [T27={1..360 OFF}] [MINRECALL=1..360] [R20=0..65535] [R22=0..65535] [R23=0..65535] [R27=0..65535] [NPVC=0..4095] [DEFCPAR=0..8] [DTEADDRESS= <i>dteaddress</i>] [LIC=0..4095] [HIC=0..4095] [LTC=0..4095] [HTC=0..4095] [LOC=0..4095] [HOC=0..4095] [ROLE={DYNAMIC DCE DTE}]	12-66



SHoW ACC	28-31
SHoW ACC CAll[=name]	28-32
SHoW ACC DOmainname	28-36
SHoW ACC SCript[=script-name]	28-36
SHoW ADSI[={interface ALL}]	8-36
SHoW ADSI[={interface ALL}] COUnter	8-38
SHoW Allas	1-130
SHoW APPlE	31-49
SHoW APPlE AARP	31-50
SHoW APPlE CIRCUit	31-51
SHoW APPlE COUnter={ALL AARP ATP DDp NBp PACket PKT PORT ROUte RTMp ZIp ZOne}	31-52
SHoW APPlE DLCi	31-58
SHoW APPlE PACKETFilter[=filter-id]	31-59
SHoW APPlE PORT[=port]	31-61
SHoW APPlE ROUte	31-63
SHoW APPlE ROUTEFilter[=filter-id]	31-64
SHoW APPlE ZOne	31-65
SHoW APPlE ZONEFilter[=filter-id]	31-66
SHoW ASYn[=port-number ALL] [{COUnters={Diagnostic INTErface Rs232}} History Summary]	7-49
SHoW ATM=0..9 [CHANnel={1..30 ALL}] COUnter	8-43
SHoW ATM=0..9 CHANnel={1..30 ALL}	8-41
SHoW ATM[=0..9]	8-39
SHoW BGP	49-111
SHoW BGP AGGregate	49-113
SHoW BGP BACKoff	49-115
SHoW BGP CONfederation	49-114
SHoW BGP IMPort	49-117
SHoW BGP MEMlimit	49-118
SHoW BGP MEMlimit SCAN	49-119
SHoW BGP NETwork	49-121
SHoW BGP PEer[=ipadd]	49-122
SHoW BGP PEERTemplate[=1..30]	49-127
SHoW BGP ROUte[=prefix] [REGexp=aspathregexp] [COMmunity={INTErnet NOAdvertise NOExport NOEXPORTSubconfed 1..4294967295}]	49-129
SHoW BOOTp RELAy	14-166
SHoW BRI[=instance] CONfiguration	11-110
SHoW BRI[=instance] COUnter[={INTErface BRI}][CHANnel={B1 B2 D 0 1 2}]	11-111
SHoW BRI[=instance] CTest	11-116
SHoW BRI[=instance] DEBUg	11-117
SHoW BRI[=instance] STate	11-118
SHoW BRI[=instance] TEst	11-121
SHoW BRIDge	24-36
SHoW BRIDge COUnter [PORT=1..32]	24-37
SHoW BRIDge FILter[=1..99] [ENTry=entry]	24-40
SHoW BRIDge GROUp[={groupname 1..32}]	24-42
SHoW BRIDge PORT[=1..32]	24-44
SHoW BRIDge PROTOcol	24-46
SHoW BRIDge SPanning	24-47
SHoW BRIDge STation [{Address=macadd [MASK=macadd]]PORT=1..32}]	24-49
SHoW BUFFer [SCAN[=address [QUEuepointers]]]	1-131



Show CLASSifier[= <i>id-list</i> ALL DYNAMIC]	5-22
Show CLNS	48-28
Show CLNS COUNTERS	48-36
Show CLNS[= <i>virtual-router-id</i>] ADJacency	48-28
Show CLNS[= <i>virtual-router-id</i>] AREa	48-30
Show CLNS[= <i>virtual-router-id</i>] CIRCUit[= <i>circ-id</i>] COUNTERS	48-34
Show CLNS[= <i>virtual-router-id</i>] CIRCUit[= <i>circ-id</i>]	48-31
Show CLNS[= virtual-router-id] DETail	48-37
Show CLNS[= <i>virtual-router-id</i>] RA	48-39
Show CLNS[= <i>virtual-router-id</i>] ROUTe[=ALL]	48-40
Show CONFIG [DYNAMIC[= <i>module-id</i>]]	1-133
Show CPU	1-136
Show DEBUG [STACK FULL]	1-137
Show DECnet	20-28
Show DECnet COUNTER[={GLOBAL INTERFACE ROUTE}]	20-29
Show DECnet EXclusion	20-31
Show DECnet INclusion	20-32
Show DECnet INTERFACE	20-33
Show DECnet LPN	20-34
Show DECnet ROUTe	20-35
Show DHCP	35-27
Show DHCP CLIENT[= <i>ipaddress</i>] [RANGE= <i>name</i>]	35-28
Show DHCP POLICY[= <i>name</i>]	35-30
Show DHCP RANGE[= <i>name</i>]	35-31
Show DHCP6	36-23
Show DHCP6 CLIENT [RANGE= <i>name</i>] [TYPE={PD NORMAL TEMP}]	36-24
Show DHCP6 COUNTER [INTERFACE= <i>interface</i>]	36-26
Show DHCP6 INTERFACE[= <i>interface</i>]	36-29
Show DHCP6 KEY[= <i>key-id</i>]	36-30
Show DHCP6 POLICY[= <i>name</i>]	36-31
Show DHCP6 RANGE[= <i>name</i>]	36-32
Show DHCP6 SERVER	36-34
Show DVMrp	17-66
Show DVMrp COUNTERS	17-67
Show DVMrp DEBUG	17-68
Show DVMrp FORWARDING	17-68
Show DVMrp INTERFACE	17-69
Show DVMrp NEIGHBOUR	17-70
Show DVMrp ROUTe	17-71
Show ENCo	25-28
Show ENCo CHANNEL[= <i>channel</i>] [COUNTERS]	25-30
Show ENCo COUNTERS={AES DES DH HARDWARE HMAC IPSec MAC PRED QUEUES RSA SSL STAC USER UTIL}	25-35
Show ENCo KEY[= <i>key-id</i>]	25-54
Show ETH= <i>n</i> CONFIGURATION	7-55
Show ETH[= <i>n</i>] COUNTERS[={COLLISION DIAGNOSTIC DOT3STAT INTERFACE}]	7-57
Show ETH[= <i>n</i>] MACADDRESS	7-63
Show ETH[= <i>n</i>] RECEIVE	7-63
Show ETH[= <i>n</i>] STATE	7-64
Show EXCEPTION	1-143



Show FEAture[={featurename index}]	1-144
Show FFile[=file-identifier] [CHECK]	1-146
Show FIlle[=filename] [DEvice={Al Flash NVs}]	1-148
Show FIREwall	41-80
Show FIREwall ACCounting [POLIcy=policy-name] [REVerse=number] [TAil=number]	41-81
Show FIREwall ARP [POLIcy=policy-name]	41-83
Show FIREwall EVent={ALLOW DENY NOTify} [POLIcy=policy-name] [REVerse=number] [TAil=number]	41-84
Show FIREwall POLIcy=policy-name [COUnter] [DYnamic] [LISt] [SUMmary] [USer]	41-86
Show FIREwall POLIcy[=policy-name] ATTack	41-100
Show FIREwall SESSion[=session-number] [POLIcy=policy-name] [COUnter] [POrt={port-port service-name}] [PROToCol={protocol ALL EGP GRE ICmp OSPF TCP UDP}] [SUMmary] [UPNP]	41-101
Show FLash [FFs]	1-150
Show FLash PHYSICAL	1-152
Show FRamerelay[=fr-interface] [{CIRUTILisation CONFig COUnter DEBUg LMI UTILisation}]	10-49
Show FRamerelay[=fr-interface] DLC[={ALL dlc}] [COUnter]	10-59
Show FRamerelay[=fr-interface] LI[={ALL logical-interface}] [COUnter]	10-66
Show GRE GENeral	29-20
Show GRE TUNnel	29-21
Show GRE[=gre-number]	29-18
Show GUI	1-153
Show H323 ENTry ENGIne=engine	52-52
Show H323 GATEway	52-53
Show H323 INTerface=interface	52-51
Show HTTP CLient	1-154
Show HTTP DEBUg	1-155
Show HTTP SERVer	1-156
Show HTTP SERVer SESSion	1-157
Show IGMPsNooping ROUTERAddress	17-72
Show INSTall	1-158
Show INTerface[=ifIndex interface] [COUnters] [PRIOrityqueue]	7-66
Show IP	14-168
Show IP ADVertise	14-171
Show IP ARP	14-172
Show IP ASPATHlist[=1..99]	49-131
Show IP COMMunitylist[=1..99]	49-132
Show IP COUnter[={ALL ARP EGP ICmp INterface IP MUlticast ROutes SNmp UDp}]	14-173
Show IP DEBUg[=1..40]	14-182
Show IP DNS	14-183
Show IP DNS CAChe	14-184
Show IP EGP	14-185
Show IP FILter[= 0..399]	14-186
Show IP HElper [COUnter]	14-188
Show IP HOSt	14-189
Show IP ICMPReply	14-190
Show IP IGMP [COUnter] [INTerface=interface]	17-73
Show IP IGMP DEBUg	17-76
Show IP INTerface[=interface] [COUnter[=MULTicast]]	14-191
Show IP NAT [COUnter] [SUMmary]	14-195
Show IP POOL[=pool-name] [IPaddress=ipadd[-ipadd]] [SUMmary]	14-199



SHoW IP PREFIXList[= <i>name</i>]	49-133
SHoW IP RIP [INTERface= <i>interface</i>] [CIRCUit= <i>miox-circuit</i>] [DLCi= <i>dlci</i>] [IP= <i>ipadd</i>]	14-201
SHoW IP RIP COUnTer[={Detail Summary}] [INTERface= <i>interface</i>] [CIRCUit= <i>miox-circuit</i>] [DLCi= <i>dlci</i>] [IP= <i>ipadd</i>]	14-203
SHoW IP RIPTimer	14-205
SHoW IP ROUte FILter	14-210
SHoW IP ROUte MULTicast	14-211
SHoW IP ROUte PREference	14-212
SHoW IP ROUte TEMPlate[= <i>name</i>]	14-212
SHoW IP ROUte[= <i>ipadd</i>] [{GENeral CACHe COUnT FUL}]	14-206
SHoW IP ROUTEMap[= <i>routemap</i>]	49-135
SHoW IP SA INTERface= <i>interface</i>	14-214
SHoW IP TRusted	14-215
SHoW IP UDP	14-215
SHoW IPSec	45-86
SHoW IPSec BUNDlespecitification[= <i>bundlespecification-id</i>]	45-86
SHoW IPSec COUnTer[={AH ALG COMp ESp MAIn SAD SETUP SPD}]	45-88
SHoW IPSec POLIcy[= <i>name</i>] [SABundle] [COUnTer]	45-105
SHoW IPSec SA[= <i>sa-id</i>] [COUnTer]	45-113
SHoW IPSec SASpecification[= <i>spec-id</i>]	45-120
SHoW IPV6	15-70
SHoW IPV6 COUnTer	15-72
SHoW IPV6 FILter[= <i>filter-id</i>]	15-76
SHoW IPV6 HOSt	15-78
SHoW IPV6 INTERface[= <i>interface</i>]	15-79
SHoW IPV6 MLD CONFig	18-43
SHoW IPV6 MLD COUnTers	18-44
SHoW IPV6 MLD DEBUg	18-45
SHoW IPV6 MLD INTERface= <i>interface</i>	18-40
SHoW IPV6 MULTicast	15-81
SHoW IPV6 NDCAche	15-82
SHoW IPV6 NDConfig [INTERface= <i>interface</i>]	15-83
SHoW IPV6 RIP [{COUnTer TIMer}]	15-85
SHoW IPV6 ROUte	15-87
SHoW IPV6 ROUte MULTicast[= <i>ipv6address</i>] [SOurce= <i>ipv6address</i>]	15-88
SHoW IPV6 ROUte PREference	15-90
SHoW IPV6 TUNnel	15-91
SHoW IPX	19-54
SHoW IPX CACHE	19-56
SHoW IPX CALLLOG[= <i>circuit</i>]	19-56
SHoW IPX CIRCUIT[= <i>circuit</i>]	19-60
SHoW IPX COUNTER[={CIRCUIT GATEWAY ROUTES}]	19-62
SHoW IPX EXCLUSION	19-65
SHoW IPX INCLUSION	19-66
SHoW IPX RIP[= <i>filter-number</i>]	19-67
SHoW IPX ROUTE	19-68
SHoW IPX SAP[= <i>filter-number</i>]	19-69
SHoW IPX SERVICE	19-70
SHoW IPX SPXSPOOF	19-71
SHoW ISAkmp	45-122



Show ISAKmp COUNTERS[={AGGressive GENeral HEARtbeat INFo IPSec MAIn NETwork QUick SAD SPD TRAnSACTION XDB}]	45-123
Show ISAKmp EXChange[=exchange-id]	45-151
Show ISAKmp POLIcy[=name]	45-159
Show ISAKmp SA[=sa-id]	45-162
Show ISDN CALL[={acnum name}]	11-123
Show ISDN CLIList[=0..99]	11-127
Show ISDN DOMainname	11-128
Show ISDN LOG	11-129
Show L2TP [COUNTER]	37-29
Show L2TP CALL[=name]	37-33
Show L2TP IP	37-35
Show L2TP TUNnel[=tunnelid] [CALL[=callid]] [COUNTER]	37-36
Show L2TP USer[=mapping]	37-44
SHOW LAPB[=lapb-interface] [{CONFIG COUNT IDLETIMER}]	12-68
Show LAPD[=interface]	11-130
Show LAPD[=interface] COUNt	11-132
Show LAPD[=interface] STAtE	11-134
Show LDAP [DEBUg]	1-159
Show LDAP REQuest[={ALL number}]	1-160
Show LOADBalancer	50-43
Show LOADBalancer AFFinity [{CLientip=ipadd}][RESource=resourcename][VIRTualbalancer=virtualbalancename}]	50-44
Show LOADBalancer REDUNDancy	50-47
Show LOADBalancer RESource[=resourcename]	50-49
Show LOADBalancer RESPool[=resourcepoolname]	50-51
Show LOADBalancer VIRTualbalancer[=virtualbalancename]	50-53
Show LOADBlancer CONnections[=virtualbalancename]	50-46
Show LOAdER	1-162
Show LOG COUNTER	33-40
Show LOG OUTput[={Temporary output-id}] [{FILter=filter-id FULL}]	33-42
Show LOG QUEue[=output-id]	33-45
Show LOG RECeive[=ipadd] [MASK=ipadd]	33-46
Show LOG STatus	33-47
Show LOG[=output-id] [DAte=[op]dd-mmm-yyyy] [DEVice=[op]device] [File=[op]filename] [FULL] [MASK=ipadd] [MODUle=[op]module-id] [MSGOnly] [MSGtext=[op]string] [ORIGin=ipadd] [REFerence=[op]string] [REVerse=[count]] [SEVerity=[op]severity] [SOUrceline=[op]line] [SUBType=[op]subtype-id] [TAil=[count]] [TIme=[op]hh:mm:ss] [TYpe=[op]type-id] [ZONe={time-zone-name utc-offset}]	33-34
Show LPD[=queue-name]	22-21
Show MAIL	1-163
Show MANager ASYN	1-165
SHOW MIOX[=x25t-interface]	12-73
SHOW MIOX[=x25t-interface] CIRCUIT[=circuit-name] [COUNTER ENCAP]	12-76
SHOW MIOX[=x25t-interface] COUNT	12-74
Show NTP	27-9
Show OSPF	23-49
Show OSPF AREa[={Backbone area-number}] [{FUL SUMmary}]	23-51
Show OSPF DEBUg	23-53
Show OSPF HOst[=ipadd] [AREa={Backbone area-number}]	23-53



SHoW OSPF INTeRface[=interface] [AREa={BAckbone area-number}] [IPaddress=ipadd] [{FUL SUMmary}]	23-55
SHoW OSPF LSA=link-id [AREa={BAckbone area-number}] [{FUL SUMmary}] [Type={ASBrsummary ASExternal ASNSSA ASSummary IPsummary SUMmary NETwork ROUTer}]	23-59
SHoW OSPF NEIghbour[=ipadd] [INTeRface=interface]	23-63
SHoW OSPF RANge[=ipadd] [AREa={BAckbone area-number}]	23-64
SHoW OSPF ROUte[=ipadd] [AREa={BAckbone area-number}] [Type={AB ASbr}]	23-65
SHoW OSPF STUB[=ipadd] [AREa={BAckbone area-number}]	23-67
SHoW PATch	1-165
SHoW PERM[=perm-name]	22-22
SHoW PIM	17-77
SHoW PIM BSRCandidate	17-78
SHoW PIM CONFig	17-79
SHoW PIM COUnters	17-79
SHoW PIM DEBUg	17-83
SHoW PIM INTeRface	17-84
SHoW pim NEIghbour	17-86
SHoW PIM ROUte	17-87
SHoW PIM RPCandidate	17-92
SHoW PIM RPSet	17-93
SHoW PIM STATerefresh	17-95
SHoW PIM TIMer	17-96
SHoW PIM6	18-45
SHoW PIM6 BSRCandidate	18-46
SHoW PIM6 CONFig	18-47
SHoW PIM6 COUnters	18-48
SHoW PIM6 DEBUg	18-51
SHoW PIM6 INTeRface	18-52
SHoW PIM6 NEIghbour	18-53
SHoW PIM6 ROUte	18-54
SHoW PIM6 RPCandidate	18-60
SHoW PIM6 RPSet	18-60
SHoW PIM6 STATerefresh	18-62
SHoW PIM6 TIMer	18-63
SHoW PING	14-216
SHoW PING POLI[=poll-id] [COUnter] [FUL] [STAt={UP DOWn CRItical}]	16-16
SHoW PKI [COUnters]	46-29
SHoW PKI CeRTificate[=name]	46-36
SHoW PKI CRL[=name]	46-39
SHoW PKI ENRollmentrequest[=name]	46-42
SHoW PKI KEYUpdaterequest[=name]	46-43
SHoW PKI LDaprepository	46-45
SHoW PORTAuth	4-36
SHoW PORTAuth COUnter PORT={ALL port-name}	4-37
SHoW PORTAuth MULTIsupplicant PORT={ALL port-name}	4-44
SHoW PORTAuth PORT={ALL port-name}	4-40
SHoW PORTAuth TIMer PORT={ALL port-name}	4-47
SHoW PPP NAMESERVER	9-122
SHoW PPP PPPOE	9-123
SHoW PPP TEMPLATE[=template] [DEBUG]	9-124



SHOW PPP[=ppp-interface]	9-96
SHOW PPP[=ppp-interface] CONFIG	9-97
SHOW PPP[=ppp-interface] COUNT[={INTERFACE LCP MULTILINK NCP PPPOE}]	9-103
SHOW PPP[=ppp-interface] DEBUG	9-117
SHOW PPP[=ppp-interface] IDLETIMER	9-118
SHOW PPP[=ppp-interface] LIMITS	9-119
SHOW PPP[=ppp-interface] MULTILINK	9-120
SHOW PPP[=ppp-interface] TXSTATUS	9-128
SHOW PPP[=ppp-interface] UTILISATION	9-129
SHoW PRI[=instance] COnfiguration	11-135
SHoW PRI[=instance] COUnTer[={DIAGnostic INterface LINK PRI}] [CHANnel=channel] [HIStory[=interval]] [{NEAR FAR BOTH}]	11-136
SHOW PRI[=instance] CTEST	11-145
SHOW PRI[=instance] DEBUG	11-147
SHOW PRI[=instance] STATE	11-147
SHOW PRI[=instance] TEST	11-153
SHOW Q931[=interface] [CALL[=q931-call]]	11-155
SHOW Q931[=interface] SPID	11-158
SHoW RADius	1-166
SHoW RADius DEBug	1-167
SHoW RELease	1-168
SHoW RSVP	40-19
SHoW RSVP COUnTer	40-21
SHoW RSVP INterface	40-23
SHoW RSVP PATH	40-24
SHoW RSVP PROXY COUnTer	40-27
SHoW RSVP PROXY[=name]	40-25
SHoW RSVP RESV	40-28
SHoW SA USER	45-175
SHoW SA[={sa-id ALL}]	45-167
SHoW SA[=sa-id] COUnTer	45-170
SHoW SCript[=filename]	34-12
SHoW SERvice[=service-name] [TYpe={Telnet Interactive TElBin}]	21-24
SHoW SESsions	21-25
SHOW SIP GATEWAY	52-55
SHOW SIP INTERFACE=interface	52-54
SHoW SKEY [SEquence=seq_no SEED=seed_name [NUMber=value]]	1-169
SHOW SNMP	38-44
SHOW SNMP COMMUNITY=name	38-48
SHOW SNMP GROUP[=group-name]	38-49
SHOW SNMP TARGETADDR[=address-name]	38-50
SHOW SNMP TARGETPARAMS=[params-name]	38-51
SHOW SNMP USER[=user-name]	38-52
SHOW SNMP VIEW[=view-name]	38-53
SHoW SQOS	6-139
SHoW SQOS COUnTers CLASSifier[=id-list] [DIRECTION={In OUT TUNnel ALL}] [INterface=interface] [TRAfficclass=id-list]	6-140
SHoW SQOS COUnTers DAR[=id-list] [DIRECTION={In OUT TUNnel}] [INterface=interface]	6-140
SHoW SQOS COUnTers POLIcy[=id-list] [DIRECTION={In OUT TUNnel}] [INterface=interface]	6-140



SHoW SQOS COunters TRaFFicclass[={id-list DEfault SYStem}] [DIRECTION={In OUT TUNnel ALL}] [INteRface=interface]	6-140
SHoW SQOS DAR[={id-list ALL}] [FULl SUMmary] [SHOwunused={Yes No}]	6-146
SHoW SQOS DSCPMaP[={id-list ALL}] [FULl SUMmary]	6-148
SHoW SQOS INteRface[={interface ALL}]	6-150
SHoW SQOS METer[={id-list ALL}] [FULl SUMmary]	6-151
SHoW SQOS POLIcy[={id-list ALL}] [FULl SUMmary TREE] [SHOwunused={Yes No}]	6-153
SHoW SQOS RED[={id-list ALL}] [FULl SUMmary] [SHOwunused={Yes No}]	6-156
SHoW SQOS TRaFFicclass[={id-list ALL}] [FULl SUMmary] [SHOwunused={Yes No ON OFF}]	6-158
SHoW SSH [COunter]	43-16
SHoW SSH SESSions	43-23
SHoW SSH USER[=username]	43-24
SHoW SSL [COunters]	51-10
SHoW SSL SESSions	51-19
SHoW STAR MKTTransfer LOG	44-23
SHoW STAR=entity-id NETkey	44-24
SHoW STAR[=entity-id]	44-16
SHoW STAR[=entity-id] COunter	44-18
SHoW STARTup	1-170
SHoW STReam[=stream-name]	22-23
SHoW STT[=sttname]	13-7
SHoW SWItch	2-25
SHoW SWItch	3-39
SHoW SWItch COunter	2-27
SHoW SWItch COunter	3-41
SHoW SWItch DEBUg	2-29
SHoW SWItch DEBUg	3-40
SHoW SWItch FDB [ADDRESS=macadd][PORT={port-list ALL}] [STATus={STATic DYnamic}]	3-43
SHoW SWItch PORT[={port-list ALL}]	2-30
SHoW SWItch PORT[={port-list ALL}]	3-44
SHoW SWItch PORT[={port-list ALL}] COunter	3-46
SHoW SWItch QOS	2-31
SHoW SWItch QOS	3-49
SHoW SYN[=n]	7-71
SHoW SYN[=n] COunter[={INteRface SYN}]	7-73
SHoW SYStem	1-171
SHoW SYStem SErialnumber	1-173
SHoW TACacs DEBUg	1-174
SHoW TACacs SERVER	1-175
SHoW TACPlus Key	1-175
SHoW TACPlus SERVER	1-176
SHoW TACPlus TELnet	1-177
SHoW TACPlus USer	1-177
SHoW TCP[=tcB]	14-218
SHoW TDM GROup[=groupname] [INteRface=interface]	32-12
SHoW TELnet	21-26
SHoW TEST [INteRface[={ALL BAsE EXPPansion MAC}]] [COunter]	26-14
SHoW Time	1-178
SHoW TPAD[=name]	39-25
SHoW TPAD[=name] CONnections	39-27



Show TPAD[= <i>name</i>] COUNTER	39-28
Show TRAcE	14-223
SHOW TRIGGER[= <i>trigger-id</i>] [{COUNTER FUL STatus SUMmary}]	30-21
Show TTY[= <i>tty-number</i> All] [{Summary Default}]	21-27
SHOW UPNP	42-15
SHOW UPNP COUNTER	42-16
SHOW UPNP FWPolICy= <i>name</i> INTERFACE=[{ALL <i>interface</i> }]	42-18
SHOW UPNP FWPolICy= <i>name</i> INTERFACE={ALL <i>interface</i> } SUBSCRIPTIONS	42-21
Show USEr RSO	1-183
Show USER[= <i>login-name</i>] [Configuration]	1-179
Show VLAN DEBUg	2-33
Show VLAN DEBUg	3-52
Show VLAN[={ <i>vlanname</i> 1..4094 ALL}]	2-31
Show VLAN[={ <i>vlan-name</i> 1..4094 ALL}]	3-50
Show VOIP [ENGine= engine]	52-55
Show VOIP AP INTERface= <i>interface</i>	52-57
Show VOIP COUNTER [ENGine= <i>engine</i>]	52-58
Show VOIP INSTANCE	52-61
Show VOIP LOAd [ENGine= <i>engine</i>]	52-61
Show VOIP PHone INTERface= <i>interface</i>	52-62
Show VRRP[= <i>vr-identifier</i>]	47-21
SHOW X25C HUNTGROUp[= <i>huntname</i>]	12-85
SHOW X25C ROUTE	12-87
SHOW X25C TCPKEEPAliVE	12-89
SHOW X25C= <i>x25-interface</i> COUNTER	12-81
SHOW X25C= <i>x25-interface</i> STATE	12-88
SHOW X25C[= <i>x25-interface</i>]	12-80
SHOW X25C[= <i>x25-interface</i>] DTEADDRESS	12-84
SHOW X25C[= <i>x25-interface</i>] PATH	12-86
SHOW X25T CPAR[= <i>call-index</i>]	12-94
SHOW X25T[= <i>x25-interface</i>] [{CIRCUIT COUNT}]	12-90
SSH { <i>ipadd</i> <i>ipv6add</i> [% <i>interface</i>] <i>host</i> } USER= <i>username</i> {PASSword= <i>password</i> KEYid= <i>key-id</i> } [COMmand= <i>string</i>]	43-25
STop PING	14-224
STop TRAcE	14-225
TELnet { <i>ipadd</i> <i>ipv6add</i> [% <i>interface</i>] <i>host</i> }	21-31
This command creates a template for use on BGP peers.	49-57
TRAcE [{IPAddress=} <i>ipadd</i>] [ADDROnly={No OFF ON Yes}] [MAXTtl= <i>number</i>] [MINTtl= <i>number</i>] [NUMBER= <i>number</i>] [PORT=1..65535] [SCREENoutput={No OFF ON Yes}] [SOURCE= <i>ipadd</i>] [TIMEOut= <i>number</i>] [TOS=0..255]	14-225
UPLoad [METHod=TFtp] [DESTFile= <i>destfilename</i>] [File= <i>filename</i>] [SErver={ <i>hostname</i> <i>ipadd</i> <i>ipv6add</i>]}	1-186
UPLOAD [METHod=ZModem] [ASYN= <i>port</i>] [DESTFile= <i>destfilename</i>] [File= <i>filename</i>]	1-186
WAIT delay	34-14
where <i>ipadd</i> is an IP address in dotted decimal notation	23-39

